

SCons

API Documentation

November 14, 2017

Contents

Contents	1
1 Package SCons	2
1.1 Modules	2
1.2 Variables	4
2 Module SCons.Action	5
2.1 Functions	6
2.2 Variables	6
2.3 Class ActionBase	6
2.3.1 Methods	7
2.3.2 Properties	7
2.4 Class CommandAction	8
2.4.1 Methods	8
2.4.2 Properties	9
2.5 Class CommandGeneratorAction	9
2.5.1 Methods	10
2.5.2 Properties	11
2.6 Class LazyAction	11
2.6.1 Methods	12
2.6.2 Properties	13
2.7 Class FunctionAction	13
2.7.1 Methods	13
2.7.2 Properties	14
2.8 Class ListAction	14
2.8.1 Methods	15
2.8.2 Properties	16
2.9 Class ActionCaller	16
2.9.1 Methods	16
2.9.2 Properties	17
2.10 Class ActionFactory	17
2.10.1 Methods	17
2.10.2 Properties	18
3 Module SCons.Builder	19
3.1 Functions	20
3.2 Variables	20

3.3	Class DictCmdGenerator	21
3.3.1	Methods	21
3.3.2	Class Variables	21
3.4	Class CallableSelector	22
3.4.1	Methods	22
3.4.2	Class Variables	22
3.5	Class DictEmitter	23
3.5.1	Methods	23
3.5.2	Class Variables	23
3.6	Class ListEmitter	24
3.6.1	Methods	24
3.6.2	Properties	25
3.6.3	Class Variables	25
3.7	Class OverrideWarner	25
3.7.1	Methods	25
3.7.2	Class Variables	25
3.8	Class EmitterProxy	26
3.8.1	Methods	26
3.8.2	Properties	26
3.9	Class BuilderBase	27
3.9.1	Methods	27
3.9.2	Properties	29
3.10	Class CompositeBuilder	29
3.10.1	Methods	30
3.10.2	Properties	30
4	Module SCons.CacheDir	31
4.1	Functions	31
4.2	Variables	31
4.3	Class CacheDir	32
4.3.1	Methods	32
4.3.2	Properties	33
5	Module SCons.Conftest	34
5.1	Functions	34
5.2	Variables	38
6	Module SCons.Debug	39
6.1	Functions	39
6.2	Variables	40
7	Module SCons.Defaults	41
7.1	Functions	41
7.2	Variables	42
7.3	Class NullCmdGenerator	43
7.3.1	Methods	44
7.3.2	Properties	44
7.4	Class Variable_Method_Caller	44
7.4.1	Methods	45
7.4.2	Properties	45
8	Module SCons.Environment	46

8.1	Functions	46
8.2	Variables	47
8.3	Class MethodWrapper	47
8.3.1	Methods	48
8.3.2	Properties	48
8.4	Class BuilderWrapper	48
8.4.1	Methods	49
8.4.2	Properties	50
8.5	Class BuilderDict	50
8.5.1	Methods	50
8.5.2	Class Variables	50
8.6	Class SubstitutionEnvironment	51
8.6.1	Methods	51
8.6.2	Properties	54
8.7	Class Base	55
8.7.1	Methods	55
8.7.2	Properties	63
8.8	Class OverrideEnvironment	63
8.8.1	Methods	64
8.8.2	Properties	66
8.9	Class Base	66
8.9.1	Methods	67
8.9.2	Properties	75
9	Module SCons.Errors	76
9.1	Functions	76
9.2	Variables	76
9.3	Class BuildError	76
9.3.1	Methods	77
9.3.2	Properties	78
9.4	Class InternalError	78
9.4.1	Methods	78
9.4.2	Properties	78
9.5	Class UserError	79
9.5.1	Methods	79
9.5.2	Properties	79
9.6	Class StopError	80
9.6.1	Methods	80
9.6.2	Properties	80
9.7	Class EnvironmentError	80
9.7.1	Methods	81
9.7.2	Properties	81
9.8	Class MSVCErrors	81
9.8.1	Methods	81
9.8.2	Properties	82
9.9	Class ExplicitExit	82
9.9.1	Methods	82
9.9.2	Properties	83
10	Module SCons.Executor	84
10.1	Functions	84
10.2	Variables	84

10.3 Class Batch	85
10.3.1 Methods	85
10.3.2 Properties	85
10.4 Class TSList	86
10.4.1 Methods	86
10.4.2 Properties	87
10.4.3 Class Variables	87
10.5 Class TSOBJECT	88
10.5.1 Methods	88
10.5.2 Properties	88
10.6 Class Executor	88
10.6.1 Methods	89
10.6.2 Properties	92
10.7 Class NullEnvironment	93
10.7.1 Methods	93
10.7.2 Properties	93
10.8 Class Null	93
10.8.1 Methods	94
10.8.2 Properties	95
11 Module SCons.Job	96
11.1 Variables	96
11.2 Class InterruptState	96
11.2.1 Methods	96
11.2.2 Properties	97
11.3 Class Jobs	97
11.3.1 Methods	97
11.3.2 Properties	98
11.4 Class Serial	98
11.4.1 Methods	98
11.4.2 Properties	99
11.5 Class Worker	99
11.5.1 Methods	100
11.5.2 Properties	101
11.6 Class ThreadPool	101
11.6.1 Methods	101
11.6.2 Properties	102
11.7 Class Parallel	102
11.7.1 Methods	103
11.7.2 Properties	103
12 Module SCons.Memoize	104
12.1 Functions	105
12.2 Variables	106
12.3 Class Counter	106
12.3.1 Methods	106
12.3.2 Properties	107
12.4 Class CountValue	107
12.4.1 Methods	107
12.4.2 Properties	108
12.5 Class CountDict	108
12.5.1 Methods	108

12.5.2 Properties	109
13 Package SCons.Node	110
13.1 Modules	110
13.2 Functions	110
13.3 Variables	112
13.4 Class NodeInfoBase	113
13.4.1 Methods	114
13.4.2 Properties	114
13.4.3 Class Variables	114
13.5 Class BuildInfoBase	115
13.5.1 Methods	115
13.5.2 Properties	116
13.5.3 Class Variables	116
13.6 Class Node	116
13.6.1 Methods	117
13.6.2 Properties	129
13.7 Class NodeList	130
13.7.1 Methods	130
13.7.2 Properties	131
13.7.3 Class Variables	131
13.8 Class Walker	131
13.8.1 Methods	132
13.8.2 Properties	132
14 Module SCons.Node.Alias	133
14.1 Variables	133
14.2 Class AliasNameSpace	133
14.2.1 Methods	133
14.2.2 Class Variables	133
14.3 Class AliasNodeInfo	134
14.3.1 Methods	134
14.3.2 Properties	134
14.3.3 Class Variables	135
14.4 Class AliasBuildInfo	135
14.4.1 Methods	135
14.4.2 Properties	135
14.4.3 Class Variables	136
14.5 Class Alias	136
14.5.1 Methods	136
14.5.2 Properties	138
15 Module SCons.Node.FS	139
15.1 Functions	139
15.2 Variables	140
15.3 Class EntryProxyAttributeError	142
15.3.1 Methods	142
15.3.2 Properties	142
15.4 Class DiskChecker	143
15.4.1 Methods	143
15.4.2 Properties	143
15.5 Class EntryProxy	144

15.5.1	Methods	144
15.5.2	Properties	145
15.5.3	Class Variables	145
15.6	Class Base	145
15.6.1	Methods	145
15.6.2	Properties	150
15.6.3	Instance Variables	151
15.7	Class Entry	151
15.7.1	Methods	151
15.7.2	Properties	154
15.7.3	Instance Variables	154
15.8	Class LocalFS	154
15.8.1	Methods	155
15.8.2	Properties	156
15.9	Class FS	156
15.9.1	Methods	156
15.9.2	Properties	159
15.10	Class DirNodeInfo	159
15.10.1	Methods	159
15.10.2	Properties	159
15.10.3	Class Variables	160
15.11	Class DirBuildInfo	160
15.11.1	Methods	160
15.11.2	Properties	160
15.11.3	Class Variables	161
15.12	Class Dir	161
15.12.1	Methods	161
15.12.2	Properties	169
15.12.3	Instance Variables	170
15.13	Class RootDir	170
15.13.1	Methods	170
15.13.2	Properties	172
15.13.3	Instance Variables	173
15.14	Class FileInfo	173
15.14.1	Methods	173
15.14.2	Properties	174
15.14.3	Class Variables	174
15.15	Class FileBuildInfo	174
15.15.1	Methods	175
15.15.2	Properties	176
15.15.3	Class Variables	176
15.16	Class File	176
15.16.1	Methods	176
15.16.2	Properties	183
15.16.3	Class Variables	184
15.16.4	Instance Variables	184
15.17	Class FileFinder	184
15.17.1	Methods	184
15.17.2	Properties	185
16	Module SCons.Node.Python	186
16.1	Variables	186

16.2	Class ValueNodeInfo	186
16.2.1	Methods	186
16.2.2	Properties	187
16.2.3	Class Variables	187
16.3	Class ValueBuildInfo	187
16.3.1	Methods	188
16.3.2	Properties	188
16.3.3	Class Variables	188
16.4	Class Value	188
16.4.1	Methods	189
16.4.2	Properties	191
17	Module SCons.PathList	192
17.1	Functions	192
17.2	Variables	192
18	Module SCons.SConf	193
18.1	Functions	193
18.2	Variables	195
18.3	Class SConfWarning	196
18.3.1	Methods	196
18.3.2	Properties	196
18.4	Class SConfError	197
18.4.1	Methods	197
18.4.2	Properties	197
18.5	Class ConfigureDryRunError	198
18.5.1	Methods	198
18.5.2	Properties	198
18.6	Class ConfigureCacheError	199
18.6.1	Methods	199
18.6.2	Properties	199
18.7	Class SConfBuildInfo	200
18.7.1	Methods	200
18.7.2	Properties	200
18.7.3	Class Variables	201
18.8	Class Streamer	201
18.8.1	Methods	201
18.8.2	Properties	202
18.9	Class SConfBuildTask	202
18.9.1	Methods	202
18.9.2	Properties	203
18.10	Class SConfBase	204
18.10.1	Methods	204
18.10.2	Properties	206
18.11	Class CheckContext	207
18.11.1	Methods	207
18.11.2	Properties	208
19	Module SCons.SConsign	209
19.1	Functions	209
19.2	Variables	209
19.3	Class SConsignEntry	210

19.3.1	Methods	210
19.3.2	Properties	210
19.3.3	Class Variables	210
19.4	Class Base	211
19.4.1	Methods	211
19.4.2	Properties	212
19.5	Class DB	212
19.5.1	Methods	212
19.5.2	Properties	212
19.6	Class Dir	213
19.6.1	Methods	213
19.6.2	Properties	213
19.7	Class DirFile	214
19.7.1	Methods	214
19.7.2	Properties	214
19.8	Class DB	215
19.8.1	Methods	215
19.8.2	Properties	215
20	Package SCons.Scanner	216
20.1	Modules	216
20.2	Functions	216
20.3	Variables	216
20.4	Class FindPathDirs	217
20.4.1	Methods	217
20.4.2	Properties	217
20.5	Class Base	218
20.5.1	Methods	218
20.5.2	Properties	220
20.6	Class Selector	220
20.6.1	Methods	223
20.6.2	Properties	224
20.7	Class Current	224
20.7.1	Methods	226
20.7.2	Properties	227
20.8	Class Classic	227
20.8.1	Methods	229
20.8.2	Properties	230
20.9	Class ClassicCPP	230
20.9.1	Methods	231
20.9.2	Properties	231
21	Module SCons.Scanner.C	232
21.1	Functions	232
21.2	Variables	232
21.3	Class SConsCPPScanner	232
21.3.1	Methods	233
21.3.2	Properties	233
21.4	Class SConsCPPScannerWrapper	234
21.4.1	Methods	234
21.4.2	Properties	234

22	Module SCons.Scanner.D	235
22.1	Functions	235
22.2	Variables	235
22.3	Class D	235
22.3.1	Methods	237
22.3.2	Properties	238
23	Module SCons.Scanner.Dir	239
23.1	Functions	239
23.2	Variables	239
24	Module SCons.Scanner.Fortran	241
24.1	Functions	241
24.2	Variables	241
24.3	Class F90Scanner	241
24.3.1	Methods	244
24.3.2	Properties	245
25	Module SCons.Scanner.IDL	246
25.1	Functions	246
25.2	Variables	246
26	Module SCons.Scanner.LaTeX	247
26.1	Functions	247
26.2	Variables	247
26.3	Class FindENVPPathDirs	247
26.3.1	Methods	248
26.3.2	Properties	248
26.4	Class LaTeX	248
26.4.1	Methods	251
26.4.2	Properties	252
26.4.3	Class Variables	252
27	Module SCons.Scanner.Prog	254
27.1	Functions	254
27.2	Variables	254
28	Module SCons.Scanner.RC	255
28.1	Functions	255
28.2	Variables	255
29	Module SCons.Scanner.SWIG	256
29.1	Functions	256
29.2	Variables	256
30	Package SCons.Script	257
30.1	Modules	257
30.2	Functions	257
30.3	Variables	257
30.4	Class TargetList	264
30.4.1	Methods	264
30.4.2	Properties	265
30.4.3	Class Variables	265

31 Module SCons.Script.Interactive	266
31.1 Functions	266
31.2 Variables	266
31.3 Class SConsInteractiveCmd	266
31.3.1 Methods	267
31.3.2 Class Variables	268
32 Module SCons.Script.Main	269
32.1 Functions	269
32.2 Variables	270
32.3 Class SConsPrintHelpException	271
32.3.1 Methods	271
32.3.2 Properties	271
32.4 Class Progressor	272
32.4.1 Methods	272
32.4.2 Properties	272
32.4.3 Class Variables	272
32.5 Class BuildTask	273
32.5.1 Methods	273
32.5.2 Properties	275
32.5.3 Class Variables	275
32.6 Class CleanTask	275
32.6.1 Methods	276
32.6.2 Properties	277
32.7 Class QuestionTask	277
32.7.1 Methods	278
32.7.2 Properties	279
32.8 Class TreePrinter	279
32.8.1 Methods	279
32.8.2 Properties	279
32.9 Class FakeOptionParser	280
32.9.1 Methods	280
32.9.2 Properties	280
32.9.3 Class Variables	280
32.10 Class Stats	280
32.10.1 Methods	281
32.10.2 Properties	281
32.11 Class CountStats	281
32.11.1 Methods	281
32.11.2 Properties	282
32.12 Class MemStats	282
32.12.1 Methods	282
32.12.2 Properties	282
33 Module SCons.Script.SConscript'	283
33.1 Functions	283
33.2 Variables	284
33.3 Class SConscriptReturn	284
33.3.1 Methods	284
33.3.2 Properties	285
33.4 Class Frame	285
33.4.1 Methods	285

33.4.2	Properties	285
33.5	Class SConsEnvironment	286
33.5.1	Methods	286
33.5.2	Properties	287
33.6	Class DefaultEnvironmentCall	288
33.6.1	Methods	288
33.6.2	Properties	288
34	Module SCons.Subst	289
34.1	Functions	289
34.2	Variables	290
34.3	Class Literal	291
34.3.1	Methods	291
34.3.2	Properties	292
34.4	Class SpecialAttrWrapper	292
34.4.1	Methods	292
34.4.2	Properties	293
34.5	Class CmdStringHolder	293
34.5.1	Methods	293
34.5.2	Properties	294
34.5.3	Class Variables	294
34.6	Class NLWrapper	295
34.6.1	Methods	295
34.6.2	Properties	295
34.7	Class Targets_or_Sources	296
34.7.1	Methods	296
34.7.2	Properties	297
34.7.3	Class Variables	297
34.8	Class Target_or_Source	298
34.8.1	Methods	298
34.8.2	Properties	298
34.9	Class NullNodeList	299
34.9.1	Methods	299
34.9.2	Properties	299
35	Module SCons.Taskmaster	300
35.1	Functions	300
35.2	Variables	300
35.3	Class Stats	301
35.3.1	Methods	301
35.3.2	Properties	301
35.4	Class Task	302
35.4.1	Methods	302
35.4.2	Properties	306
35.5	Class AlwaysTask	306
35.5.1	Methods	307
35.5.2	Properties	307
35.6	Class OutOfDateTask	307
35.6.1	Methods	308
35.6.2	Properties	308
35.7	Class Taskmaster	308
35.7.1	Methods	308

35.7.2 Properties	310
36 Module SCons.Util	311
36.1 Functions	311
36.2 Variables	318
36.3 Class NodeList	319
36.3.1 Methods	320
36.3.2 Properties	321
36.3.3 Class Variables	321
36.4 Class DisplayEngine	321
36.4.1 Methods	321
36.4.2 Properties	321
36.4.3 Class Variables	321
36.5 Class Proxy	322
36.5.1 Methods	322
36.5.2 Properties	323
36.6 Class Delegate	323
36.6.1 Methods	324
36.6.2 Properties	324
36.7 Class _NoError	324
36.7.1 Methods	324
36.7.2 Properties	325
36.8 Class PlainWindowsError	325
36.8.1 Methods	325
36.8.2 Properties	326
36.9 Class PlainWindowsError	326
36.9.1 Methods	326
36.9.2 Properties	327
36.10Class CLVar	327
36.10.1Methods	328
36.10.2Properties	328
36.10.3Class Variables	329
36.11Class OrderedDict	329
36.11.1Methods	329
36.11.2Class Variables	330
36.12Class Selector	330
36.12.1Methods	330
36.12.2Class Variables	331
36.13Class LogicalLines	331
36.13.1Methods	331
36.13.2Properties	331
36.14Class UniqueList	332
36.14.1Methods	332
36.14.2Properties	335
36.14.3Class Variables	335
36.15Class Unbuffered	335
36.15.1Methods	336
36.15.2Properties	336
36.16Class Null	336
36.16.1Methods	337
36.16.2Properties	337
36.17Class NullSeq	338

36.17.1 Methods	338
36.17.2 Properties	338
37 Package SCons.Variables	339
37.1 Modules	339
37.2 Variables	339
37.3 Class Variables	339
37.3.1 Methods	340
37.3.2 Properties	342
37.3.3 Class Variables	342
38 Module SCons.Variables.BoolVariable'	343
38.1 Functions	343
39 Module SCons.Variables.EnumVariable'	344
39.1 Functions	344
40 Module SCons.Variables.ListVariable'	345
40.1 Functions	345
41 Module SCons.Variables.PackageVariable'	346
41.1 Functions	346
42 Module SCons.Variables.PathVariable'	347
42.1 Variables	347
43 Module SCons.Warnings	348
43.1 Functions	348
43.2 Variables	349
43.3 Class Warning	349
43.3.1 Methods	350
43.3.2 Properties	350
43.4 Class WarningOnByDefault	350
43.4.1 Methods	351
43.4.2 Properties	351
43.5 Class TargetNotBuiltWarning	351
43.5.1 Methods	351
43.5.2 Properties	352
43.6 Class CacheVersionWarning	352
43.6.1 Methods	352
43.6.2 Properties	353
43.7 Class CacheWriteErrorWarning	353
43.7.1 Methods	353
43.7.2 Properties	354
43.8 Class CorruptSConsignWarning	354
43.8.1 Methods	354
43.8.2 Properties	354
43.9 Class DependencyWarning	355
43.9.1 Methods	355
43.9.2 Properties	355
43.10 Class DevelopmentVersionWarning	356
43.10.1 Methods	356
43.10.2 Properties	356

43.11Class DuplicateEnvironmentWarning	357
43.11.1Methods	357
43.11.2Properties	357
43.12Class FutureReservedVariableWarning	358
43.12.1Methods	358
43.12.2Properties	358
43.13Class LinkWarning	359
43.13.1Methods	359
43.13.2Properties	359
43.14Class MisleadingKeywordsWarning	360
43.14.1Methods	360
43.14.2Properties	360
43.15Class MissingSConscriptWarning	361
43.15.1Methods	361
43.15.2Properties	361
43.16Class NoMD5ModuleWarning	362
43.16.1Methods	362
43.16.2Properties	362
43.17Class NoMetaclassSupportWarning	363
43.17.1Methods	363
43.17.2Properties	363
43.18Class NoObjectCountWarning	364
43.18.1Methods	364
43.18.2Properties	364
43.19Class NoParallelSupportWarning	365
43.19.1Methods	365
43.19.2Properties	365
43.20Class ReservedVariableWarning	366
43.20.1Methods	366
43.20.2Properties	366
43.21Class StackSizeWarning	367
43.21.1Methods	367
43.21.2Properties	367
43.22Class VisualCMissingWarning	368
43.22.1Methods	368
43.22.2Properties	368
43.23Class VisualVersionMismatch	369
43.23.1Methods	369
43.23.2Properties	369
43.24Class VisualStudioMissingWarning	370
43.24.1Methods	370
43.24.2Properties	370
43.25Class FortranCxxMixWarning	371
43.25.1Methods	371
43.25.2Properties	371
43.26Class FutureDeprecatedWarning	372
43.26.1Methods	372
43.26.2Properties	372
43.27Class DeprecatedWarning	373
43.27.1Methods	373
43.27.2Properties	373

43.28	Class MandatoryDeprecatedWarning	374
43.28.1	Methods	374
43.28.2	Properties	374
43.29	Class PythonVersionWarning	375
43.29.1	Methods	375
43.29.2	Properties	375
43.30	Class DeprecatedSourceCodeWarning	376
43.30.1	Methods	376
43.30.2	Properties	376
43.31	Class DeprecatedBuildDirWarning	377
43.31.1	Methods	377
43.31.2	Properties	377
43.32	Class TaskmasterNeedsExecuteWarning	378
43.32.1	Methods	378
43.32.2	Properties	378
43.33	Class DeprecatedCopyWarning	379
43.33.1	Methods	379
43.33.2	Properties	379
43.34	Class DeprecatedOptionsWarning	380
43.34.1	Methods	380
43.34.2	Properties	380
43.35	Class DeprecatedSourceSignaturesWarning	381
43.35.1	Methods	381
43.35.2	Properties	381
43.36	Class DeprecatedTargetSignaturesWarning	382
43.36.1	Methods	382
43.36.2	Properties	382
43.37	Class DeprecatedDebugOptionsWarning	383
43.37.1	Methods	383
43.37.2	Properties	383
43.38	Class DeprecatedSigModuleWarning	384
43.38.1	Methods	384
43.38.2	Properties	384
43.39	Class DeprecatedBuilderKeywordsWarning	385
43.39.1	Methods	385
43.39.2	Properties	385
44	Module SCons.cpp	386
44.1	Functions	386
44.2	Variables	386
44.3	Class FunctionEvaluator	387
44.3.1	Methods	387
44.3.2	Properties	387
44.4	Class PreProcessor	387
44.4.1	Methods	388
44.4.2	Properties	392
44.5	Class DumbPreProcessor	392
44.5.1	Methods	392
44.5.2	Properties	392
45	Module SCons.dblite	394
45.1	Functions	394

45.2 Variables	394
45.3 Class dblite	394
45.3.1 Methods	395
45.3.2 Properties	395
46 Module SCons.exitfuncs	396
46.1 Functions	396
46.2 Variables	396

1 Package SCons

SCons

The main package for the SCons software construction utility. **Version:** 3.0.1

Date: 2017/11/14 13:16:53

1.1 Modules

- **Action:** SCons.Action
(Section 2, p. 5)
- **Builder:** SCons.Builder
(Section 3, p. 19)
- **CacheDir:** CacheDir support
(Section 4, p. 31)
- **Conftest:** SCons.Conftest
(Section 5, p. 34)
- **Debug:** SCons.Debug
(Section 6, p. 39)
- **Defaults:** SCons.Defaults
(Section 7, p. 41)
- **Environment:** SCons.Environment
(Section 8, p. 46)
- **Errors:** SCons.Errors
(Section 9, p. 76)
- **Executor:** SCons.Executor
(Section 10, p. 84)
- **Job:** SCons.Job
(Section 11, p. 96)
- **Memoize:** Memoizer
(Section 12, p. 104)
- **Node:** SCons.Node
(Section 13, p. 110)
 - **Alias:** scons.Node.Alias
(Section 14, p. 133)
 - **FS:** scons.Node.FS
(Section 15, p. 139)
 - **Python:** scons.Node.Python
(Section 16, p. 186)
- **PathList:** SCons.PathList
(Section 17, p. 192)
- **SConf:** SCons.SConf
(Section 18, p. 193)
- **SConsign:** SCons.SConsign
(Section 19, p. 209)
- **Scanner:** SCons.Scanner
(Section 20, p. 216)
 - **C:** SCons.Scanner.C
(Section 21, p. 232)
 - **D:** SCons.Scanner.D

- (Section 22, p. 235)
 - **Dir** (Section 23, p. 239)
 - **Fortran**: SCons.Scanner.Fortran
(Section 24, p. 241)
 - **IDL**: SCons.Scanner.IDL
(Section 25, p. 246)
 - **LaTeX**: SCons.Scanner.LaTeX
(Section 26, p. 247)
 - **Prog** (Section 27, p. 254)
 - **RC**: SCons.Scanner.RC
(Section 28, p. 255)
 - **SWIG**: SCons.Scanner.SWIG
(Section 29, p. 256)
- **Script**: SCons.Script
(Section 30, p. 257)
 - **Interactive**: SCons interactive mode
(Section 31, p. 266)
 - **Main**: SCons.Script
(Section 32, p. 269)
 - **SConscript'**: SCons.Script.SConscript
(Section 33, p. 283)
- **Subst**: SCons.Subst
(Section 34, p. 289)
- **Taskmaster**: This module contains the primary interface(s) between a wrapping user interface and the SCons build engine. There are two key classes here:
(Section 35, p. 300)
- **Util**: SCons.Util
(Section 36, p. 311)
- **Variables**: engine.SCons.Variables
(Section 37, p. 339)
 - **BoolVariable** (Section ??, p. ??)
 - **BoolVariable'**: engine.SCons.Variables.BoolVariable
(Section 38, p. 343)
 - **EnumVariable** (Section ??, p. ??)
 - **EnumVariable'**: engine.SCons.Variables.EnumVariable
(Section 39, p. 344)
 - **ListVariable** (Section ??, p. ??)
 - **ListVariable'**: engine.SCons.Variables.ListVariable
(Section 40, p. 345)
 - **PackageVariable** (Section ??, p. ??)
 - **PackageVariable'**: engine.SCons.Variables.PackageVariable
(Section 41, p. 346)
 - **PathVariable** (Section ??, p. ??)
 - **PathVariable'**: SCons.Variables.PathVariable
(Section 42, p. 347)
- **Warnings**: SCons.Warnings
(Section 43, p. 348)
- **cpp**: SCons C Pre-Processor module
(Section 44, p. 386)
- **dblite** (Section 45, p. 394)
- **exitfuncs**: SCons.exitfuncs

(Section 46, p. 396)

1.2 Variables

Name	Description
__build__	Value: '74b2c53bc42290e911b334a6b44f187da698a668'
__buildsys__	Value: 'hpmicrodog'
__developer__	Value: 'bdbaddog'
__package__	Value: 'SCons'
__revision__	Value: 'src/engine/SCons/__init__.py 74b2c53bc42290e911b334a6b44...

2 Module SCons.Action

SCons.Action

This encapsulates information about executing any sort of action that can build one or more target Nodes (typically files) from one or more source Nodes (also typically files) given a specific Environment.

The base class here is ActionBase. The base class supplies just a few OO utility methods and some generic methods for displaying information about an Action in response to the various commands that control printing.

A second-level base class is `_ActionAction`. This extends ActionBase by providing the methods that can be used to show and perform an action. True Action objects will subclass `_ActionAction`; Action factory class objects will subclass ActionBase.

The heavy lifting is handled by subclasses for the different types of actions we might execute:

CommandAction CommandGeneratorAction FunctionAction ListAction

The subclasses supply the following public interface methods used by other modules:

__call__() THE public interface, "calling" an Action object executes the command or Python function. This also takes care of printing a pre-substitution command for debugging purposes.

get_contents() Fetches the "contents" of an Action for signature calculation plus the varlist. This is what gets MD5 checksummed to decide if a target needs to be rebuilt because its action changed.

genstring() Returns a string representation of the Action *without* command substitution, but allows a CommandGeneratorAction to generate the right action based on the specified target, source and env. This is used by the Signature subsystem (through the Executor) to obtain an (imprecise) representation of the Action operation for informative purposes.

Subclasses also supply the following methods for internal use within this module:

__str__() Returns a string approximation of the Action; no variable substitution is performed.

execute() The internal method that really, truly, actually handles the execution of a command or Python function. This is used so that the `__call__()` methods can take care of displaying any pre-substitution representations, and *then* execute an action without worrying about the specific Actions involved.

get_presig() Fetches the "contents" of a subclass for signature calculation. The varlist is added to this to produce the Action's contents. TODO(?): Change this to always return ascii/bytes and not unicode (or py3 strings)

strfunction() Returns a substituted string representation of the Action. This is used by the `_ActionAction.show()` command to display the command/function that will be executed to generate the target(s).

There is a related independent ActionCaller class that looks like a regular Action, and which serves as a wrapper for arbitrary functions that we want to let the user specify the arguments to now, but actually execute later (when an out-of-date check determines that it's needed to be executed, for example). Objects

of this class are returned by an *ActionFactory* class that provides a `__call__()` method as a convenient way for wrapping up the functions.

2.1 Functions

rfile(*n*)

default_exitstatfunc(*s*)

Action(*act*, **args*, ***kw*)

A factory for action objects.

get_default_ENV(*env*)

A fiddlin' little function that has an 'import SCons.Environment' which can't be moved to the top level without creating an import loop. Since this import creates a local variable named 'SCons', it blocks access to the global variable, so we move it here to prevent complaints about local variables being used uninitialized.

2.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Action.py 74b2c53bc42290e911b334a6b44f1...
<code>print_actions</code>	Value: 1
<code>execute_actions</code>	Value: 1
<code>print_actions_presub</code>	Value: 0
<code>ACTION_SIGNATURE_PICTURE_PROTOCOL</code>	Value: 1
<code>strip_quotes</code>	Value: <code>re.compile(r'^(\\')(.*)[\\']\$')</code>
<code>default_ENV</code>	Value: None
<code>__package__</code>	Value: 'SCons'

2.3 Class *ActionBase*

object  **SCons.Action.ActionBase**

Known Subclasses: *SCons.Action._ActionAction*, *SCons.Action.CommandGeneratorAction*, *SCons.Action.ListAction*

Base class for all types of action objects that can be held by other objects (Builders, Executors, etc.) This provides the common methods for manipulating and combining those actions.

2.3.1 Methods

<code>__eq__(self, other)</code>

<code>no_batch_key(self, env, target, source)</code>
--

<code>batch_key(self, env, target, source)</code>

<code>genstring(self, target, source, env)</code>

<code>get_contents(self, target, source, env)</code>
--

<code>__add__(self, other)</code>

<code>__radd__(self, other)</code>

<code>presub_lines(self, env)</code>

<code>get_varlist(self, target, source, env, executor=None)</code>
--

<code>get_targets(self, env, executor)</code>

Returns the type of targets (\$TARGETS, \$CHANGED_TARGETS) used by this action.


Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__init__()`,
`__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`,
`__sizeof__()`, `__str__()`, `__subclasshook__()`

2.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

2.4 Class `CommandAction`



Known Subclasses: `SCons.Action.LazyAction`

Class for command-execution actions.

2.4.1 Methods

`__init__`(*self*, *cmd*, ***kw*)

x.**`__init__`**(...) initializes *x*; see `help(type(x))` for signature Overrides:
`object.__init__` `exitit`(inherited documentation)

`__str__`(*self*)

`str(x)` Overrides: `object.__str__` `exitit`(inherited documentation)

`process`(*self*, *target*, *source*, *env*, *executor=None*)

`strfunction`(*self*, *target*, *source*, *env*, *executor=None*)

`execute`(*self*, *target*, *source*, *env*, *executor=None*)

Execute a command action.

This will handle lists of commands as well as individual commands, because construction variable substitution may turn a single "command" into a list. This means that this class can actually handle lists of commands, even though that's not how we use it externally.

```
get_presig(self, target, source, env, executor=None)
```

Return the signature contents of this action’s command line.

This strips `$(-$)` and everything in between the string, since those parts don’t affect signatures.

```
get_implicit_deps(self, target, source, env, executor=None)
```

Inherited from `SCons.Action._ActionAction`

```
__call__(), print_cmd_line()
```

Inherited from `SCons.Action.ActionBase` (Section 2.3)

```
__add__(), __eq__(), __radd__(), batch_key(), genstring(), get_contents(),
get_targets(), get_varlist(), no_batch_key(), presub_lines()
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__subclasshook__()
```

2.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

2.5 Class `CommandGeneratorAction`



Known Subclasses: `SCons.Action.LazyAction`

Class for command-generator actions.

2.5.1 Methods

__init__(*self*, *generator*, *kw*)

x.**__init__**(...) initializes *x*; see `help(type(x))` for signature Overrides: `object.__init__` `exitit`(inherited documentation)

__str__(*self*)

`str(x)` Overrides: `object.__str__` `exitit`(inherited documentation)

batch_key(*self*, *env*, *target*, *source*)

Overrides: `SCons.Action.ActionBase.batch_key`

genstring(*self*, *target*, *source*, *env*, *executor*=None)

Overrides: `SCons.Action.ActionBase.genstring`

__call__(*self*, *target*, *source*, *env*, *exitstatfunc*=<class 'SCons.Action._null'>, *presub*=<class 'SCons.Action._null'>, *show*=<class 'SCons.Action._null'>, *execute*=<class 'SCons.Action._null'>, *chdir*=<class 'SCons.Action._null'>, *executor*=None)

get_presig(*self*, *target*, *source*, *env*, *executor*=None)

Return the signature contents of this action's command line.

This strips `$(-$)` and everything in between the string, since those parts don't affect signatures.

get_implicit_deps(*self*, *target*, *source*, *env*, *executor*=None)

get_varlist(*self*, *target*, *source*, *env*, *executor*=None)

Overrides: `SCons.Action.ActionBase.get_varlist`

get_targets(*self*, *env*, *executor*)

Returns the type of targets (`$TARGETS`, `$CHANGED_TARGETS`) used by this action. Overrides: `SCons.Action.ActionBase.get_targets` `exitit`(inherited documentation)

Inherited from SCons.Action.ActionBase(Section 2.3)


`__add__()`, `__eq__()`, `__radd__()`, `get_contents()`, `no_batch_key()`, `presub_lines()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__subclasshook__()`

2.5.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

2.6 Class LazyAction

A `LazyAction` is a kind of hybrid generator and command action for strings of the form "\$VAR". These strings normally expand to other strings (think "\$CCCOM" to "\$CC -c -o \$TARGET \$SOURCE"), but we also want to be able to replace them with functions in the construction environment. Consequently, we want lazy evaluation and creation of an Action in the case of the function, but that's overkill in the more normal case of expansion to other strings.

So we do this with a subclass that's both a generator *and* a command action. The overridden methods all do a quick check of the construction variable, and if it's a string we just call the corresponding `CommandAction` method to do the heavy lifting. If not, then we call the same-

named `CommandGeneratorAction` method. The `CommandGeneratorAction` methods work by using the overridden `__generate()` method, that is, our own way of handling "generation" of an action based on what's in the construction variable.

2.6.1 Methods

`__init__(self, var, kw)`

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides: `object.__init__` `exitit`(inherited documentation)

`get_parent_class(self, env)`

`__call__(self, target, source, env, *args, **kw)`

Overrides: `SCons.Action._ActionAction.__call__`

`get_presig(self, target, source, env)`

Return the signature contents of this action's command line.

This strips `$(-$)` and everything in between the string, since those parts don't affect signatures. Overrides: `SCons.Action.CommandAction.get_presig` `exitit`(inherited documentation)

`get_varlist(self, target, source, env, executor=None)`

Overrides: `SCons.Action.ActionBase.get_varlist`

Inherited from `SCons.Action.CommandGeneratorAction`(Section 2.5)

`__str__()`, `batch_key()`, `genstring()`, `get_implicit_deps()`, `get_targets()`

Inherited from `SCons.Action.CommandAction`(Section 2.4)

`execute()`, `process()`, `strfunction()`

Inherited from `SCons.Action._ActionAction`

`print_cmd_line()`

Inherited from `SCons.Action.ActionBase`(Section 2.3)

`__add__()`, `__eq__()`, `__radd__()`, `get_contents()`, `no_batch_key()`, `presub_lines()`

Inherited from object


`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,

`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__subclasshook__()`

2.6.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

2.7 Class `FunctionAction`



Class for Python function actions.

2.7.1 Methods

<code>__init__</code> (<i>self</i> , <i>execfunction</i> , <i>kw</i>) x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature Overrides: object. <code>__init__</code> <code>exitit</code> (inherited documentation)
<code>function_name</code> (<i>self</i>)
<code>strfunction</code> (<i>self</i> , <i>target</i> , <i>source</i> , <i>env</i> , <i>executor</i> =None)
<code>__str__</code> (<i>self</i>) str(x) Overrides: object. <code>__str__</code> <code>exitit</code> (inherited documentation)
<code>execute</code> (<i>self</i> , <i>target</i> , <i>source</i> , <i>env</i> , <i>executor</i> =None)

get_presig (<i>self</i> , <i>target</i> , <i>source</i> , <i>env</i>)
--

Return the signature contents of this callable action.
--

get_implicit_deps (<i>self</i> , <i>target</i> , <i>source</i> , <i>env</i>)

Inherited from SCons.Action.__ActionAction

__call__(), print_cmd_line()

Inherited from SCons.Action.ActionBase(Section 2.3)

__add__(), __eq__(), __radd__(), batch_key(), genstring(), get_contents(),
get_targets(), get_varlist(), no_batch_key(), presub_lines()


Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__subclasshook__()

2.7.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

2.8 Class ListAction



Class for lists of other actions.

2.8.1 Methods

__init__(*self*, *actionlist*)

x.**__init__**(...) initializes *x*; see `help(type(x))` for signature Overrides: `object.__init__` `exitit`(inherited documentation)

genstring(*self*, *target*, *source*, *env*)

Overrides: `SCons.Action.ActionBase.genstring`

__str__(*self*)

`str(x)` Overrides: `object.__str__` `exitit`(inherited documentation)

presub_lines(*self*, *env*)

Overrides: `SCons.Action.ActionBase.presub_lines`

get_presig(*self*, *target*, *source*, *env*)

Return the signature contents of this action list.

Simple concatenation of the signatures of the elements.

__call__(*self*, *target*, *source*, *env*, *exitstatfunc*=<class 'SCons.Action._null'>, *presub*=<class 'SCons.Action._null'>, *show*=<class 'SCons.Action._null'>, *execute*=<class 'SCons.Action._null'>, *chdir*=<class 'SCons.Action._null'>, *executor*=None)

get_implicit_deps(*self*, *target*, *source*, *env*)

get_varlist(*self*, *target*, *source*, *env*, *executor*=None)

Overrides: `SCons.Action.ActionBase.get_varlist`

Inherited from SCons.Action.ActionBase(Section 2.3)

`__add__`(), `__eq__`(), `__radd__`(), `batch_key`(), `get_contents`(), `get_targets`(), `no_batch_key`()

Inherited from object

`__delattr__`(), `__format__`(), `__getattr__`(), `__hash__`(), `__new__`(),

```
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__subclasshook__()
```

2.8.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

2.9 Class ActionCaller

```
object └─ SCons.Action.ActionCaller
```

A class for delaying calling an Action function with specific (positional and keyword) arguments until the Action is actually executed.

This class looks to the rest of the world like a normal Action object, but what it's really doing is hanging on to the arguments until we have a target, source and env to use for the expansion.

2.9.1 Methods

```
__init__(self, parent, args, kw)
```

x.__init__(...) initializes x; see help(type(x)) for signature Overrides:
object.__init__ extit(inherited documentation)

```
get_contents(self, target, source, env)
```

```
subst(self, s, target, source, env)
```

```
subst_args(self, target, source, env)
```

```
subst_kw(self, target, source, env)
```

```
__call__(self, target, source, env, executor=None)
```

```
strfunction(self, target, source, env)
```

<pre>__str__(self) str(x) Overrides: object.__str__ extit(inherited documentation)</pre>

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__subclasshook__()
```

2.9.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

2.10 Class ActionFactory

A factory class that will wrap up an arbitrary function as an SCons-executable Action object.

The real heavy lifting here is done by the ActionCaller class. We just collect the (positional and keyword) arguments that we're called with and give them to the ActionCaller object we create, so it can hang onto them until it needs them.

2.10.1 Methods

<pre>__init__(self, actfunc, strfunc, convert=<function <lambda> at 0x7f2c43d9aed8>) x.__init__(...) initializes x; see help(type(x)) for signature Overrides: object.__init__ extit(inherited documentation)</pre>
--

<pre>__call__(self, *args, **kw)</pre>
--

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```


2.10.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

3 Module **SCons.Builder**

SCons.Builder

Builder object subsystem.

A Builder object is a callable that encapsulates information about how to execute actions to create a target Node (file) from source Nodes (files), and how to create those dependencies for tracking.

The main entry point here is the Builder() factory method. This provides a procedural interface that creates the right underlying Builder object based on the keyword arguments supplied and the types of the arguments.

The goal is for this external interface to be simple enough that the vast majority of users can create new Builders as necessary to support building new types of files in their configurations, without having to dive any deeper into this subsystem.

The base class here is BuilderBase. This is a concrete base class which does, in fact, represent the Builder objects that we (or users) create.

There is also a proxy that looks like a Builder:

CompositeBuilder

This proxies for a Builder with an action that is actually a dictionary that knows how to map file suffixes to a specific action. This is so that we can invoke different actions (compilers, compile options) for different flavors of source files.

Builders and their proxies have the following public interface methods used by other modules:

- **__call__()** THE public interface. Calling a Builder object (with the use of internal helper methods) sets up the target and source dependencies, appropriate mapping to a specific action, and the environment manipulation necessary for overridden construction variable. This also takes care of warning about possible mistakes in keyword arguments.
- **add_emitter()** Adds an emitter for a specific file suffix, used by some Tool modules to specify that (for example) a yacc invocation on a .y can create a .h *and* a .c file.
- **add_action()** Adds an action for a specific file suffix, heavily used by Tool modules to add their specific action(s) for turning a source file into an object file to the global static and shared object file Builders.

There are the following methods for internal use within this module:

- **__execute()** The internal method that handles the heavily lifting when a

Builder is called. This is used so that the `__call__()` methods can set up warning about possible mistakes in keyword-argument overrides, and *then* execute all of the steps necessary so that the warnings only occur once.

- **get_name()** Returns the Builder's name within a specific Environment, primarily used to try to return helpful information in error messages.
- **adjust_suffix()**
- **get_prefix()**
- **get_suffix()**
- **get_src_suffix()**
- **set_src_suffix()** Miscellaneous stuff for handling the prefix and suffix manipulation we use in turning source file names into target file names.

3.1 Functions

match_splitext (<i>path</i> , <i>suffixes</i> =[])
--

Builder (** <i>kw</i>)

A factory for builder objects.

is_a_Builder (<i>obj</i>)


"Returns True if the specified obj is one of our Builder classes.

The test is complicated a bit by the fact that CompositeBuilder is a proxy, not a subclass of BuilderBase.
--

3.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Builder.py 74b2c53bc42290e911b334a6b44f...
<code>misleading_keywords</code>	Value: {'sources': 'source', 'targets': 'target'}
<code>__package__</code>	Value: 'SCons'

3.3 Class DictCmdGenerator



This is a callable class that can be used as a command generator function. It holds on to a dictionary mapping file suffixes to Actions. It uses that dictionary to return the proper action based on the file suffix of the source file.

3.3.1 Methods

<code>__init__(self, dict=None, source_ext_match=1)</code>
--

Overrides: UserDict.UserDict.__init__

<code>src_suffixes(self)</code>

<code>add_action(self, suffix, action)</code>

Add a suffix-action pair to the mapping.
--

<code>__call__(self, target, source, env, for_signature)</code>

Overrides: SCons.Util.Selector.__call__

Inherited from SCons.Util.OrderedDict(Section 36.11)

`__delitem__()`, `__setitem__()`, `clear()`, `copy()`, `items()`, `keys()`, `popitem()`, `setdefault()`, `update()`, `values()`

Inherited from UserDict.UserDict

`__cmp__()`, `__contains__()`, `__getitem__()`, `__len__()`, `__repr__()`, `fromkeys()`, `get()`, `has_key()`, `iteritems()`, `iterkeys()`, `itervalues()`, `pop()`


3.3.2 Class Variables

Name	Description
<i>Inherited from UserDict.UserDict</i>	

continued on next page

Name	Description
<code>__hash__</code>	

3.4 Class CallableSelector



A callable dictionary that will, in turn, call the value it finds if it can.

3.4.1 Methods

<code>__call__(self, env, source)</code>
--

Overrides: <code>SCons.Util.Selector.__call__</code>
--

Inherited from SCons.Util.OrderedDict(Section 36.11)

`__delitem__()`, `__init__()`, `__setitem__()`, `clear()`, `copy()`, `items()`, `keys()`, `popitem()`, `setdefault()`, `update()`, `values()`


Inherited from UserDict.UserDict

`__cmp__()`, `__contains__()`, `__getitem__()`, `__len__()`, `__repr__()`, `fromkeys()`, `get()`, `has_key()`, `iteritems()`, `iterkeys()`, `itervalues()`, `pop()`

3.4.2 Class Variables

Name	Description
<i>Inherited from UserDict.UserDict</i>	
<code>__hash__</code>	

3.5 Class DictEmitter



A callable dictionary that maps file suffixes to emitters. When called, it finds the right emitter in its dictionary for the suffix of the first source file, and calls that emitter to get the right lists of targets and sources to return. If there's no emitter for the suffix in its dictionary, the original target and source are returned.

3.5.1 Methods

__call__ (<i>self</i> , <i>target</i> , <i>source</i> , <i>env</i>)
--

Overrides: SCons.Util.Selector.__call__

Inherited from SCons.Util.OrderedDict(Section 36.11)

__delitem__(), __init__(), __setitem__(), clear(), copy(), items(), keys(),
popitem(), setdefault(), update(), values()


Inherited from UserDict.UserDict

__cmp__(), __contains__(), __getitem__(), __len__(), __repr__(), fromkeys(),
get(), has_key(), iteritems(), iterkeys(), itervalues(), pop()

3.5.2 Class Variables

Name	Description
<i>Inherited from UserDict.UserDict</i>	
__hash__	

3.6 Class **ListEmitter**



A callable list of emitters that calls each in sequence, returning the result.

3.6.1 Methods

<code>__call__(self, target, source, env)</code>
--

*Inherited from **UserList.UserList***

`__add__()`, `__cmp__()`, `__contains__()`, `__delitem__()`, `__delslice__()`, `__eq__()`, `__ge__()`, `__getitem__()`, `__getslice__()`, `__gt__()`, `__iadd__()`, `__imul__()`, `__init__()`, `__le__()`, `__len__()`, `__lt__()`, `__mul__()`, `__ne__()`, `__radd__()`, `__repr__()`, `__rmul__()`, `__setitem__()`, `__setslice__()`, `append()`, `count()`, `extend()`, `index()`, `insert()`, `pop()`, `remove()`, `reverse()`, `sort()`

*Inherited from **__abcoll.Sequence***

`__iter__()`, `__reversed__()`

*Inherited from **__abcoll.Sized***

`__subclasshook__()`

*Inherited from **object***

`__delattr__()`, `__format__()`, `__getattr__()`, `__new__()`, `__reduce__()`,

`__reduce_ex__()`, `__setattr__()`, `__sizeof__()`, `__str__()`

3.6.2 Properties

Name	Description
<code>__class__</code>	<i>Inherited from object</i>

3.6.3 Class Variables

Name	Description
<code>__abstractmethods__</code> , <code>__hash__</code>	<i>Inherited from UserList.UserList</i>

3.7 Class OverrideWarner

UserDict.UserDict —
SCons.Builder.OverrideWarner

A class for warning about keyword arguments that we use as overrides in a Builder call.

This class exists to handle the fact that a single Builder call can actually invoke multiple builders. This class only emits the warnings once, no matter how many Builders are invoked.

3.7.1 Methods

`__init__(self, dict)`

Overrides: UserDict.UserDict.`__init__`

`warn(self)`

Inherited from UserDict.UserDict

`__cmp__()`, `__contains__()`, `__delitem__()`, `__getitem__()`, `__len__()`,
`__repr__()`, `__setitem__()`, `clear()`, `copy()`, `fromkeys()`, `get()`, `has_key()`, `items()`,
`iteritems()`, `iterkeys()`, `itervalues()`, `keys()`, `pop()`, `popitem()`, `setdefault()`, `update()`,
`values()`

3.7.2 Class Variables

Name	Description
<i>Inherited from UserDict.UserDict</i>	
__hash__	

3.8 Class EmitterProxy

object —
SCons.Builder.EmitterProxy

This is a callable class that can act as a Builder emitter. It holds on to a string that is a key into an Environment dictionary, and will look there at actual build time to see if it holds a callable. If so, we will call that as the actual emitter.

3.8.1 Methods

__init__ (<i>self</i> , <i>var</i>)
x. __init__ (...) initializes x; see help(type(x)) for signature Overrides: object. __init__ extit(inherited documentation)
__call__ (<i>self</i> , <i>target</i> , <i>source</i> , <i>env</i>)
__eq__ (<i>self</i> , <i>other</i>)
__lt__ (<i>self</i> , <i>other</i>)

Inherited from object

__delattr__(), **__format__**(), **__getattr__**(), **__hash__**(), **__new__**(),
__reduce__(), **__reduce_ex__**(), **__repr__**(), **__setattr__**(), **__sizeof__**(),
__str__(), **__subclasshook__**()

3.8.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

3.9 Class BuilderBase



Base class for Builders, objects that create output nodes (files) from input nodes (files).

3.9.1 Methods

```

__init__(self, action=None, prefix='', suffix='', src_suffix='',
target_factory=None, source_factory=None, target_scanner=None,
source_scanner=None, emitter=None, multi=0, env=None, single_source=0,
name=None, chdir=<class 'SCons.Builder._Null'>, is_explicit=1,
src_builder=None, ensure_suffix=False, **overrides)

```

x.__init__(...) initializes x; see help(type(x)) for signature Overrides:
 object.__init__ extit(inherited documentation)

```
__nonzero__(self)
```

```
__bool__(self)
```

```
get_name(self, env)
```

Attempts to get the name of the Builder.

Look at the BUILDERS variable of env, expecting it to be a dictionary containing this Builder, and return the key of the dictionary. If there's no key, then return a directly-configured name (if there is one) or the name of the class (by default).

```
__eq__(self, other)
```

```
splitext(self, path, env=None)
```

```
__call__(self, env, target=None, source=None, chdir=<class
'SCons.Builder._Null'>, **kw)
```

```
adjust_suffix(self, suff)
```

```
get_prefix(self, env, sources=[])
```

```
set_suffix(self, suffix)
```

```
get_suffix(self, env, sources=[])
```

```
set_src_suffix(self, src_suffix)
```

```
get_src_suffix(self, env)
```

Get the first `src_suffix` in the list of `src_suffixes`.

```
add_emitter(self, suffix, emitter)
```

Add a suffix-emitter mapping to this Builder.

This assumes that emitter has been initialized with an appropriate dictionary type, and will throw a `TypeError` if not, so the caller is responsible for knowing that this is an appropriate method to call for the Builder in question.

```
add_src_builder(self, builder)
```

Add a new Builder to the list of `src_builders`.

This requires wiping out cached values so that the computed lists of source suffixes get re-calculated.

```
src_builder_sources(self, env, source, overwarn={})
```

```
get_src_builders(self, env)
```

Returns the list of source Builders for this Builder.

This exists mainly to look up Builders referenced as strings in the 'BUILDER' variable of the construction environment and cache the result.

```
subst_src_suffixes(self, env)
```

The suffix list may contain construction variable expansions, so we have to evaluate the individual strings. To avoid doing this over and over, we memoize the results for each construction environment.

```
src_suffixes(self, env)
```

Returns the list of source suffixes for all src_builders of this Builder.

This is essentially a recursive descent of the src_builder "tree." (This value isn't cached because there may be changes in a src_builder many levels deep that we can't see.)

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

3.9.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

3.10 Class CompositeBuilder



A Builder Proxy whose main purpose is to always have a DictCmdGenerator as its action, and to provide access to the DictCmdGenerator's add_action() method.

3.10.1 Methods

__init__(*self, builder, cmdgen*)

Wrap an object as a Proxy object. Overrides: object.__init__ extit(inherited documentation)

__call__(...)

A Python Descriptor class that delegates attribute fetches to an underlying wrapped subject of a Proxy. Typical use:

```
class Foo(Proxy): __str__ = Delegate('__str__')
```

add_action(*self, suffix, action*)

Inherited from SCons.Util.Proxy(Section 36.5)

__eq__(), __getattr__(), get()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

3.10.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

4 Module *SCons.CacheDir*

CacheDir support

4.1 Functions

CacheRetrieveFunc (<i>target, source, env</i>)

CacheRetrieveString (<i>target, source, env</i>)

CachePushFunc (<i>target, source, env</i>)

4.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/CacheDir.py 74b2c53bc42290e911b334a6b44...
<code>__doc__</code>	Value: ...
<code>cache_enabled</code>	Value: True
<code>cache_debug</code>	Value: False
<code>cache_force</code>	Value: False
<code>cache_show</code>	Value: False
<code>cache_readonly</code>	Value: False
<code>CacheRetrieve</code>	Value: <code>SCons.Action.Action(CacheRetrieveFunc, CacheRetrieveString)</code>
<code>CacheRetrieveSilent</code>	Value: <code>SCons.Action.Action(CacheRetrieveFunc, None)</code>
<code>CachePush</code>	Value: <code>SCons.Action.Action(CachePushFunc, None)</code>
<code>warned</code>	Value: {}
<code>__package__</code>	Value: 'SCons'

4.3 Class *CacheDir*



4.3.1 Methods

__init__(*self*, *path*)

x.**__init__**(...) initializes *x*; see `help(type(x))` for signature Overrides: `object.__init__` `exitit`(inherited documentation)

CacheDebug(*self*, *fmt*, *target*, *cachefile*)

is_enabled(*self*)

is_readonly(*self*)

cachepath(*self*, *node*)

retrieve(*self*, *node*)

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in `built()`.

Note that there's a special trick here with the execute flag (one that's not normally done for other actions). Basically if the user requested a `no_exec` (-n) build, then `SCons.Action.execute_actions` is set to 0 and when any action is called, it does its showing but then just returns zero instead of actually calling the action execution operation. The problem for caching is that if the file does NOT exist in cache then the `CacheRetrieveString` won't return anything to show for the task, but the `Action.__call__` won't call `CacheRetrieveFunc`; instead it just returns zero, which makes the code below think that the file *was* successfully retrieved from the cache, therefore it doesn't do any subsequent building. However, the `CacheRetrieveString` didn't print anything because it didn't actually exist in the cache, and no more build actions will be performed, so the user just sees nothing. The fix is to tell `Action.__call__` to always execute the `CacheRetrieveFunc` and then have the latter explicitly check `SCons.Action.execute_actions` itself.

push (<i>self</i> , <i>node</i>)

push_if_forced (<i>self</i> , <i>node</i>)

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

4.3.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

5 Module **SCons.Conftest**

SCons.Conftest

Autoconf-like configuration support; low level implementation of tests.

5.1 Functions

CheckBuilder(*context*, *text*=None, *language*=None)

Configure check to see if the compiler works. Note that this uses the current value of compiler and linker flags, make sure \$CFLAGS, \$CPPFLAGS and \$LIBS are set correctly. "language" should be "C" or "C++" and is used to select the compiler. Default is "C". "text" may be used to specify the code to be build. Returns an empty string for success, an error message for failure.

CheckCC(*context*)

Configure check for a working C compiler.

This checks whether the C compiler, as defined in the \$CC construction variable, can compile a C source file. It uses the current \$CCCOM value too, so that it can test against non working flags.

CheckSHCC(*context*)

Configure check for a working shared C compiler.

This checks whether the C compiler, as defined in the \$SHCC construction variable, can compile a C source file. It uses the current \$SHCCCOM value too, so that it can test against non working flags.

CheckCXX(*context*)

Configure check for a working CXX compiler.

This checks whether the CXX compiler, as defined in the \$CXX construction variable, can compile a CXX source file. It uses the current \$CXXCOM value too, so that it can test against non working flags.

CheckSHCXX(*context*)

Configure check for a working shared CXX compiler.

This checks whether the CXX compiler, as defined in the \$SHCXX construction variable, can compile a CXX source file. It uses the current \$SHCXXCOM value too, so that it can test against non working flags.

CheckFunc(*context*, *function_name*, *header*=None, *language*=None)

Configure check for a function "function_name". "language" should be "C" or "C++" and is used to select the compiler. Default is "C". Optional "header" can be defined to define a function prototype, include a header file or anything else that comes before main(). Sets HAVE_function_name in context.havedict according to the result. Note that this uses the current value of compiler and linker flags, make sure \$CFLAGS, \$CPPFLAGS and \$LIBS are set correctly. Returns an empty string for success, an error message for failure.

CheckHeader(*context*, *header_name*, *header*=None, *language*=None, *include_quotes*=None)

Configure check for a C or C++ header file "header_name". Optional "header" can be defined to do something before including the header file (unusual, supported for consistency). "language" should be "C" or "C++" and is used to select the compiler. Default is "C". Sets HAVE_header_name in context.havedict according to the result. Note that this uses the current value of compiler and linker flags, make sure \$CFLAGS and \$CPPFLAGS are set correctly. Returns an empty string for success, an error message for failure.

CheckType(*context*, *type_name*, *fallback*=None, *header*=None, *language*=None)

Configure check for a C or C++ type "*type_name*". Optional "*header*" can be defined to include a header file. "*language*" should be "C" or "C++" and is used to select the compiler. Default is "C". Sets HAVE_*type_name* in *context*.havedict according to the result. Note that this uses the current value of compiler and linker flags, make sure \$CFLAGS, \$CPPFLAGS and \$LIBS are set correctly. Returns an empty string for success, an error message for failure.

CheckTypeSize(*context*, *type_name*, *header*=None, *language*=None, *expect*=None)

This check can be used to get the size of a given type, or to check whether the type is of expected size.

Arguments:

- **type** (**str**)
the type to check
- **includes** (**sequence**)
list of headers to include in the test code before testing the type
- **language** (**str**)
'C' or 'C++'
- **expect** (**int**)
if given, will test whether the type has the given number of bytes.
If not given, will automatically find the size.

Returns:

- status** (**int**)
0 if the check failed, or the found size of the type if the check succeeded.

CheckDeclaration(*context*, *symbol*, *includes*=None, *language*=None)

Checks whether symbol is declared.

Use the same test as `autoconf`, that is test whether the symbol is defined as a macro or can be used as an r-value.

Arguments:

symbol (**str**)

the symbol to check

includes (**str**)

Optional "header" can be defined to include a header file.

language (**str**)

only C and C++ supported.

Returns:

status (**bool**)

True if the check failed, False if succeeded.

CheckLib(*context*, *libs*, *func_name*=None, *header*=None, *extra_libs*=None, *call*=None, *language*=None, *autoadd*=1, *append*=True)

Configure check for a C or C++ libraries "libs". Searches through the list of libraries, until one is found where the test succeeds. Tests if "func_name" or "call" exists in the library. Note: if it exists in another library the test succeeds anyway! Optional "header" can be defined to include a header file. If not given a default prototype for "func_name" is added. Optional "extra_libs" is a list of library names to be added after "lib_name" in the build command. To be used for libraries that "lib_name" depends on. Optional "call" replaces the call to "func_name" in the test code. It must consist of complete C statements, including a trailing ";". Both "func_name" and "call" arguments are optional, and in that case, just linking against the libs is tested. "language" should be "C" or "C++" and is used to select the compiler. Default is "C". Note that this uses the current value of compiler and linker flags, make sure \$CFLAGS, \$CPPFLAGS and \$LIBS are set correctly. Returns an empty string for success, an error message for failure.

CheckProg(*context*, *prog_name*)

Configure check for a specific program.

Check whether program *prog_name* exists in path. If it is found, returns the path for it, otherwise returns None.

5.2 Variables

Name	Description
LogInputFiles	Value: 1
LogErrorMessages	Value: 1
__package__	Value: 'SCons'

6 Module SCons.Debug

SCons.Debug

Code for debugging SCons internal things. Shouldn't be needed by most users. Quick shortcuts:

```
from SCons.Debug import caller_trace caller_trace()
```

6.1 Functions

```
logInstanceCreation(instance, name=None)
```

```
string__to__classes(s)
```

```
fetchLoggedInstances(classes='*')
```

```
countLoggedInstances(classes, file=sys.stderr)
```

```
listLoggedInstances(classes, file=sys.stderr)
```

```
dumpLoggedInstances(classes, file=sys.stderr)
```

```
memory()
```

```
caller_stack()
```

```
caller_trace(back=0)
```

Trace caller stack and save info into global dicts, which are printed automatically at the end of SCons execution.

```
dump_caller_counts(file=sys.stderr)
```

```
func_shorten(func_tuple)
```

```
Trace(msg, file=None, mode='w', tstamp=None)
```

Write a trace message to a file. Whenever a file is specified, it becomes the default for the next call to `Trace()`.

6.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Debug.py 74b2c53bc42290e911b334a6b44f18...
<code>track_instances</code>	Value: False
<code>tracked_classes</code>	Value: {}
<code>caller_bases</code>	Value: {}
<code>caller_dicts</code>	Value: {}
<code>shorten_list</code>	Value: [('scons/SCons/', 1), ('/src/engine/SCons/', 1), ('usr/...
<code>TraceFP</code>	Value: {}
<code>TraceDefault</code>	Value: '/dev/tty'
<code>TimeStampDefault</code>	Value: None
<code>StartTime</code>	Value: 1510694480.8
<code>PreviousTime</code>	Value: 1510694480.8
<code>__package__</code>	Value: 'SCons'

7 Module *SCons.Defaults*

SCons.Defaults

Builders and other things for the local site. Here's where we'll duplicate the functionality of `autoconf` until we move it into the installation procedure or use something like `qmconf`.

The code that reads the registry to find MSVC components was borrowed from `distutils.msvccompiler`.

7.1 Functions

DefaultEnvironment(**args, **kw*)

Initial public entry point for creating the default construction Environment.

After creating the environment, we overwrite our name (`DefaultEnvironment`) with the `_fetch_DefaultEnvironment()` function, which more efficiently returns the initialized default construction environment without checking for its existence.

(This function still exists with its `_default_check` because someone else (*cough* `Script/__init__.py` *cough*) may keep a reference to this function. So we can't use the fully functional idiom of having the name originally be a something that *only* creates the construction environment and then overwrites the name.)

StaticObjectEmitter(*target, source, env*)

SharedObjectEmitter(*target, source, env*)

SharedFlagChecker(*source, target, env*)

get_paths_str(*dest*)

chmod_func(*dest, mode*)

chmod_strfunc(*dest, mode*)

copy__func(*dest*, *src*, *symlinks*=True)

If symlinks (is true), then a symbolic link will be shallow copied and recreated as a symbolic link; otherwise, copying a symbolic link will be equivalent to copying the symbolic link's final target regardless of symbolic link depth.

delete__func(*dest*, *must_exist*=0)

delete__strfunc(*dest*, *must_exist*=0)

mkdir__func(*dest*)

move__func(*dest*, *src*)

touch__func(*dest*)

processDefines(*defs*)

process defines, resolving strings, lists, dictionaries, into a list of strings

7.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Defaults.py 74b2c53bc42290e911b334a6b44...
SharedCheck	Value: SCons.Action.Action(SharedFlagChecker, None)
CScan	Value: SCons.Defaults.CScan
DScan	Value: SCons.Tool.DScanner
LaTeXScan	Value: SCons.Tool.LaTeXScanner
ObjSourceScan	Value: SCons.Tool.SourceFileScanner
ProgScan	Value: SCons.Tool.ProgramScanner
DirScanner	Value: SCons.Defaults.DirScanner
DirEntryScanner	Value: SCons.Scanner.Dir.DirEntryScanner()
CAction	Value: SCons.Action.Action("\$CCCOM", "\$CCCOMSTR")

continued on next page

Name	Description
ShCAction	Value: SCons.Action.Action("\$SHCCCOM", "\$SHCCCOMSTR")
CXXAction	Value: SCons.Action.Action("\$CXXCOM", "\$CXXCOMSTR")
ShCXXAction	Value: SCons.Action.Action("\$SHCXXCOM", "\$SHCXXCOMSTR")
DAction	Value: SCons.Action.Action("\$DCOM", "\$DCOMSTR")
ShDAction	Value: SCons.Action.Action("\$SHDCOM", "\$SHDCOMSTR")
ASAction	Value: SCons.Action.Action("\$ASCOM", "\$ASCOMSTR")
ASPPAction	Value: SCons.Action.Action("\$ASPPCOM", "\$ASPPCOMSTR")
LinkAction	Value: SCons.Action.Action("\$LINKCOM", "\$LINKCOMSTR")
ShLinkAction	Value: SCons.Action.Action("\$SHLINKCOM", "\$SHLINKCOMSTR")
LdModuleLinkAction	Value: SCons.Action.Action("\$LDMODULECOM", "\$LDMODULECOMSTR")
permission_dic	Value: {'g': {'r': 32, 'w': 16, 'x': 8}, 'o': {'r': 4, 'w': 2, '...}}
Chmod	Value: SCons.Defaults.Chmod
Copy	Value: SCons.Defaults.Copy
Delete	Value: SCons.Defaults.Delete
Mkdir	Value: SCons.Defaults.Mkdir
Move	Value: SCons.Defaults.Move
Touch	Value: SCons.Defaults.Touch
ConstructionEnvironment	Value: {'BUILDERS': {}, 'CONFIGUREDIREN': '#/.sconf_temp', 'CONFIG...
__package__	Value: 'SCons'

7.3 Class NullCmdGenerator

object —
SCons.Defaults.NullCmdGenerator

This is a callable class that can be used in place of other command generators if you don't want them to do anything.

The `__call__` method for this class simply returns the thing you instantiated it with.

Example usage: `env["DO_NOthing"] = NullCmdGenerator env["LINKCOM"] = "${DO_NOthing('$L$SOURCES $TARGET')}"`

7.3.1 Methods

`__init__(self, cmd)`

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` `exitit`(inherited documentation)

`__call__(self, target, source, env, for_signature=None)`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

7.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

7.4 Class Variable_Method_Caller

object —
SCons.Defaults.Variable_Method_Caller

A class for finding a construction variable on the stack and calling one of its methods.

We use this to support "construction variables" in our string `eval()`s that actually stand in for methods--specifically, use of "RDirs" in call to `__concat` that should actually execute the "TARGET.RDirs" method. (We used to support this by creating a little "build dictionary" that mapped RDirs to the method, but this got in the way of Memoizing construction environments, because we had to create new environment objects to hold the variables.)

7.4.1 Methods

<code>__init__(self, variable, method)</code>

<code>x.__init__(...)</code> initializes x; see <code>help(type(x))</code> for signature <code>object.__init__</code> extit(inherited documentation)

<code>__call__(self, *args, **kw)</code>
--

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

7.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

8 Module **SCons.Environment**

SCons.Environment

Base class for construction Environments. These are the primary objects used to communicate dependency and construction information to the build engine.

Keyword arguments supplied when the construction Environment is created are construction variables used to initialize the Environment

8.1 Functions

<code>alias_builder(<i>env</i>, <i>target</i>, <i>source</i>)</code>
--

<code>apply_tools(<i>env</i>, <i>tools</i>, <i>toolpath</i>)</code>

<code>copy_non_reserved_keywords(<i>dict</i>)</code>
--

<code>is_valid_construction_var(<i>varstr</i>)</code>

Return if the specified string is a legitimate construction variable.

<code>default_decide_source(<i>dependency</i>, <i>target</i>, <i>prev_ni</i>)</code>
--

<code>default_decide_target(<i>dependency</i>, <i>target</i>, <i>prev_ni</i>)</code>
--

<code>default_copy_from_cache(<i>src</i>, <i>dst</i>)</code>
--

NoSubstitutionProxy(*subject*)

An entry point for returning a proxy subclass instance that overrides the subst*() methods so they don't actually perform construction variable substitution. This is specifically intended to be the shim layer in between global function calls (which don't want construction variable substitution) and the DefaultEnvironment() (which would substitute variables if left to its own devices).

We have to wrap this in a function that allows us to delay definition of the class until it's necessary, so that when it subclasses Environment it will pick up whatever Environment subclass the wrapper interface might have assigned to SCons.Environment.Environment.

8.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Environment.py 74b2c53bc42290e911b334a6...
CleanTargets	Value: {}
CalculatorArgs	Value: {}
AliasBuilder	Value: SCons.Builder.Builder(action= alias_builder, target_facto...
reserved_construction_var_names	Value: ['CHANGED_SOURCES', 'CHANGED_TARGETS', 'SOURCE', 'SOURCES...']
future_reserved_construction_var_names	Value: []
__package__	Value: 'SCons'

8.3 Class MethodWrapper

object —
SCons.Environment.MethodWrapper

Known Subclasses: SCons.Environment.BuilderWrapper

A generic Wrapper class that associates a method (which can actually be any callable) with an object. As part of creating this MethodWrapper object an attribute with the specified (by default, the name of the supplied method) is added to the underlying object. When

that new "method" is called, our `__call__()` method adds the object as the first argument, simulating the Python behavior of supplying "self" on method calls.

We hang on to the name by which the method was added to the underlying base class so that we can provide a method to "clone" ourselves onto a new underlying object being copied (without which we wouldn't need to save that info).

8.3.1 Methods

```
__init__(self, object, method, name=None)
```

x.`__init__`(...) initializes x; see `help(type(x))` for signature Overrides:
object.`__init__` `exitit`(inherited documentation)

```
__call__(self, *args, **kwargs)
```

```
clone(self, new_object)
```

Returns an object that re-binds the underlying "method" to the specified new object.

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

8.3.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

8.4 Class BuilderWrapper

object └

SCons.Environment.MethodWrapper └

SCons.Environment.BuilderWrapper

A MethodWrapper subclass that that associates an environment with a Builder.

This mainly exists to wrap the `__call__()` function so that all calls to Builders can have their argument lists massaged in the same way (treat a lone argument as the source, treat two arguments as target then source, make sure both target and source are lists) without having to have cut-and-paste code to do it.

As a bit of obsessive backwards compatibility, we also intercept attempts to get or set the "env" or "builder" attributes, which were the names we used before we put the common functionality into the MethodWrapper base class. We'll keep this around for a while in case people shipped Tool modules that reached into the wrapper (like the Tool/qt.py module does, or did). There shouldn't be a lot attribute fetching or setting on these, so a little extra work shouldn't hurt.

8.4.1 Methods

```
__call__(self, target=None, source=<class
'SCons.Environment._Null'>, *args, **kw)
Overrides: SCons.Environment.MethodWrapper.__call__
```

```
__repr__(self)
repr(x) Overrides: object.__repr__ extit(inherited documentation)
```

```
__str__(self)
str(x) Overrides: object.__str__ extit(inherited documentation)
```

```
__getattr__(self, name)
```

```
__setattr__(self, name, value)
x.__setattr__('name', value) <==> x.name = value Overrides:
object.__setattr__ extit(inherited documentation)
```

Inherited from SCons.Environment.MethodWrapper(Section 8.3)

```
__init__(), clone()
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __sizeof__(), __subclasshook__()
```


8.4.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

8.5 Class BuilderDict

UserDict.UserDict —
SCons.Environment.BuilderDict

This is a dictionary-like class used by an Environment to hold the Builders. We need to do this because every time someone changes the Builders in the Environment's BUILDERS dictionary, we must update the Environment's attributes.

8.5.1 Methods

__init__ (<i>self, dict, env</i>) Overrides: UserDict.UserDict.__init__
__semi_deepcopy__ (<i>self</i>)
__setitem__ (<i>self, item, val</i>) Overrides: UserDict.UserDict.__setitem__
__delitem__ (<i>self, item</i>) Overrides: UserDict.UserDict.__delitem__
update (<i>self, dict</i>) Overrides: UserDict.UserDict.update

Inherited from UserDict.UserDict

__cmp__(), __contains__(), __getitem__(), __len__(), __repr__(), clear(), copy(), fromkeys(), get(), has_key(), items(), iteritems(), iterkeys(), itervalues(), keys(), pop(), popitem(), setdefault(), values()

8.5.2 Class Variables

Name	Description
<i>Inherited from <code>UserDict.UserDict</code></i>	
<code>__hash__</code>	

8.6 Class `SubstitutionEnvironment`

object —
`SCons.Environment.SubstitutionEnvironment`

Known Subclasses: `SCons.Environment.Base`

Base class for different flavors of construction environments.

This class contains a minimal set of methods that handle construction variable expansion and conversion of strings to Nodes, which may or may not be actually useful as a stand-alone class. Which methods ended up in this class is pretty arbitrary right now. They're basically the ones which we've empirically determined are common to the different construction environment subclasses, and most of the others that use or touch the underlying dictionary of construction variables.

Eventually, this class should contain all the methods that we determine are necessary for a "minimal" interface to the build engine. A full "native Python" SCons environment has gotten pretty heavyweight with all of the methods and Tools and construction variables we've jammed in there, so it would be nice to have a lighter weight alternative for interfaces that don't need all of the bells and whistles. (At some point, we'll also probably rename this class "Base," since that more reflects what we want this class to become, but because we've released comments that tell people to subclass `Environment.Base` to create their own flavors of construction environment, we'll save that for a future refactoring when this class actually becomes useful.)

8.6.1 Methods

<code>__init__(self, **kw)</code>
Initialization of an underlying <code>SubstitutionEnvironment</code> class. Overrides: <code>object.__init__</code>
<code>__eq__(self, other)</code>
<code>__delitem__(self, key)</code>

```
__getitem__(self, key)
```

```
__setitem__(self, key, value)
```

```
get(self, key, default=None)
```

Emulates the `get()` method of dictionaries.

```
has_key(self, key)
```

```
__contains__(self, key)
```

```
items(self)
```

```
arg2nodes(self, args, node_factory=<class 'SCons.Environment._Null'>,  
lookup_list=<class 'SCons.Environment._Null'>, **kw)
```

```
gvars(self)
```

```
lvars(self)
```

```
subst(self, string, raw=0, target=None, source=None, conv=None,  
executor=None)
```

Recursively interpolates construction variables from the Environment into the specified string, returning the expanded result. Construction variables are specified by a `$` prefix in the string and begin with an initial underscore or alphabetic character followed by any number of underscores or alphanumeric characters. The construction variable names may be surrounded by curly braces to separate the name from trailing characters.

```
subst_kw(self, kw, raw=0, target=None, source=None)
```

```
subst_list(self, string, raw=0, target=None, source=None, conv=None,  
executor=None)
```

Calls through to `SCons.Subst.scons_subst_list()`. See the documentation for that function.

subst_path(*self*, *path*, *target*=None, *source*=None)

Substitute a path list, turning EntryProxies into Nodes and leaving Nodes (and other objects) as-is.

subst_target_source(*self*, *string*, *raw*=0, *target*=None, *source*=None, *conv*=None, *executor*=None)

Recursively interpolates construction variables from the Environment into the specified string, returning the expanded result. Construction variables are specified by a \$ prefix in the string and begin with an initial underscore or alphabetic character followed by any number of underscores or alphanumeric characters. The construction variable names may be surrounded by curly braces to separate the name from trailing characters.

backtick(*self*, *command*)**AddMethod**(*self*, *function*, *name*=None)

Adds the specified function as a method of this construction environment with the specified name. If the name is omitted, the default name is the name of the function itself.

RemoveMethod(*self*, *function*)

Removes the specified function's MethodWrapper from the added_methods list, so we don't re-bind it when making a clone.

Override(*self*, *overrides*)

Produce a modified environment whose variables are overridden by the overrides dictionaries. "overrides" is a dictionary that will override the variables of this environment.

This function is much more efficient than Clone() or creating a new Environment because it doesn't copy the construction environment dictionary, it just wraps the underlying construction environment, and doesn't even create a wrapper object if there are no overrides.

ParseFlags(*self*, **flags*)

Parse the set of flags and return a dict with the flags placed in the appropriate entry. The flags are treated as a typical set of command-line flags for a GNU-like toolchain and used to populate the entries in the dict immediately below. If one of the flag strings begins with a bang (exclamation mark), it is assumed to be a command and the rest of the string is executed; the result of that evaluation is then added to the dict.

MergeFlags(*self*, *args*, *unique*=1, *dict*=None)

Merge the dict in args into the construction variables of this env, or the passed-in dict. If args is not a dict, it is converted into a dict using ParseFlags. If unique is not set, the flags are appended rather than merged.

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

8.6.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

8.7 Class Base



Known Subclasses: SCons.Environment.OverrideEnvironment, SCons.Script.SConscript'.SConsEnvironment

Base class for "real" construction Environments. These are the primary objects used to communicate dependency and construction information to the build engine.

Keyword arguments supplied when the construction Environment is created are construction variables used to initialize the Environment.

8.7.1 Methods

Action(*self*, **args*, ***kw*)

AddPostAction(*self*, *files*, *action*)

AddPreAction(*self*, *files*, *action*)

Alias(*self*, *target*, *source*=[], *action*=None, ***kw*)

AlwaysBuild(*self*, **targets*)

Append(*self*, ***kw*)

Append values to existing construction variables in an Environment.

AppendENVPath(*self*, *name*, *newpath*, *envname*='ENV', *sep*=':',
delete_existing=1)

Append path elements to the path 'name' in the 'ENV' dictionary for this environment. Will only add any particular path once, and will normpath and normcase all paths to help assure this. This can also handle the case where the env variable is a list instead of a string.

If *delete_existing* is 0, a *newpath* which is already in the path will not be moved to the end (it will be left where it is).

AppendUnique(*self*, *delete_existing*=0, ***kw*)

Append values to existing construction variables in an Environment, if they're not already there. If *delete_existing* is 1, removes existing values first, so values move to end.

BuildDir(*self*, **args*, ***kw*)

Builder(*self*, ***kw*)

CacheDir(*self*, *path*)

Clean(*self*, *targets*, *files*)

Clone(*self*, *tools*=[], *toolpath*=None, *parse_flags*=None, ***kw*)

Return a copy of a construction Environment. The copy is like a Python "deep copy"--that is, independent copies are made recursively of each objects--except that a reference is copied when an object is not deep-copyable (like a function). There are no references to any mutable objects in the original Environment.

Command(*self*, *target*, *source*, *action*, ***kw*)

Builds the supplied target files from the supplied source files using the supplied action. Action may be any type that the Builder constructor will accept for an action.

Configure(*self*, *args, **kw)

Copy(*self*, *args, **kw)

Decider(*self*, function)

Depends(*self*, target, dependency)

Explicitly specify that 'target's depend on 'dependency'.

Detect(*self*, progs)

Return the first available program in progs.

Dictionary(*self*, *args)

Dir(*self*, name, *args, **kw)

Dump(*self*, key=None)

Using the standard Python pretty printer, return the contents of the scons build environment as a string.

If the key passed in is anything other than None, then that will be used as an index into the build environment dictionary and whatever is found there will be fed into the pretty printer. Note that this key is case sensitive.

Entry(*self*, name, *args, **kw)

Environment(*self*, **kw)

Execute(*self*, action, *args, **kw)

Directly execute an action through an Environment

File(*self*, name, *args, **kw)

FindFile(*self*, *file*, *dirs*)

FindInstalledFiles(*self*)

returns the list of all targets of the Install and InstallAs Builder.

FindIxes(*self*, *paths*, *prefix*, *suffix*)

Search a list of paths for something that matches the prefix and suffix.

paths - the list of paths or nodes. prefix - construction variable for the prefix.
suffix - construction variable for the suffix.

FindSourceFiles(*self*, *node*='.')

returns a list of all source files.

Flatten(*self*, *sequence*)

GetBuildPath(*self*, *files*)

Glob(*self*, *pattern*, *ondisk*=True, *source*=False, *strings*=False, *exclude*=None)

Ignore(*self*, *target*, *dependency*)

Ignore a dependency.

Literal(*self*, *string*)

Local(*self*, **targets*)

NoCache(*self*, **targets*)

Tags a target so that it will not be cached

NoClean(*self*, **targets*)

Tags a target so that it will not be cleaned by -c

ParseConfig(*self*, *command*, *function*=None, *unique*=1)

Use the specified function to parse the output of the command in order to modify the current environment. The 'command' can be a string or a list of strings representing a command and its arguments. 'Function' is an optional argument that takes the environment, the output of the command, and the unique flag. If no function is specified, MergeFlags, which treats the output as the result of a typical 'X-config' command (i.e. gtk-config), will merge the output into the appropriate variables.

ParseDepends(*self*, *filename*, *must_exist*=None, *only_one*=0)

Parse a mkdep-style file for explicit dependencies. This is completely abusable, and should be unnecessary in the "normal" case of proper SCons configuration, but it may help make the transition from a Make hierarchy easier for some people to swallow. It can also be genuinely useful when using a tool that can write a .d file, but for which writing a scanner would be too complicated.

Platform(*self*, *platform*)**Precious**(*self*, **targets*)**Prepend**(*self*, ***kw*)

Prepend values to existing construction variables in an Environment.

PrependENVPath(*self*, *name*, *newpath*, *envname*='ENV', *sep*=':',
delete_existing=1)

Prepend path elements to the path 'name' in the 'ENV' dictionary for this environment. Will only add any particular path once, and will normpath and normcase all paths to help assure this. This can also handle the case where the env variable is a list instead of a string.

If delete_existing is 0, a newpath which is already in the path will not be moved to the front (it will be left where it is).

PrependUnique(*self*, *delete_existing*=0, ***kw*)

Prepend values to existing construction variables in an Environment, if they're not already there. If delete_existing is 1, removes existing values first, so values move to front.

Pseudo(*self*, **targets*)

PyPackageDir(*self*, *modulename*)

Replace(*self*, ***kw*)

Replace existing construction variables in an Environment with new construction variables and/or values.

ReplaceIxes(*self*, *path*, *old_prefix*, *old_suffix*, *new_prefix*, *new_suffix*)

Replace old_prefix with new_prefix and old_suffix with new_suffix.

env - Environment used to interpolate variables. path - the path that will be modified. old_prefix - construction variable for the old prefix. old_suffix - construction variable for the old suffix. new_prefix - construction variable for the new prefix. new_suffix - construction variable for the new suffix.

Repository(*self*, **dirs*, ***kw*)

Requires(*self*, *target*, *prerequisite*)

Specify that 'prerequisite' must be built before 'target', (but 'target' does not actually depend on 'prerequisite' and need not be rebuilt if it changes).

SConsignFile(*self*, *name*='.sconsign', *dbm_module*=None)

Scanner(*self*, **args*, ***kw*)

SetDefault(*self*, ***kw*)

SideEffect(*self*, *side_effect*, *target*)

Tell scons that side_effects are built as side effects of building targets.

SourceCode(*self*, *entry*, *builder*)

Arrange for a source code builder for (part of) a tree.

SourceSignatures(*self*, *type*)

Split(*self*, *arg*)

This function converts a string or list into a list of strings or Nodes. This makes things easier for users by allowing files to be specified as a white-space separated list to be split.

The input rules are:

- A single string containing names separated by spaces. These will be split apart at the spaces.
- A single Node instance
- A list containing either strings or Node instances. Any strings in the list are not split at spaces.

In all cases, the function returns a list of Nodes and strings.

TargetSignatures(*self*, *type*)

Tool(*self*, *tool*, *toolpath*=None, ***kw*)

Value(*self*, *value*, *built_value*=None)

VariantDir(*self*, *variant_dir*, *src_dir*, *duplicate*=1)

WhereIs(*self*, *prog*, *path*=None, *pathext*=None, *reject*=[])

Find prog in the path.

__init__(*self*, *platform*=None, *tools*=None, *toolpath*=None, *variables*=None, *parse_flags*=None, ***kw*)

Initialization of a basic SCons construction environment, including setting up special construction variables like BUILDER, PLATFORM, etc., and searching for and applying available Tools.

Note that we do *not* call the underlying base class (SubstitutionEnvironment) initialization, because we need to initialize things in a very specific order that doesn't work with the much simpler base class initialization. Overrides: object.__init__

get_CacheDir(*self*)

get_builder(*self*, *name*)

Fetch the builder with the specified name from the environment.

get_factory(*self*, *factory*, *default*='File')

Return a factory function for creating Nodes for this construction environment.

```
get_scanner(self, key)
```

Find the appropriate scanner given a key (usually a file suffix).

```
get_src_sig_type(self)
```

```
get_tgt_sig_type(self)
```

```
scanner_map_delete(self, kw=None)
```

Delete the cached scanner map (if we need to).

Inherited from `SCons.Environment.SubstitutionEnvironment` (Section 8.6)

`AddMethod()`, `MergeFlags()`, `Override()`, `ParseFlags()`, `RemoveMethod()`, `__contains__()`, `__delitem__()`, `__eq__()`, `__getitem__()`, `__setitem__()`, `arg2nodes()`, `backtick()`, `get()`, `gvars()`, `has_key()`, `items()`, `lvars()`, `subst()`, `subst_kw()`, `subst_list()`, `subst_path()`, `subst_target_source()`


Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

8.7.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

8.8 Class `OverrideEnvironment`



A proxy that overrides variables in a wrapped construction environment by returning values from an overrides dictionary in preference to values from the underlying subject environment.

This is a lightweight (I hope) proxy that passes through most use of attributes to the underlying `Environment.Base` class, but has just enough additional methods defined to act like a real construction environment with overridden values. It can wrap either a `Base` construction environment, or another `OverrideEnvironment`, which can in turn nest arbitrary `OverrideEnvironments`...

Note that we do *not* call the underlying base class (`SubstitutionEnvironment`) initialization, because we get most of those from proxying the attributes of the subject construction environment. But because we subclass `SubstitutionEnvironment`, this class also has inherited `arg2nodes()` and `subst*()` methods; those methods can't be proxied because they need *this* object's methods to fetch the values from the overrides dictionary.

8.8.1 Methods

`__init__`(*self*, *subject*, *overrides*={})

Initialization of a basic SCons construction environment, including setting up special construction variables like `BUILDER`, `PLATFORM`, etc., and searching for and applying available Tools.

Note that we do *not* call the underlying base class (`SubstitutionEnvironment`) initialization, because we need to initialize things in a very specific order that doesn't work with the much simpler base class initialization. Overrides: `object.__init__` extit(inherited documentation)

`__getattr__`(*self*, *name*)

`__setattr__`(*self*, *name*, *value*)

`x.__setattr__('name', value) <==> x.name = value` Overrides: `object.__setattr__` extit(inherited documentation)

`__getitem__`(*self*, *key*)

Overrides: `SCons.Environment.SubstitutionEnvironment.__getitem__`

`__setitem__`(*self*, *key*, *value*)

Overrides: `SCons.Environment.SubstitutionEnvironment.__setitem__`

__delitem__(*self*, *key*)

Overrides: *SCons.Environment.SubstitutionEnvironment.__delitem__*

get(*self*, *key*, *default=None*)

Emulates the *get()* method of dictionaries. Overrides:
SCons.Environment.SubstitutionEnvironment.get

has_key(*self*, *key*)

Overrides: *SCons.Environment.SubstitutionEnvironment.has_key*

__contains__(*self*, *key*)

Overrides: *SCons.Environment.SubstitutionEnvironment.__contains__*

Dictionary(*self*)

Emulates the *items()* method of dictionaries. Overrides:
SCons.Environment.Base.Dictionary

items(*self*)

Emulates the *items()* method of dictionaries. Overrides:
SCons.Environment.SubstitutionEnvironment.items

gvars(*self*)

Overrides: *SCons.Environment.SubstitutionEnvironment.gvars*

lvars(*self*)

Overrides: *SCons.Environment.SubstitutionEnvironment.lvars*

Replace(*self*, ***kw*)

Replace existing construction variables in an Environment with new construction variables and/or values. Overrides:
SCons.Environment.Base.Replace exit(inherited documentation)

Inherited from SCons.Environment.Base(Section 8.9)

Action(), AddPostAction(), AddPreAction(), Alias(), AlwaysBuild(), Append(), AppendENVPath(), AppendUnique(), BuildDir(), Builder(), CacheDir(), Clean(), Clone(), Command(), Configure(), Copy(), Decider(), Depends(), Detect(), Dir(), Dump(), Entry(), Environment(), Execute(), File(), FindFile(), FindInstalledFiles(), FindIxex(), FindSourceFiles(), Flatten(), GetBuildPath(), Glob(), Ignore(), Literal(), Local(), NoCache(), NoClean(), ParseConfig(), ParseDepends(), Platform(), Precious(), Prepend(), PrependENVPath(), PrependUnique(), Pseudo(), PyPackageDir(), ReplaceIxex(), Repository(), Requires(), SConsignFile(), Scanner(), SetDefault(), SideEffect(), SourceCode(), SourceSignatures(), Split(), TargetSignatures(), Tool(), Value(), VariantDir(), WhereIs(), get_CacheDir(), get_builder(), get_factory(), get_scanner(), get_src_sig_type(), get_tgt_sig_type(), scanner_map_delete()

Inherited from SCons.Environment.SubstitutionEnvironment(Section 8.6)

AddMethod(), MergeFlags(), Override(), ParseFlags(), RemoveMethod(), __eq__(), arg2nodes(), backtick(), subst(), subst_kw(), subst_list(), subst_path(), subst_target_source()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __sizeof__(), __str__(), __subclasshook__()

8.8.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

8.9 Class Base



Known Subclasses: SCons.Environment.OverrideEnvironment, SCons.Script.SConscript.SConsEnvironment

Base class for "real" construction Environments. These are the primary objects used to communicate dependency and construction information to the build engine.

Keyword arguments supplied when the construction Environment is created are construction variables used to initialize the Environment.

8.9.1 Methods

Action(*self*, **args*, ***kw*)

AddPostAction(*self*, *files*, *action*)

AddPreAction(*self*, *files*, *action*)

Alias(*self*, *target*, *source*=[], *action*=None, ***kw*)

AlwaysBuild(*self*, **targets*)

Append(*self*, ***kw*)

Append values to existing construction variables in an Environment.

AppendENVPath(*self*, *name*, *newpath*, *envname*='ENV', *sep*=':',
delete_existing=1)

Append path elements to the path 'name' in the 'ENV' dictionary for this environment. Will only add any particular path once, and will normpath and normcase all paths to help assure this. This can also handle the case where the env variable is a list instead of a string.

If delete_existing is 0, a newpath which is already in the path will not be moved to the end (it will be left where it is).

AppendUnique(*self*, *delete_existing*=0, ***kw*)

Append values to existing construction variables in an Environment, if they're not already there. If delete_existing is 1, removes existing values first, so values move to end.

BuildDir(*self*, **args*, ***kw*)

Builder(*self*, ***kw*)

CacheDir(*self*, *path*)

Clean(*self*, *targets*, *files*)

Clone(*self*, *tools*=[], *toolpath*=None, *parse_flags*=None, ***kw*)

Return a copy of a construction Environment. The copy is like a Python "deep copy"--that is, independent copies are made recursively of each objects--except that a reference is copied when an object is not deep-copyable (like a function). There are no references to any mutable objects in the original Environment.

Command(*self*, *target*, *source*, *action*, ***kw*)

Builds the supplied target files from the supplied source files using the supplied action. Action may be any type that the Builder constructor will accept for an action.

Configure(*self*, **args*, ***kw*)

Copy(*self*, **args*, ***kw*)

Decider(*self*, *function*)

Depends(*self*, *target*, *dependency*)

Explicitly specify that 'target's depend on 'dependency'.

Detect(*self*, *progs*)

Return the first available program in progs.

Dictionary(*self*, **args*)

Dir(*self*, *name*, **args*, ***kw*)

Dump(*self*, *key*=None)

Using the standard Python pretty printer, return the contents of the scons build environment as a string.

If the key passed in is anything other than None, then that will be used as an index into the build environment dictionary and whatever is found there will be fed into the pretty printer. Note that this key is case sensitive.

Entry(*self*, *name*, **args*, ***kw*)

Environment(*self*, ***kw*)

Execute(*self*, *action*, **args*, ***kw*)

Directly execute an action through an Environment

File(*self*, *name*, **args*, ***kw*)

FindFile(*self*, *file*, *dirs*)

FindInstalledFiles(*self*)

returns the list of all targets of the Install and InstallAs Builder.

FindIxes(*self*, *paths*, *prefix*, *suffix*)

Search a list of paths for something that matches the prefix and suffix.

paths - the list of paths or nodes. prefix - construction variable for the prefix.
suffix - construction variable for the suffix.

FindSourceFiles(*self*, *node*='.')

returns a list of all source files.

Flatten(*self*, *sequence*)

GetBuildPath(*self*, *files*)

Glob(*self*, *pattern*, *ondisk=True*, *source=False*, *strings=False*,
exclude=None)

Ignore(*self*, *target*, *dependency*)

Ignore a dependency.

Literal(*self*, *string*)

Local(*self*, **targets*)

NoCache(*self*, **targets*)

Tags a target so that it will not be cached

NoClean(*self*, **targets*)

Tags a target so that it will not be cleaned by -c

ParseConfig(*self*, *command*, *function=None*, *unique=1*)

Use the specified function to parse the output of the command in order to modify the current environment. The 'command' can be a string or a list of strings representing a command and its arguments. 'Function' is an optional argument that takes the environment, the output of the command, and the unique flag. If no function is specified, MergeFlags, which treats the output as the result of a typical 'X-config' command (i.e. gtk-config), will merge the output into the appropriate variables.

ParseDepends(*self*, *filename*, *must_exist*=None, *only_one*=0)

Parse a mkdep-style file for explicit dependencies. This is completely abusable, and should be unnecessary in the "normal" case of proper SCons configuration, but it may help make the transition from a Make hierarchy easier for some people to swallow. It can also be genuinely useful when using a tool that can write a .d file, but for which writing a scanner would be too complicated.

Platform(*self*, *platform*)

Precious(*self*, **targets*)

Prepend(*self*, ***kw*)

Prepend values to existing construction variables in an Environment.

PrependENVPath(*self*, *name*, *newpath*, *envname*='ENV', *sep*=':', *delete_existing*=1)

Prepend path elements to the path 'name' in the 'ENV' dictionary for this environment. Will only add any particular path once, and will normpath and normcase all paths to help assure this. This can also handle the case where the env variable is a list instead of a string.

If delete_existing is 0, a newpath which is already in the path will not be moved to the front (it will be left where it is).

PrependUnique(*self*, *delete_existing*=0, ***kw*)

Prepend values to existing construction variables in an Environment, if they're not already there. If delete_existing is 1, removes existing values first, so values move to front.

Pseudo(*self*, **targets*)

PyPackageDir(*self*, *modulename*)

Replace(*self*, ***kw*)

Replace existing construction variables in an Environment with new construction variables and/or values.

ReplaceIxes(*self*, *path*, *old_prefix*, *old_suffix*, *new_prefix*, *new_suffix*)

Replace *old_prefix* with *new_prefix* and *old_suffix* with *new_suffix*.

env - Environment used to interpolate variables. *path* - the path that will be modified. *old_prefix* - construction variable for the old prefix. *old_suffix* - construction variable for the old suffix. *new_prefix* - construction variable for the new prefix. *new_suffix* - construction variable for the new suffix.

Repository(*self*, **dirs*, ***kw*)

Requires(*self*, *target*, *prerequisite*)

Specify that 'prerequisite' must be built before 'target', (but 'target' does not actually depend on 'prerequisite' and need not be rebuilt if it changes).

SConsignFile(*self*, *name*='.sconsign', *dbm_module*=None)

Scanner(*self*, **args*, ***kw*)

SetDefault(*self*, ***kw*)

SideEffect(*self*, *side_effect*, *target*)

Tell scons that *side_effects* are built as side effects of building targets.

SourceCode(*self*, *entry*, *builder*)

Arrange for a source code builder for (part of) a tree.

SourceSignatures(*self*, *type*)

Split(*self*, *arg*)

This function converts a string or list into a list of strings or Nodes. This makes things easier for users by allowing files to be specified as a white-space separated list to be split.

The input rules are:

- A single string containing names separated by spaces. These will be split apart at the spaces.
- A single Node instance
- A list containing either strings or Node instances. Any strings in the list are not split at spaces.

In all cases, the function returns a list of Nodes and strings.

TargetSignatures(*self*, *type*)

Tool(*self*, *tool*, *toolpath*=None, ***kw*)

Value(*self*, *value*, *built_value*=None)

VariantDir(*self*, *variant_dir*, *src_dir*, *duplicate*=1)

WhereIs(*self*, *prog*, *path*=None, *pathext*=None, *reject*=[])

Find prog in the path.


```
__init__(self, platform=None, tools=None, toolpath=None, variables=None,
parse_flags=None, **kw)
```

Initialization of a basic SCons construction environment, including setting up special construction variables like BUILDER, PLATFORM, etc., and searching for and applying available Tools.

Note that we do *not* call the underlying base class (SubstitutionEnvironment) initialization, because we need to initialize things in a very specific order that doesn't work with the much simpler base class initialization. Overrides: object.__init__

```
get__CacheDir(self)
```

```
get__builder(self, name)
```

Fetch the builder with the specified name from the environment.

```
get__factory(self, factory, default='File')
```

Return a factory function for creating Nodes for this construction environment.

```
get__scanner(self, skey)
```

Find the appropriate scanner given a key (usually a file suffix).

```
get__src_sig_type(self)
```

```
get__tgt_sig_type(self)
```

```
scanner_map_delete(self, kw=None)
```

Delete the cached scanner map (if we need to).

Inherited from SCons.Environment.SubstitutionEnvironment(Section 8.6)

AddMethod(), MergeFlags(), Override(), ParseFlags(), RemoveMethod(), __contains__(), __delitem__(), __eq__(), __getitem__(), __setitem__(), arg2nodes(), backtick(), get(), gvars(), has_key(), items(), lvars(), subst(), subst_kw(), subst_list(), subst_path(), subst_target_source()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

8.9.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

9 Module SCons.Errors

SCons.Errors

This file contains the exception classes used to handle internal and user errors in SCons.

9.1 Functions

convert_to_BuildError(*status*, *exc_info*=None)

Convert any return code a BuildError Exception.


The buildError.status we set here will normally be used as the exit status of the "scons" process. **Parameters**

status: : can either be a return code or an Exception.

9.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Errors.py 74b2c53bc42290e911b334a6b44f1...
__package__	Value: 'SCons'

9.3 Class BuildError



Errors occurring while building.

BuildError have the following attributes:

Information about the cause of the build error: **errstr** : a description of the error message

status : the return code of the action that caused the build error. Must be set to a non-zero value even if the build error is not due to an action returning a non-zero returned code.

exitstatus : SCons exit status due to this build error. Must be nonzero unless due to an explicit `Exit()` call. Not always the same as **status**, since actions return a status code that should be respected, but SCons typically exits with 2 irrespective of the return value of the failed action.

filename : The name of the file or directory that caused the build error. Set to `None` if no files are associated with this error. This might be different from the target being built. For example, failure to create the directory in which the target file will appear. It can be `None` if the error is not due to a particular filename.

exc_info : Info about exception that caused the build error. Set to `(None, None, None)` if this build error is not due to an exception.

Information about the cause of the location of the error: **node** : the error occurred while building this target node(s)

executor (the executor that caused the build to fail (might

be `None` if the build failures is not due to the executor failing)

action (the action that caused the build to fail (might be

`None` if the build failures is not due to the an action failure)

command (the command line for the action that caused the

build to fail (might be `None` if the build failures is not due to the an action failure)

9.3.1 Methods

```
__init__(self, node=None, errstr='Unknown error', status=2,
          exitstatus=2, filename=None, executor=None, action=None, command=None,
          exc_info=(None, None, None))
```

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` extit(inherited documentation)

```
__str__(self)
```

`str(x)` Overrides: `object.__str__` extit(inherited documentation)

Inherited from *exceptions.Exception*

```
__new__()
```

Inherited from `exceptions.BaseException`


`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__unicode__()`

Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

9.3.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

9.4 Class `InternalError`**9.4.1 Methods*****Inherited from `exceptions.Exception`***

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

9.4.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i> args, message	
<i>Inherited from object</i> __class__	

9.5 Class `UserError`



Known Subclasses: `SCons.SConf.SConfError`, `SCons.Warnings.Warning`

9.5.1 Methods

Inherited from exceptions.Exception

__init__(), __new__()

Inherited from exceptions.BaseException

__delattr__(), __getattr__(), __getitem__(), __getslice__(), __reduce__(), __repr__(), __setattr__(), __setstate__(), __str__(), __unicode__()


Inherited from object

__format__(), __hash__(), __reduce_ex__(), __sizeof__(), __subclasshook__()

9.5.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i> args, message	
<i>Inherited from object</i> __class__	

9.6 Class StopError



9.6.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

9.6.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

9.7 Class EnvironmentError



9.7.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

9.7.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
<code>__class__</code>	

9.8 Class MSVCErrors



9.8.1 Methods

Inherited from exceptions.IOError

`__init__()`, `__new__()`

Inherited from exceptions.EnvironmentError

`__reduce__()`, `__str__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__repr__()`,
`__setattr__()`, `__setstate__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

9.8.2 Properties

Name	Description
<i>Inherited from exceptions.EnvironmentError</i> errno, filename, strerror	
<i>Inherited from exceptions.BaseException</i> args, message	
<i>Inherited from object</i> __class__	

9.9 Class ExplicitExit



9.9.1 Methods

`__init__(self, node=None, status=None, *args)`
 x.`__init__(...)` initializes x; see `help(type(x))` for signature Overrides:
 object.`__init__` `exit`(inherited documentation)

Inherited from exceptions.Exception

`__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

9.9.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

10 Module *SCons.Executor*

SCons.Executor

A module for executing actions with specific lists of target and source Nodes.

10.1 Functions

rfile(*node*)

A function to return the results of a Node's `rfile()` method, if it exists, and the Node itself otherwise (if it's a Value Node, e.g.).

execute_nothing(*obj*, *target*, *kw*)

execute_action_list(*obj*, *target*, *kw*)

Actually execute the action list.

execute_actions_str(*obj*)

execute_null_str(*obj*)

GetBatchExecutor(*key*)

AddBatchExecutor(*key*, *executor*)

get_NullEnvironment()

Use singleton pattern for Null Environments.

10.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Executor.py 74b2c53bc42290e911b334a6b44...

continued on next page

Name	Description
__nullenv__	Value: None
__package__	Value: 'SCons'

10.3 Class Batch

object —
SCons.Executor.Batch

Remembers exact association between targets and sources of executor.

10.3.1 Methods

__init__ (<i>self</i> , <i>targets</i> =[], <i>sources</i> =[])
x. __init__ (...) initializes x; see help(type(x)) for signature Overrides: object. __init__ __exit__ (inherited documentation)


Inherited from object

__delattr__(), **__format__**(), **__getattr__**(), **__hash__**(), **__new__**(),
__reduce__(), **__reduce_ex__**(), **__repr__**(), **__setattr__**(), **__sizeof__**(),
__str__(), **__subclasshook__**()

10.3.2 Properties

Name	Description
sources	
targets	
<i>Inherited from object</i>	
__class__	

10.4 Class **TSList**



A class that implements \$TARGETS or \$SOURCES expansions by wrapping an executor Method. This class is used in the `Executor.lvars()` to delay creation of `NodeList` objects until they're needed.

Note that we subclass `collections.UserList` purely so that the `is_Sequence()` function will identify an object of this class as a list during variable expansion. We're not really using any `collections.UserList` methods in practice.

10.4.1 Methods

__init__(*self*, *func*)

x.**__init__**(...) initializes *x*; see `help(type(x))` for signature. Overrides: `object.__init__` `extit`(inherited documentation)

__getattr__(*self*, *attr*)

__getitem__(*self*, *i*)

Overrides: `_abcoll.Sequence.__getitem__`

<code>__getslice__(self, i, j)</code>

Overrides: UserList.UserList.__getslice__

<code>__str__(self)</code>

str(x) Overrides: object.__str__ exitit(inherited documentation)
--

<code>__repr__(self)</code>

repr(x) Overrides: object.__repr__ exitit(inherited documentation)
--

Inherited from UserList.UserList

`__add__()`, `__cmp__()`, `__contains__()`, `__delitem__()`, `__delslice__()`,
`__eq__()`, `__ge__()`, `__gt__()`, `__iadd__()`, `__imul__()`, `__le__()`, `__len__()`,
`__lt__()`, `__mul__()`, `__ne__()`, `__radd__()`, `__rmul__()`, `__setitem__()`,
`__setslice__()`, `append()`, `count()`, `extend()`, `index()`, `insert()`, `pop()`, `remove()`,
`reverse()`, `sort()`

Inherited from __abcoll.Sequence

`__iter__()`, `__reversed__()`

Inherited from __abcoll.Sized

`__subclasshook__()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__new__()`, `__reduce__()`,
`__reduce_ex__()`, `__setattr__()`, `__sizeof__()`

10.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

10.4.3 Class Variables

Name	Description
<i>Inherited from UserList.UserList</i>	
<code>__abstractmethods__</code> , <code>__hash__</code>	

10.5 Class TSOBJect



A class that implements \$TARGET or \$SOURCE expansions by wrapping an Executor method.

10.5.1 Methods

`__init__(self, func)`

x.`__init__`(...) initializes x; see help(type(x)) for signature Overrides: object.`__init__` extit(inherited documentation)

`__getattr__(self, attr)`

`__str__(self)`

str(x) Overrides: object.`__str__` extit(inherited documentation)

`__repr__(self)`

repr(x) Overrides: object.`__repr__` extit(inherited documentation)

Inherited from object

`__delattr__`(), `__format__`(), `__getattr__`(), `__hash__`(), `__new__`(),
`__reduce__`(), `__reduce_ex__`(), `__setattr__`(), `__sizeof__`(), `__subclasshook__`()

10.5.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

10.6 Class Executor



A class for controlling instances of executing an action.

This largely exists to hold a single association of an action, environment, list of environment override dictionaries, targets and sources for later processing as needed.

10.6.1 Methods

```
__init__(self, action, env=None, overridelist=[{}], targets=[],
sources=[], builder_kw={})
```

x.**__init__**(...) initializes *x*; see help(type(*x*)) for signature Overrides:
object.**__init__** **exitit**(inherited documentation)

```
get_lvars(self)
```

```
get_action_targets(self)
```

```
set_action_list(self, action)
```

```
get_action_list(self)
```

```
get_all_targets(self)
```

Returns all targets for all batches of this Executor.

```
get_all_sources(self)
```

Returns all sources for all batches of this Executor.

```
get_all_children(self)
```

Returns all unique children (dependencies) for all batches of this Executor.

The Taskmaster can recognize when it's already evaluated a Node, so we don't have to make this list unique for its intended canonical use case, but we expect there to be a lot of redundancy (long lists of batched .cc files #including the same .h files over and over), so removing the duplicates once up front should save the Taskmaster a lot of work.

get_all_prerequisites(*self*)

Returns all unique (order-only) prerequisites for all batches of this Executor.

get_action_side_effects(*self*)

Returns all side effects for all batches of this Executor used by the underlying Action.

get_build_env(*self*)

Fetch or create the appropriate build Environment for this Executor.

get_build_scanner_path(*self*, *scanner*)

Fetch the scanner path for this executor's targets and sources.

get_kw(*self*, *kw*={})**__call__**(*self*, *target*, ***kw*)**cleanup**(*self*)**add_sources**(*self*, *sources*)

Add source files to this Executor's list. This is necessary for "multi" Builders that can be called repeatedly to build up a source file list for a given target.

get_sources(*self*)

add_batch(*self*, *targets*, *sources*)

Add pair of associated target and source to this Executor's list. This is necessary for "batch" Builders that can be called repeatedly to build up a list of matching target and source files that will be used in order to update multiple target files at once from multiple corresponding source files, for tools like MSVC that support it.

prepare(*self*)

Preparatory checks for whether this Executor can go ahead and (try to) build its targets.

add_pre_action(*self*, *action*)**add_post_action**(*self*, *action*)**__str__**(*self*)

str(x) Overrides: object.__str__ exitit(inherited documentation)

nullify(*self*)**get_contents**(*self*)

Fetch the signature contents. This is the main reason this class exists, so we can compute this once and cache it regardless of how many target or source Nodes there are.

get_timestamp(*self*)

Fetch a time stamp for this Executor. We don't have one, of course (only files do), but this is the interface used by the timestamp module.

scan_targets(*self*, *scanner*)**scan_sources**(*self*, *scanner*)

scan(*self*, *scanner*, *node_list*)

Scan a list of this Executor's files (targets or sources) for implicit dependencies and update all of the targets with them. This essentially short-circuits an N*M scan of the sources for each individual target, which is a hell of a lot more efficient.

get_unignored_sources(*self*, *node*, *ignore=()*)

get_implicit_deps(*self*)

Return the executor's implicit dependencies, i.e. the nodes of the commands to be executed.

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__subclasshook__()`

10.6.2 Properties

Name	Description
<code>action_list</code>	
<code>batches</code>	
<code>builder_kw</code>	
<code>env</code>	
<code>lvars</code>	
<code>overridelist</code>	
<code>post_actions</code>	
<code>pre_actions</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

10.7 Class NullEnvironment



10.7.1 Methods

<code>get_CacheDir(self)</code>

Inherited from SCons.Util.Null(Section 36.16)

`__bool__()`, `__call__()`, `__delattr__()`, `__getattr__()`, `__init__()`, `__new__()`,
`__nonzero__()`, `__repr__()`, `__setattr__()`

Inherited from object

`__format__()`, `__getattribute__()`, `__hash__()`, `__reduce__()`, `__reduce_ex__()`,
`__sizeof__()`, `__str__()`, `__subclasshook__()`

10.7.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

10.8 Class Null



A null Executor, with a null build Environment, that does nothing when the rest of the methods call it.

This might be able to disappear when we refactor things to disassociate Builders from Nodes entirely, so we're not going to worry about unit tests for this--at least for now.

10.8.1 Methods

`__init__(self, *args, **kw)`

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` extit(inherited documentation)

`get_build_env(self)`

`get_build_scanner_path(self)`

`cleanup(self)`

`prepare(self)`

`get_unignored_sources(self, *args, **kw)`

`get_action_targetes(self)`

`get_action_list(self)`

`get_all_targetes(self)`

`get_all_sources(self)`

`get_all_children(self)`

`get_all_prerequisites(self)`

`get_action_side_effects(self)`

`__call__(self, *args, **kw)`

`get_contents(self)`

`add_pre_action(self, action)`

`add_post_action(self, action)`

<code>set_action_list(self, action)</code>
--

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

10.8.2 Properties

Name	Description
action_list	
batches	
builder_kw	
env	
lvars	
overridelist	
post_actions	
pre_actions	
<i>Inherited from object</i>	
__class__	

11 Module SCons.Job

SCons.Job

This module defines the Serial and Parallel classes that execute tasks to complete a build. The Jobs class provides a higher level interface to start, stop, and wait on jobs.

11.1 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Job.py 74b2c53bc42290e911b334a6b44f187d...'
<code>explicit_stack_size</code>	Value: None
<code>default_stack_size</code>	Value: 256
<code>interrupt_msg</code>	Value: 'Build interrupted.'
<code>__package__</code>	Value: 'SCons'

11.2 Class InterruptState



11.2.1 Methods

```
__init__(self)
```

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` `exitit`(inherited documentation)

```
set(self)
```

```
__call__(self)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

11.2.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

11.3 Class Jobs



An instance of this class initializes N jobs, and provides methods for starting, stopping, and waiting on all N jobs.

11.3.1 Methods

__init__ (<i>self</i> , <i>num</i> , <i>taskmaster</i>) <hr/> <p>Create 'num' jobs using the given taskmaster.</p> <p>If 'num' is 1 or less, then a serial job will be used, otherwise a parallel job with 'num' worker threads will be used.</p> <p>The 'num_jobs' attribute will be set to the actual number of jobs allocated. If more than one job is requested but the Parallel class can't do it, it gets reset to 1. Wrapping interfaces that care should check the value of 'num_jobs' after initialization. Overrides: object.__init__</p>
run (<i>self</i> , <i>postfunc</i> =<function <lambda> at 0x7f2c432745f0>) <hr/> <p>Run the jobs.</p> <p>postfunc() will be invoked after the jobs has run. It will be invoked even if the jobs are interrupted by a keyboard interrupt (well, in fact by a signal such as either SIGINT, SIGTERM or SIGHUP). The execution of postfunc() is protected against keyboard interrupts and is guaranteed to run to completion.</p>

were_interrupted (<i>self</i>)
Returns whether the jobs were interrupted by a signal.

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

11.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

11.4 Class Serial

```
object └─ SCons.Job.Serial
```

This class is used to execute tasks in series, and is more efficient than Parallel, but is only appropriate for non-parallel builds. Only one instance of this class should be in existence at a time.

This class is not thread safe.

11.4.1 Methods

<code>__init__</code> (<i>self</i> , <i>taskmaster</i>)
Create a new serial job given a taskmaster.
The taskmaster's <code>next_task()</code> method should return the next task that needs to be executed, or None if there are no more tasks. The taskmaster's <code>executed()</code> method will be called for each task when it is successfully executed, or <code>failed()</code> will be called if it failed to execute (e.g. <code>execute()</code> raised an exception). Overrides: <code>object.__init__</code>

start(*self*)

Start the job. This will begin pulling tasks from the taskmaster and executing them, and return when there are no more tasks. If a task fails to execute (i.e. `execute()` raises an exception), then the job will stop.


Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

11.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

11.5 Class Worker



A worker thread waits on a task to be posted to its request queue, dequeues the task, executes it, and posts a tuple including the task and a boolean indicating whether the task executed successfully.

11.5.1 Methods

__init__(*self, requestQueue, resultsQueue, interrupted*)

This constructor should always be called with keyword arguments. Arguments are:

group should be None; reserved for future extension when a ThreadGroup class is implemented.

target is the callable object to be invoked by the run() method. Defaults to None, meaning nothing is called.

name is the thread name. By default, a unique name is constructed of the form "Thread-N" where N is a small decimal number.

args is the argument tuple for the target invocation. Defaults to ().

kwargs is a dictionary of keyword arguments for the target invocation. Defaults to {}.

If a subclass overrides the constructor, it must make sure to invoke the base class constructor (Thread.__init__()) before doing anything else to the thread. Overrides: object.__init__ exitit(inherited documentation)

run(*self*)

Method representing the thread's activity.

You may override this method in a subclass. The standard run() method invokes the callable object passed to the object's constructor as the target argument, if any, with sequential and keyword arguments taken from the args and kwargs arguments, respectively. Overrides: threading.Thread.run exitit(inherited documentation)

Inherited from threading.Thread

__repr__(), getName(), isAlive(), isDaemon(), is_alive(), join(), setDaemon(), setName(), start()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

11.5.2 Properties

Name	Description
<i>Inherited from threading.Thread</i> daemon, ident, name	
<i>Inherited from object</i> __class__	

11.6 Class ThreadPool



This class is responsible for spawning and managing worker threads.

11.6.1 Methods

__init__ (<i>self, num, stack_size, interrupted</i>) <hr/> <p>Create the request and reply queues, and 'num' worker threads.</p> <p>One must specify the stack size of the worker threads. The stack size is specified in kilobytes. Overrides: object.__init__</p>
put (<i>self, task</i>) <hr/> <p>Put task into request queue.</p>
get (<i>self</i>) <hr/> <p>Remove and return a result tuple from the results queue.</p>
preparation_failed (<i>self, task</i>) <hr/>

cleanup(*self*)

Shuts down the thread pool, giving each worker thread a chance to shut down gracefully.

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

11.6.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

11.7 Class Parallel

object —
SCons.Job.Parallel

This class is used to execute tasks in parallel, and is somewhat less efficient than Serial, but is appropriate for parallel builds.

This class is thread safe.

11.7.1 Methods

<code>__init__</code> (<i>self</i> , <i>taskmaster</i> , <i>num</i> , <i>stack_size</i>)
<p>Create a new parallel job given a taskmaster.</p> <p>The taskmaster's <code>next_task()</code> method should return the next task that needs to be executed, or <code>None</code> if there are no more tasks. The taskmaster's <code>executed()</code> method will be called for each task when it is successfully executed, or <code>failed()</code> will be called if the task failed to execute (i.e. <code>execute()</code> raised an exception).</p> <p>Note: calls to taskmaster are serialized, but calls to <code>execute()</code> on distinct tasks are not serialized, because that is the whole point of parallel jobs: they can execute multiple tasks simultaneously. Overrides: <code>object.__init__</code></p>
<code>start</code> (<i>self</i>)
<p>Start the job. This will begin pulling tasks from the taskmaster and executing them, and return when there are no more tasks. If a task fails to execute (i.e. <code>execute()</code> raises an exception), then the job will stop.</p>

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

11.7.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

12 Module *SCons.Memoize*

Memoizer

A decorator-based implementation to count hits and misses of the computed values that various methods cache in memory.

Use of this modules assumes that wrapped methods be coded to cache their values in a consistent way. In particular, it requires that the class uses a dictionary named "`__memo`" to store the cached values.

Here is an example of wrapping a method that returns a computed value, with no input parameters:

```
@SCons.Memoize.CountMethodCall
def foo(self):

    try:                                # Memoization
        return self._memo['foo']        # Memoization
    except KeyError:                    # Memoization
        pass                            # Memoization

    result = self.compute_foo_value()

    self._memo['foo'] = result          # Memoization

    return result
```

Here is an example of wrapping a method that will return different values based on one or more input arguments:

```
def _bar_key(self, argument):           # Memoization
    return argument                     # Memoization

@SCons.Memoize.CountDictCall(_bar_key)
def bar(self, argument):

    memo_key = argument                 # Memoization
    try:                                # Memoization
        memo_dict = self._memo['bar']  # Memoization
    except KeyError:                    # Memoization
        memo_dict = {}                 # Memoization
        self._memo['dict'] = memo_dict # Memoization
    else:                               # Memoization
        try:                            # Memoization
```

```

        return memo_dict[memo_key]                # Memoization
    except KeyError:                               # Memoization
        pass                                       # Memoization

    result = self.compute_bar_value(argument)

    memo_dict[memo_key] = result                  # Memoization

    return result

```

Deciding what to cache is tricky, because different configurations can have radically different performance tradeoffs, and because the tradeoffs involved are often so non-obvious. Consequently, deciding whether or not to cache a given method will likely be more of an art than a science, but should still be based on available data from this module. Here are some VERY GENERAL guidelines about deciding whether or not to cache return values from a method that's being called a lot:

- **The first question to ask is, "Can we change the calling code** so this method isn't called so often?" Sometimes this can be done by changing the algorithm. Sometimes the *caller* should be memoized, not the method you're looking at.
- The memoized function should be timed with multiple configurations to make sure it doesn't inadvertently slow down some other configuration.
- **When memoizing values based on a dictionary key composed of** input arguments, you don't need to use all of the arguments if some of them don't affect the return values.

12.1 Functions

Dump (<i>title=None</i>)
Dump the hit/miss count for all the counters collected so far.

EnableMemoization ()

CountMethodCall (<i>fn</i>)
Decorator for counting memoizer hits/misses while retrieving a simple value in a class method. It wraps the given method <i>fn</i> and uses a CountValue object to keep track of the caching statistics. Wrapping gets enabled by calling EnableMemoization().

CountDictCall(*keyfunc*)

Decorator for counting memoizer hits/misses while accessing dictionary values with a key-generating function. Like CountMethodCall above, it wraps the given method fn and uses a CountDict object to keep track of the caching statistics. The dict-key function keyfunc has to get passed in the decorator call and gets stored in the CountDict instance. Wrapping gets enabled by calling EnableMemoization().

12.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Memoize.py 74b2c53bc42290e911b334a6b44f...'
__doc__	Value: ""Memoi...
use_memoizer	Value: None
CounterList	Value: {}
__package__	Value: 'SCons'

12.3 Class Counter

object —
SCons.Memoize.Counter

Known Subclasses: SCons.Memoize.CountDict, SCons.Memoize.CountValue

Base class for counting memoization hits and misses.

We expect that the initialization in a matching decorator will fill in the correct class name and method name that represents the name of the function being counted.

12.3.1 Methods

__init__(*self*, *cls_name*, *method_name*)

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides:
object.**__init__**

key(*self*)

display(*self*)

__eq__(*self*, *other*)

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

12.3.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

12.4 Class CountValue

A counter class for simple, atomic memoized values.

A CountValue object should be instantiated in a decorator for each of the class's methods that memoizes its return value by simply storing the return value in its `__memo` dictionary.

12.4.1 Methods

count(*self*, **args*, ***kw*)

Counts whether the memoized value has already been set (a hit) or not (a miss).

Inherited from SCons.Memoize.Counter(Section 12.3)

__eq__(), __init__(), display(), key()

Inherited from object

```


__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

```

12.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

12.5 Class CountDict



A counter class for memoized values stored in a dictionary, with keys based on the method's input arguments.

A CountDict object is instantiated in a decorator for each of the class's methods that memoizes its return value in a dictionary, indexed by some key that can be computed from one or more of its input arguments.

12.5.1 Methods

<code>__init__(self, cls_name, method_name, keymaker)</code> x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature Overrides: object. <code>__init__</code>
<code>count(self, *args, **kw)</code> <hr/> Counts whether the computed key value is already present in the memoization dictionary (a hit) or not (a miss).

Inherited from SCons.Memoize.Counter(Section 12.3)

```
__eq__(), display(), key()
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),  
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),  
__str__(), __subclasshook__()
```

12.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

13 Package SCons.Node

SCons.Node

The Node package for the SCons software construction utility.

This is, in many ways, the heart of SCons.

A Node is where we encapsulate all of the dependency information about any thing that SCons can build, or about any thing which SCons can use to build some other thing. The canonical "thing," of course, is a file, but a Node can also represent something remote (like a web page) or something completely abstract (like an Alias).

Each specific type of "thing" is specifically represented by a subclass of the Node base class: Node.FS.File for files, Node.Alias for aliases, etc. Dependency information is kept here in the base class, and information specific to files/aliases/etc. is in the subclass. The goal, if we've done this correctly, is that any type of "thing" should be able to depend on any other type of "thing."

13.1 Modules

- **Alias:** `scons.Node.Alias`
(Section 14, p. 133)
- **FS:** `scons.Node.FS`
(Section 15, p. 139)
- **Python:** `scons.Node.Python`
(Section 16, p. 186)

13.2 Functions

<code>classname(obj)</code>

<code>Annotate(node)</code>

<code>is_derived_none(node)</code>

<code>is_derived_node(node)</code>

Returns true if this node is derived (i.e. built).
--

<code>exists_none(node)</code>

```
exists_always(node)
```

```
exists_base(node)
```

```
exists_entry(node)
```

Return if the Entry exists. Check the file system to see what we should turn into first. Assume a file if there's no directory.

```
exists_file(node)
```

```
rexists_none(node)
```

```
rexists_node(node)
```

```
rexists_base(node)
```

```
get_contents_none(node)
```

```
get_contents_entry(node)
```

Fetch the contents of the entry. Returns the exact binary contents of the file.

```
get_contents_dir(node)
```

Return content signatures and names of all our children separated by new-lines. Ensure that the nodes are sorted.

```
get_contents_file(node)
```

```
target_from_source_none(node, prefix, suffix, splitext)
```

```
target_from_source_base(node, prefix, suffix, splitext)
```

```
changed_since_last_build_node(node, target, prev_ni)
```

Must be overridden in a specific subclass to return True if this Node (a dependency) has changed since the last time it was used to build the specified target. *prev_ni* is this Node's state (for example, its file timestamp, length, maybe content signature) as of the last time the target was built.

Note that this method is called through the dependency, not the target, because a dependency Node must be able to use its own logic to decide if it changed. For example, File Nodes need to obey if we're configured to use timestamps, but Python Value Nodes never use timestamps and always use the content. If this method were called through the target, then each Node's implementation of this method would have to have more complicated logic to handle all the different Node types on which it might depend.

```
changed_since_last_build_alias(node, target, prev_ni)
```

```
changed_since_last_build_entry(node, target, prev_ni)
```

```
changed_since_last_build_state_changed(node, target, prev_ni)
```

```
decide_source(node, target, prev_ni)
```

```
decide_target(node, target, prev_ni)
```

```
changed_since_last_build_python(node, target, prev_ni)
```

```
store_info_pass(node)
```

```
store_info_file(node)
```

```
get_children(node, parent)
```

```
ignore_cycle(node, stack)
```

```
do_nothing(node, parent)
```

13.3 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Node/__init__.py 74b2c53bc42290e911b334...'
<code>print_duplicate</code>	Value: 0
<code>no_state</code>	Value: 0
<code>pending</code>	Value: 1
<code>executing</code>	Value: 2
<code>up_to_date</code>	Value: 3
<code>executed</code>	Value: 4
<code>failed</code>	Value: 5
<code>StateString</code>	Value: {0: 'no_state', 1: 'pending', 2: 'executing', 3: 'up_to_d...'}
<code>implicit_cache</code>	Value: 0
<code>implicit_deps_unchanged</code>	Value: 0
<code>implicit_deps_changed</code>	Value: 0
<code>interactive</code>	Value: False
<code>do_store_info</code>	Value: True
<code>store_info_map</code>	Value: {0: store_info_pass, 1: store_info_file}
<code>arg2nodes_lookups</code>	Value: [<bound method AliasNameSpace.lookup of {}>]
<code>__package__</code>	Value: 'SCons.Node'

13.4 Class *NodeInfoBase*

object —
SCons.Node.NodeInfoBase

Known Subclasses: *SCons.Node.Alias.AliasNodeInfo*, *SCons.Node.FS.DirNodeInfo*, *SCons.Node.FS.FileNodeInfo*, *SCons.Node.Python.ValueNodeInfo*

The generic base class for signature information for a Node.

Node subclasses should subclass *NodeInfoBase* to provide their own logic for dealing with their own Node-specific signature information.

13.4.1 Methods

__getstate__(*self*)

Return all fields that shall be pickled. Walk the slots in the class hierarchy and add those to the state dictionary. If a '___dict___' slot is available, copy all entries to the dictionary. Also include the version id, which is fixed for all instances of a class.

__setstate__(*self*, *state*)

Restore the attributes from a pickled state. The version is discarded.

convert(*self*, *node*, *val*)

format(*self*, *field_list*=None, *names*=0)

merge(*self*, *other*)

Merge the fields of another object into this object. Already existing information is overwritten by the other instance's data. WARNING: If a '___dict___' slot is added, it should be updated instead of replaced.

update(*self*, *node*)

Inherited from object

___delattr___(), ___format___(), ___getattr___(), ___hash___(), ___init___(),
___new___(), ___reduce___(), ___reduce_ex___(), ___repr___(), ___setattr___(),
___sizeof___(), ___str___(), ___subclasshook___()

13.4.2 Properties

Name	Description
<i>Inherited from object</i> ___class___	

13.4.3 Class Variables

Name	Description
current_version_id	Value: 2

13.5 Class **BuildInfoBase**



Known Subclasses: *SCons.Node.Alias.AliasBuildInfo*, *SCons.Node.FS.DirBuildInfo*, *SCons.Node.FS.FileBuildInfo*, *SCons.Node.Python.ValueBuildInfo*

The generic base class for build information for a Node.

This is what gets stored in a *.sconsign* file for each target file. It contains a *NodeInfo* instance for this node (signature information that's specific to the type of Node) and direct attributes for the generic build stuff we have to track: sources, explicit dependencies, implicit dependencies, and action information.

13.5.1 Methods

__getstate__(*self*)

Return all fields that shall be pickled. Walk the slots in the class hierarchy and add those to the state dictionary. If a '**__dict__**' slot is available, copy all entries to the dictionary. Also include the version id, which is fixed for all instances of a class.

__init__(*self*)

x.**__init__**(...) initializes *x*; see *help(type(x))* for signature Overrides: *object.__init__* extit(inherited documentation)

__setstate__(*self, state*)

Restore the attributes from a pickled state.

merge(*self*, *other*)

Merge the fields of another object into this object. Already existing information is overwritten by the other instance's data. WARNING: If a '___dict___' slot is added, it should be updated instead of replaced.

Inherited from object

___delattr___(), ___format___(), ___getattr___(), ___hash___(), ___new___(),
___reduce___(), ___reduce_ex___(), ___repr___(), ___setattr___(), ___sizeof___(),
___str___(), ___subclasshook___()

13.5.2 Properties

Name	Description
bact	
bactsig	
bdepends	
bdependsigs	
bimplicit	
bimplicitigs	
bsources	
bsourcesigs	
<i>Inherited from object</i>	
___class___	

13.5.3 Class Variables

Name	Description
current_version_id	Value: 2

13.6 Class Node

object —
 SCons.Node.Node

Known Subclasses: SCons.Node.Alias.Alias, SCons.Node.FS.Base, SCons.Node.Python.Value

The base Node class, for entities that we know how to build, or use to build other Nodes.

13.6.1 Methods

Decider(*self*, *function*)

GetTag(*self*, *key*)

Return a user-defined tag.

Tag(*self*, *key*, *value*)

Add a user-defined tag.

__init__(*self*)

x.__init__(...) initializes x; see help(type(x)) for signature Overrides: object.__init__ exitit(inherited documentation)

add_dependency(*self*, *depend*)

Adds dependencies.

add_ignore(*self*, *depend*)

Adds dependencies to ignore.

add_prerequisite(*self*, *prerequisite*)

Adds prerequisites

add_source(*self*, *source*)

Adds sources.

add_to_implicit(*self*, *deps*)

add_to_waiting_parents(*self*, *node*)

Returns the number of nodes added to our waiting parents list: 1 if we add a unique waiting parent, 0 if not. (Note that the returned values are intended to be used to increment a reference count, so don't think you can "clean up" this function by using True and False instead...)

add_to_waiting_s_e(*self*, *node*)**add_wkid**(*self*, *wkid*)

Add a node to the list of kids waiting to be evaluated

all_children(*self*, *scan*=1)

Return a list of all the node's direct children.

alter_targets(*self*)

Return a list of alternate targets for this Node.

build(*self*, ***kw*)

Actually build the node.

This is called by the Taskmaster after it's decided that the Node is out-of-date and must be rebuilt, and after the prepare() method has gotten everything, uh, prepared.

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in built().

builder_set(*self*, *builder*)

built(*self*)

Called just after this node is successfully built.

changed(*self*, *node=None*, *allowcache=False*)

Returns if the node is up-to-date with respect to the BuildInfo stored last time it was built. The default behavior is to compare it against our own previously stored BuildInfo, but the stored BuildInfo from another Node (typically one in a Repository) can be used instead.

Note that we now *always* check every dependency. We used to short-circuit the check by returning as soon as we detected any difference, but we now rely on checking every dependency to make sure that any necessary Node information (for example, the content signature of an `#included .h` file) is updated.

The `allowcache` option was added for supporting the early release of the executor/builder structures, right after a File target was built. When set to true, the return value of this `changed` method gets cached for File nodes. Like this, the executor isn't needed any longer for subsequent calls to `changed()`.

@see: `FS.File.changed()`, `FS.File.release_target_info()`

children(*self*, *scan=1*)

Return a list of the node's direct children, minus those that are ignored by this node.

children_are_up_to_date(*self*)

Alternate check for whether the Node is current: If all of our children were up-to-date, then this Node was up-to-date, too.

The `SCons.Node.Alias` and `SCons.Node.Python.Value` subclasses rebind their `current()` method to this method.

clear(*self*)

Completely clear a Node of all its cached state (so that it can be re-evaluated by interfaces that do continuous integration builds).

clear_memoized_values(*self*)**del_binfo**(*self*)

Delete the build info from this node.

disambiguate(*self*, *must_exist*=None)**env_set**(*self*, *env*, *safe*=0)**executor_cleanup**(*self*)

Let the executor clean up any cached information.

exists(*self*)

Does this node exists?

explain(*self*)**for_signature**(*self*)

Return a string representation of the Node that will always be the same for this particular Node, no matter what. This is by contrast to the `__str__()` method, which might, for instance, return a relative path for a file Node. The purpose of this method is to generate a value to be used in signature calculation for the command line used to build a target, and we use this method instead of `str()` to avoid unnecessary rebuilds. This method does not need to return something that would actually work in a command line; it can return any kind of nonsense, so long as it does not change.

get_abspath(*self*)

Return an absolute path to the Node. This will return simply str(Node) by default, but for Node types that have a concept of relative path, this might return something different.

get_binfo(*self*)

Fetch a node's build information.

node - the node whose sources will be collected
cache - alternate node to use for the signature
returns - the build signature

This no longer handles the recursive descent of the node's children's signatures. We expect that they're already built and updated by someone else, if that's what's wanted.

get_build_env(*self*)

Fetch the appropriate Environment to build this node.

get_build_scanner_path(*self*, *scanner*)

Fetch the appropriate scanner path for this node.

get_builder(*self*, *default_builder*=None)

Return the set builder, or a specified default value

get_cachedir_csig(*self*)**get_contents(*self*)**

Fetch the contents of the entry.

get_csig(*self*)

get_env(*self*)

get_env_scanner(*self*, *env*, *kw*={})

get_executor(*self*, *create*=1)

Fetch the action executor for this node. Create one if there isn't already one, and requested to do so.

get_found_includes(*self*, *env*, *scanner*, *path*)

Return the scanned include lines (implicit dependencies) found in this node.

The default is no implicit dependencies. We expect this method to be overridden by any subclass that can be scanned for implicit dependencies.

get_implicit_deps(*self*, *env*, *initial_scanner*, *path_func*, *kw*={})

Return a list of implicit dependencies for this node.

This method exists to handle recursive invocation of the scanner on the implicit dependencies returned by the scanner, if the scanner's recursive flag says that we should.

get_ninfo(*self*)

get_source_scanner(*self*, *node*)

Fetch the source scanner for the specified node

NOTE: "self" is the target being built, "node" is the source file for which we want to fetch the scanner.

Implies self.has_builder() is true; again, expect to only be called from locations where this is already verified.

This function may be called very often; it attempts to cache the scanner found to improve performance.

get_state(*self*)**get_stored_implicit**(*self*)

Fetch the stored implicit dependencies

get_stored_info(*self*)**get_string**(*self*, *for_signature*)

This is a convenience function designed primarily to be used in command generators (i.e., `CommandGeneratorActions` or `Environment` variables that are callable), which are called with a `for_signature` argument that is nonzero if the command generator is being called to generate a signature for the command line, which determines if we should rebuild or not.

Such command generators should use this method in preference to `str(Node)` when converting a `Node` to a string, passing in the `for_signature` parameter, such that we will call `Node.for_signature()` or `str(Node)` properly, depending on whether we are calculating a signature or actually constructing a command line.

get_subst_proxy(*self*)

This method is expected to return an object that will function exactly like this `Node`, except that it implements any additional special features that we would like to be in effect for `Environment` variable substitution. The principle use is that some `Nodes` would like to implement a `__getattr__()` method, but putting that in the `Node` type itself has a tendency to kill performance. We instead put it in a proxy and return it from this method. It is legal for this method to return `self` if no new functionality is needed for `Environment` substitution.

get_suffix(*self*)**get_target_scanner**(*self*)

has_builder(*self*)

Return whether this Node has a builder or not.

In Boolean tests, this turns out to be a *lot* more efficient than simply examining the builder attribute directly ("if node.builder: ..."). When the builder attribute is examined directly, it ends up calling `__getattr__` for both the `__len__` and `__nonzero__` attributes on instances of our Builder Proxy class(es), generating a bazillion extra calls and slowing things down immensely.

has_explicit_builder(*self*)

Return whether this Node has an explicit builder

This allows an internal Builder created by SCons to be marked non-explicit, so that it can be overridden by an explicit builder that the user supplies (the canonical example being directories).

is_derived(*self*)

Returns true if this node is derived (i.e. built).

This should return true only for nodes whose path should be in the variant directory when `duplicate=0` and should contribute their build signatures when they are used as source files to other derived files. For example: source with source builders are not derived in this sense, and hence should not return true.

is_literal(*self*)

Always pass the string representation of a Node to the command interpreter literally.

is_up_to_date(*self*)

Default check for whether the Node is current: unknown Node subtypes are always out of date, so they will always get built.

make_ready(*self*)

Get a Node ready for evaluation.

This is called before the Taskmaster decides if the Node is up-to-date or not. Overriding this method allows for a Node subclass to be disambiguated if necessary, or for an implicit source builder to be attached.

missing(*self*)**multiple_side_effect_has_builder**(*self*)

Return whether this Node has a builder or not.

In Boolean tests, this turns out to be a *lot* more efficient than simply examining the builder attribute directly ("if node.builder: ..."). When the builder attribute is examined directly, it ends up calling `__getattr__` for both the `__len__` and `__nonzero__` attributes on instances of our Builder Proxy class(es), generating a bazillion extra calls and slowing things down immensely.

new_binfo(*self*)**new_ninfo**(*self*)**postprocess**(*self*)

Clean up anything we don't need to hang onto after we've been built.

prepare(*self*)

Prepare for this Node to be built.

This is called after the Taskmaster has decided that the Node is out-of-date and must be rebuilt, but before actually calling the method to build the Node.

This default implementation checks that explicit or implicit dependencies either exist or are derived, and initializes the BuildInfo structure that will hold the information about how this node is, uh, built.

(The existence of source files is checked separately by the Executor, which aggregates checks for all of the targets built by a specific action.)

Overriding this method allows for for a Node subclass to remove the underlying file from the file system. Note that subclass methods should call this base class method to get the child check and the BuildInfo structure.

push_to_cache(*self*)

Try to push a node into a cache

release_target_info(*self*)

Called just after this node has been marked up-to-date or was built completely.

This is where we try to release as many target node infos as possible for clean builds and update runs, in order to minimize the overall memory consumption.

By purging attributes that aren't needed any longer after a Node (=File) got built, we don't have to care that much how many KBytes a Node actually requires...as long as we free the memory shortly afterwards.

@see: built() and File.release_target_info()

remove(*self*)

Remove this Node: no-op by default.

render_include_tree(*self*)

Return a text representation, suitable for displaying to the user, of the include tree for the sources of this node.

reset_executor(*self*)

Remove cached executor; forces recompute when needed.

retrieve_from_cache(*self*)

Try to retrieve the node's content from a cache

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in `built()`.

Returns true if the node was successfully retrieved.

rexists(*self*)

Does this node exist locally or in a repository?

scan(*self*)

Scan this node's dependents for implicit dependencies.

scanner_key(*self*)**select_scanner**(*self*, *scanner*)

Selects a scanner for this Node.

This is a separate method so it can be overridden by Node subclasses (specifically, Node.FS.Dir) that *must* use their own Scanner and don't select one the Scanner.Selector that's configured for the target.

```
set_always_build(self, always_build=1)
```

Set the Node's `always_build` value.

```
set_executor(self, executor)
```

Set the action executor for this node.

```
set_explicit(self, is_explicit)
```

```
set_nocache(self, nocache=1)
```

Set the Node's `nocache` value.

```
set_noclean(self, noclean=1)
```

Set the Node's `noclean` value.

```
set_precious(self, precious=1)
```

Set the Node's `precious` value.

```
set_pseudo(self, pseudo=True)
```

Set the Node's `precious` value.

```
set_specific_source(self, source)
```

```
set_state(self, state)
```

```
visited(self)
```

Called just after this node has been visited (with or without a build).

Inherited from object

```

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

```


13.6.2 Properties

Name	Description
always_build	
attributes	
binfo	
builder	
cached	
changed_since_last_built	
depends	
depends_set	
env	
executor	
ignore	
ignore_set	
implicit	
implicit_set	
includes	
is_explicit	
linked	
ninfo	
nocache	
noclean	
precious	
prerequisites	
pseudo	
ref_count	
side_effect	
side_effects	
sources	
sources_set	
state	
store_info	
waiting_parents	
waiting_s_e	
wkids	
<i>Inherited from object</i>	

continued on next page

Name	Description
<code>__class__</code>	

13.7 Class *NodeList*



13.7.1 Methods

<code>__str__(self)</code>
<code>str(x)</code> Overrides: <code>object.__str__</code> <code>exitit</code> (inherited documentation)

Inherited from UserList.UserList

`__add__()`, `__cmp__()`, `__contains__()`, `__delitem__()`, `__delslice__()`, `__eq__()`, `__ge__()`, `__getitem__()`, `__getslice__()`, `__gt__()`, `__iadd__()`, `__imul__()`, `__init__()`, `__le__()`, `__len__()`, `__lt__()`, `__mul__()`, `__ne__()`, `__radd__()`, `__repr__()`, `__rmul__()`, `__setitem__()`, `__setslice__()`, `append()`, `count()`, `extend()`, `index()`, `insert()`, `pop()`, `remove()`, `reverse()`, `sort()`

Inherited from __abcoll.Sequence

`__iter__()`, `__reversed__()`

Inherited from __abcoll.Sized

__subclasshook__()

Inherited from object

__delattr__(), __format__(), __getattr__(), __new__(), __reduce__(),
__reduce_ex__(), __setattr__(), __sizeof__()

13.7.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

13.7.3 Class Variables

Name	Description
<i>Inherited from UserList.UserList</i> __abstractmethods__, __hash__	

13.8 Class Walker

object —
 SCons.Node.Walker

An iterator for walking a Node tree.

This is depth-first, children are visited before the parent. The Walker object can be initialized with any node, and returns the next node on the descent with each `get_next()` call. 'kids_func' is an optional function that will be called to get the children of a node instead of calling 'children'. 'cycle_func' is an optional function that will be called when a cycle is detected.

This class does not get caught in node cycles caused, for example, by C header file include loops.

13.8.1 Methods

```
__init__(self, node, kids_func=<function get_children at
0x7f2c4333c2a8>, cycle_func=<function ignore_cycle at
0x7f2c4333c320>, eval_func=<function do_nothing at 0x7f2c4333c398>)
x.__init__(...) initializes x; see help(type(x)) for signature  Overrides:
object.__init__  extit(inherited documentation)
```

```
get_next(self)
```

Return the next node for this walk of the tree.

This function is intentionally iterative, not recursive, to sidestep any issues of stack size limitations.

```
is_done(self)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

13.8.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

14 Module *SCons.Node.Alias*

scons.Node.Alias

Alias nodes.

This creates a hash of global Aliases (dummy targets).

14.1 Variables

Name	Description
<code>__revision__</code>	Value: <code>'src/engine/SCons/Node/Alias.py 74b2c53bc42290e911b334a6b...</code>
<code>default__ans</code>	Value: <code>{}</code>
<code>__package__</code>	Value: <code>'SCons.Node'</code>

14.2 Class *AliasNameSpace*

UserDict.UserDict —
 SCons.Node.Alias.AliasNameSpace

14.2.1 Methods

<i>Alias</i> (<i>self</i> , <i>name</i> , <i>**kw</i>)
--

<i>lookup</i> (<i>self</i> , <i>name</i> , <i>**kw</i>)

Inherited from UserDict.UserDict

`__cmp__()`, `__contains__()`, `__delitem__()`, `__getitem__()`, `__init__()`,
`__len__()`, `__repr__()`, `__setitem__()`, `clear()`, `copy()`, `fromkeys()`, `get()`, `has__key()`,
`items()`, `iteritems()`, `iterkeys()`, `itervalues()`, `keys()`, `pop()`, `popitem()`, `setdefault()`,
`update()`, `values()`

14.2.2 Class Variables

Name	Description
<i>Inherited from UserDict.UserDict</i> <code>__hash__</code>	

14.3 Class *AliasNodeInfo*



The generic base class for signature information for a Node.

Node subclasses should subclass *NodeInfoBase* to provide their own logic for dealing with their own Node-specific signature information.

14.3.1 Methods

<code>str__to__node(self, s)</code>
--

<code>__getstate__(self)</code>
--

<p>Return all fields that shall be pickled. Walk the slots in the class hierarchy and add those to the state dictionary. If a '<code>__dict__</code>' slot is available, copy all entries to the dictionary. Also include the version id, which is fixed for all instances of a class. Overrides: <i>SCons.Node.NodeInfoBase.__getstate__</i></p>

<code>__setstate__(self, state)</code>

<p>Restore the attributes from a pickled state. Overrides: <i>SCons.Node.NodeInfoBase.__setstate__</i></p>
--

Inherited from *SCons.Node.NodeInfoBase*(Section 13.4)

`convert()`, `format()`, `merge()`, `update()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__init__()`,
`__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`,
`__sizeof__()`, `__str__()`, `__subclasshook__()`

14.3.2 Properties

Name	Description
<code>csig</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

14.3.3 Class Variables

Name	Description
<code>current_version_id</code>	Value: 2
<code>field_list</code>	Value: ['csig']

14.4 Class *AliasBuildInfo*



The generic base class for build information for a Node.

This is what gets stored in a `.sconsign` file for each target file. It contains a `NodeInfo` instance for this node (signature information that's specific to the type of Node) and direct attributes for the generic build stuff we have to track: sources, explicit dependencies, implicit dependencies, and action information.

14.4.1 Methods

Inherited from `SCons.Node.BuildInfoBase` (Section 13.5)

`__getstate__()`, `__init__()`, `__setstate__()`, `merge()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

14.4.2 Properties

Name	Description
<i>Inherited from <code>SCons.Node.BuildInfoBase</code> (Section 13.5)</i>	


continued on next page

Name	Description
bact, bactsig, bdepends, bdependsigs, bimplicit, bimplicitsigs, bsources, bsourcesigs	
<i>Inherited from object</i>	
__class__	

14.4.3 Class Variables

Name	Description
current_version_id	Value: 2

14.5 Class Alias



14.5.1 Methods

__init__ (<i>self</i> , <i>name</i>) x. __init__ (...) initializes x; see help(type(x)) for signature Overrides: object. __init__ extit(inherited documentation)
str_for_display (<i>self</i>)
__str__ (<i>self</i>) str(x) Overrides: object. __str__ extit(inherited documentation)
make_ready (<i>self</i>) Get a Node ready for evaluation. This is called before the Taskmaster decides if the Node is up-to-date or not. Overriding this method allows for a Node subclass to be disambiguated if necessary, or for an implicit source builder to be attached. Overrides: SCons.Node.Node. make_ready extit(inherited documentation)

really_build(*self*, ***kw*)

Actually build the node.

This is called by the Taskmaster after it's decided that the Node is out-of-date and must be rebuilt, and after the prepare() method has gotten everything, uh, prepared.

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in built().

is_up_to_date(*self*)

Alternate check for whether the Node is current: If all of our children were up-to-date, then this Node was up-to-date, too.

The SCons.Node.Alias and SCons.Node.Python.Value subclasses rebind their current() method to this method. Overrides:
SCons.Node.Node.is_up_to_date

is_under(*self*, *dir*)**get_contents**(*self*)

The contents of an alias is the concatenation of the content signatures of all its sources. Overrides: SCons.Node.Node.get_contents

sconsign(*self*)

An Alias is not recorded in .sconsign files

build(*self*)

A "builder" for aliases. Overrides: SCons.Node.Node.build

convert(*self*)

get_csig(*self*)

Generate a node's content signature, the digested signature of its content.

node - the node cache - alternate node to use for the signature cache returns - the content signature Overrides: SCons.Node.Node.get_csig

Inherited from SCons.Node.Node(Section 13.6)

Decider(), GetTag(), Tag(), add_dependency(), add_ignore(), add_prerequisite(), add_source(), add_to_implicit(), add_to_waiting_parents(), add_to_waiting_s_e(), add_wkid(), all_children(), alter_targets(), builder_set(), built(), changed(), children(), children_are_up_to_date(), clear(), clear_memoized_values(), del_binfo(), disambiguate(), env_set(), executor_cleanup(), exists(), explain(), for_signature(), get_abspath(), get_binfo(), get_build_env(), get_build_scanner_path(), get_builder(), get_cachedir_csig(), get_env(), get_env_scanner(), get_executor(), get_found_includes(), get_implicit_deps(), get_ninfo(), get_source_scanner(), get_state(), get_stored_implicit(), get_stored_info(), get_string(), get_subst_proxy(), get_suffix(), get_target_scanner(), has_builder(), has_explicit_builder(), is_derived(), is_literal(), missing(), multiple_side_effect_has_builder(), new_binfo(), new_ninfo(), postprocess(), prepare(), push_to_cache(), release_target_info(), remove(), render_include_tree(), reset_executor(), retrieve_from_cache(), reexists(), scan(), scanner_key(), select_scanner(), set_always_build(), set_executor(), set_explicit(), set_nocache(), set_noclean(), set_precious(), set_pseudo(), set_specific_source(), set_state(), visited()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __subclasshook__()

14.5.2 Properties

Name	Description
<i>Inherited from SCons.Node.Node (Section 13.6)</i>	
always_build, attributes, binfo, builder, cached, changed_since_last_build, depends, depends_set, env, executor, ignore, ignore_set, implicit, implicit_set, includes, is_explicit, linked, ninfo, nocache, noclean, precious, prerequisites, pseudo, ref_count, side_effect, side_effects, sources, sources_set, state, store_info, waiting_parents, waiting_s_e, wkids	
<i>Inherited from object</i>	
__class__	

15 Module **SCons.Node.FS**

`scons.Node.FS`

File system nodes.

These Nodes represent the canonical external objects that people think of when they think of building software: files and directories.

This holds a "default_fs" variable that should be initialized with an FS that can be used by scripts or modules looking for the canonical default.

15.1 Functions

<code>sconsign__none(<i>node</i>)</code>
--

<code>sconsign__dir(<i>node</i>)</code>

Return the .sconsign file info for this directory, creating it first if necessary.
--

<code>save__strings(<i>val</i>)</code>
--

<code>initialize__do__splitdrive()</code>

<code>needs__normpath__match(...)</code>
--

<code>match(string[, pos[, endpos]]) --> match object or None. Matches zero or more characters at the beginning of the string</code>

<code>set__duplicate(<i>duplicate</i>)</code>

<code>LinkFunc(<i>target, source, env</i>)</code>

<code>LocalString(<i>target, source, env</i>)</code>
--

<code>UnlinkFunc(<i>target, source, env</i>)</code>

<code>MkdirFunc(<i>target, source, env</i>)</code>
--

```
get_MkdirBuilder()
```

```
do_diskcheck_match(node, predicate, errorfmt)
```

```
ignore_diskcheck_match(node, predicate, errorfmt)
```

```
set_diskcheck(list)
```

```
diskcheck_types()
```

```
has_glob_magic(s)
```

```
get_default_fs()
```

```
find_file(filename, paths, verbose=None)
```

Find a node corresponding to either a derived file or a file that exists already.

Only the first file found is returned, and none is returned if no file is found.

filename: A filename to find
paths: A list of directory path *nodes* to search in.
Can be represented as a list, a tuple, or a callable that is called with no arguments and returns the list or tuple.

returns The node created from the found file.

```
invalidate_node_memos(targets)
```

Invalidate the memoized values of all Nodes (files or directories) that are associated with the given entries. Has been added to clear the cache of nodes affected by a direct execution of an action (e.g. Delete/Copy/Chmod). Existing Node caches become inconsistent if the action is run through `Execute()`. The argument **targets** can be a single Node object or filename, or a sequence of Nodes/filenames.


15.2 Variables

continued on next page

Name	Description
------	-------------

Name	Description
__revision__	Value: 'src/engine/SCons/Node/FS.py 74b2c53bc42290e911b334a6b44f...
print_duplicate	Value: 0
default_max_drift	Value: 172800
Save_Strings	Value: None
do_splitdrive	Value: False
needs_normpath_check	Value: re.compile(r'(?x).*// (.*/)?\.\.(?:/ \$) \./ .*\/\.(?:/ \$)')
Valid_Duplicates	Value: ['hard-soft-copy', 'soft-hard-copy', 'hard-copy', 'soft-c...']
Link_Funcs	Value: []
Link	Value: SCons.Action.Action(LinkFunc, None)
LocalCopy	Value: SCons.Action.Action(LinkFunc, LocalString)
Unlink	Value: SCons.Action.Action(UnlinkFunc, None)
Mkdir	Value: SCons.Action.Action(MkdirFunc, None, presub= None)
MkdirBuilder	Value: None
diskcheck_match	Value: DiskChecker('match', do_diskcheck_match, ignore_diskcheck...)
diskcheckers	Value: [diskcheck_match,]
node_bwcomp	Value: {'abspath': <unbound method Base.get_abspath>, 'labspath'...
glob_magic_check	Value: re.compile(r'[*\?\[]')
default_fs	Value: None
OS_SEP	Value: '/'
UNC_PREFIX	Value: '///'
__package__	Value: 'SCons.Node'
has_unc	Value: False
os_sep_is_slash	Value: True

15.3 Class `EntryProxyAttributeError`



An `AttributeError` subclass for recording and displaying the name of the underlying `Entry` involved in an `AttributeError` exception.

15.3.1 Methods

<code>__init__(self, entry_proxy, attribute)</code>

<code>x.__init__(...)</code> initializes <code>x</code> ; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)

<code>__str__(self)</code>

<code>str(x)</code> Overrides: <code>object.__str__</code> <code>exitit</code> (inherited documentation)
--

Inherited from `exceptions.AttributeError`

`__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__unicode__()`

Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

15.3.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	

continued on next page

Name	Description
args, message	
<i>Inherited from object</i>	
__class__	

15.4 Class *DiskChecker*



15.4.1 Methods

__init__ (<i>self</i> , <i>type</i> , <i>do</i> , <i>ignore</i>)
x. __init__ (...) initializes x; see help(type(x)) for signature Overrides: object. __init__ extit(inherited documentation)

__call__ (<i>self</i> , * <i>args</i> , ** <i>kw</i>)
--

set (<i>self</i> , <i>list</i>)
--

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

15.4.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

15.5 Class EntryProxy



15.5.1 Methods

__str__(...)

A Python Descriptor class that delegates attribute fetches to an underlying wrapped subject of a Proxy. Typical use:

```
class Foo(Proxy): __str__ = Delegate('__str__')
```

Overrides: object.__str__

__hash__(...)

A Python Descriptor class that delegates attribute fetches to an underlying wrapped subject of a Proxy. Typical use:

```
class Foo(Proxy): __str__ = Delegate('__str__')
```

Overrides: object.__hash__

__getattr__(self, name)

Retrieve an attribute from the wrapped object. If the named attribute doesn't exist, AttributeError is raised Overrides: SCons.Util.Proxy.__getattr__
extit(inherited documentation)

Inherited from SCons.Util.Proxy(Section 36.5)

__eq__(), **__init__**(), **get**()

Inherited from object

__delattr__(), **__format__**(), **__getattribute__**(), **__new__**(), **__reduce__**(),
__reduce_ex__(), **__repr__**(), **__setattr__**(), **__sizeof__**(), **__subclasshook__**()


15.5.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

15.5.3 Class Variables

Name	Description
dictSpecialAttrs	Value: {"base": __get_base_path, "posix": __get_posix_path, "win..."

15.6 Class Base



Known Subclasses: SCons.Node.FS.Dir, SCons.Node.FS.Entry, SCons.Node.FS.File

A generic class for file system entries. This class is for when we don't know yet whether the entry being looked up is a file or a directory. Instances of this class can morph into either Dir or File objects by a later, more precise lookup.

Note: this class does not define __cmp__ and __hash__ for efficiency reasons. SCons does a lot of comparing of Node.FS.{Base,Entry,File,Dir} objects, so those operations must be as fast as possible, which means we want to use Python's built-in object identity comparisons.

15.6.1 Methods

__init__ (<i>self</i> , <i>name</i> , <i>directory</i> , <i>fs</i>)
Initialize a generic Node.FS.Base object. Call the superclass initialization, take care of setting up our relative and absolute paths, identify our parent directory, and indicate that this node should use signatures. Overrides: object.__init__
str_for_display (<i>self</i>)

must_be_same(*self*, *klass*)

This node, which already existed, is being looked up as the specified klass. Raise an exception if it isn't.

get_dir(*self*)

get_suffix(*self*)

Overrides: SCons.Node.Node.get_suffix

rfile(*self*)

__getattr__(*self*, *attr*)

Together with the node_bwcomp dict defined below, this method provides a simple backward compatibility layer for the Node attributes 'abspath', 'labspath', 'path', 'tpath', 'suffix' and 'path_elements'. These Node attributes used to be directly available in v2.3 and earlier, but have been replaced by getter methods that initialize the single variables lazily when required, in order to save memory. The redirection to the getters lets older Tools and SConstruct continue to work without any additional changes, fully transparent to the user. Note, that __getattr__ is only called as fallback when the requested attribute can't be found, so there should be no speed performance penalty involved for standard builds.

__str__(*self*)

A Node.FS.Base object's string representation is its path name. Overrides: object.__str__

__lt__(*self*, *other*)

less than operator used by sorting on py3

rstr(*self*)

A Node.FS.Base object's string representation is its path name.

stat(*self*)**exists**(*self*)

Does this node exists? Overrides: SCons.Node.Node.exists extit(inherited documentation)

rexists(*self*)

Does this node exist locally or in a repository? Overrides: SCons.Node.Node.rexists extit(inherited documentation)

getmtime(*self*)**getsize**(*self*)**isdir**(*self*)**isfile**(*self*)**islink**(*self*)**is_under**(*self*, *dir*)**set_local**(*self*)**srcnode**(*self*)

If this node is in a build path, return the node corresponding to its source file. Otherwise, return ourself.

get_path(*self*, *dir*=None)

Return path relative to the current working directory of the Node.FS.Base object that owns us.

set_src_builder(*self*, *builder*)

Set the source code builder for this node.

src_builder(*self*)

Fetch the source code builder for this node.

If there isn't one, we cache the source code builder specified for the directory (which in turn will cache the value from its parent directory, and so on up to the file system root).

get_abspath(*self*)

Get the absolute path of the file. Overrides: SCons.Node.Node.get_abspath

get_labspath(*self*)

Get the absolute path of the file.

get_internal_path(*self*)**get_tpath**(*self*)**get_path_elements**(*self*)

for_signature(*self*)

Return a string representation of the Node that will always be the same for this particular Node, no matter what. This is by contrast to the `__str__()` method, which might, for instance, return a relative path for a file Node. The purpose of this method is to generate a value to be used in signature calculation for the command line used to build a target, and we use this method instead of `str()` to avoid unnecessary rebuilds. This method does not need to return something that would actually work in a command line; it can return any kind of nonsense, so long as it does not change. Overrides: `SCons.Node.Node.for_signature` `exitit`(inherited documentation)

get_subst_proxy(*self*)

This method is expected to return an object that will function exactly like this Node, except that it implements any additional special features that we would like to be in effect for Environment variable substitution. The principle use is that some Nodes would like to implement a `__getattr__()` method, but putting that in the Node type itself has a tendency to kill performance. We instead put it in a proxy and return it from this method. It is legal for this method to return `self` if no new functionality is needed for Environment substitution. Overrides: `SCons.Node.Node.get_subst_proxy` `exitit`(inherited documentation)

target_from_source(*self*, *prefix*, *suffix*, *splitext*=<function splitext at 0x7f2c43d6ad70>)

Generates a target entry that corresponds to this entry (usually a source file) with the specified prefix and suffix.

Note that this method can be overridden dynamically for generated files that need different behavior. See `Tool/swig.py` for an example.

Rfindalldirs(*self*, *pathlist*)

Return all of the directories for a given path list, including corresponding "backing" directories in any repositories.

The Node lookups are relative to this Node (typically a directory), so memoizing result saves cycles from looking up the same path for each target in a given directory.

RDirs (<i>self</i> , <i>pathlist</i>)
--

Search for a list of directories in the Repository list.
--

rentry (<i>self</i>)

Inherited from SCons.Node.Node(Section 13.6)

Decider(), GetTag(), Tag(), add_dependency(), add_ignore(), add_prerequisite(), add_source(), add_to_implicit(), add_to_waiting_parents(), add_to_waiting_s_e(), add_wkid(), all_children(), alter_targets(), build(), builder_set(), built(), changed(), children(), children_are_up_to_date(), clear(), clear_memoized_values(), del_binfo(), disambiguate(), env_set(), executor_cleanup(), explain(), get_binfo(), get_build_env(), get_build_scanner_path(), get_builder(), get_cachedir_csig(), get_contents(), get_csig(), get_env(), get_env_scanner(), get_executor(), get_found_includes(), get_implicit_deps(), get_ninfo(), get_source_scanner(), get_state(), get_stored_implicit(), get_stored_info(), get_string(), get_target_scanner(), has_builder(), has_explicit_builder(), is_derived(), is_literal(), is_up_to_date(), make_ready(), missing(), multiple_side_effect_has_bui, new_binfo(), new_ninfo(), postprocess(), prepare(), push_to_cache(), release_target_info(), remove(), render_include_tree(), reset_executor(), retrieve_from_cache(), scan(), scanner_key(), select_scanner(), set_always_build(), set_executor(), set_explicit(), set_nocache(), set_noclean(), set_precious(), set_pseudo(), set_specific_source(), set_state(), visited()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __subclasshook__()

15.6.2 Properties

Name	Description
cwd	
dir	
duplicate	
name	
sbuilder	
<i>Inherited from SCons.Node.Node (Section 13.6)</i>	


continued on next page

Name	Description
always_build, attributes, binfo, builder, cached, changed_since_last_build, depends, depends_set, env, executor, ignore, ignore_set, implicit, implicit_set, includes, is_explicit, linked, ninfo, nocache, noclean, precious, prerequisites, pseudo, ref_count, side_effect, side_effects, sources, sources_set, state, store_info, waiting_parents, waiting_s_e, wkids	
<i>Inherited from object</i>	
__class__	

15.6.3 Instance Variables

Name	Description
fs	

15.7 Class Entry



This is the class for generic Node.FS entries--that is, things that could be a File or a Dir, but we're just not sure yet. Consequently, the methods in this class really exist just to transform their associated object into the right class when the time comes, and then call the same-named method in the transformed class.

15.7.1 Methods

__init__ (<i>self, name, directory, fs</i>) Initialize a generic Node.FS.Base object. Call the superclass initialization, take care of setting up our relative and absolute paths, identify our parent directory, and indicate that this node should use signatures. Overrides: object.__init__ exitit(inherited documentation)
--

diskcheck_match(*self*)

disambiguate(*self*, *must_exist*=None)

Overrides: SCons.Node.Node.disambiguate

rfile(*self*)

We're a generic Entry, but the caller is actually looking for a File at this point, so morph into one. Overrides: SCons.Node.FS.Base.rfile

scanner_key(*self*)

Overrides: SCons.Node.Node.scanner_key

get_contents(*self*)

Fetch the contents of the entry. Returns the exact binary contents of the file. Overrides: SCons.Node.Node.get_contents

get_text_contents(*self*)

Fetch the decoded text contents of a Unicode encoded Entry.

Since this should return the text contents from the file system, we check to see into what sort of subclass we should morph this Entry.

must_be_same(*self*, *klass*)

Called to make sure a Node is a Dir. Since we're an Entry, we can morph into one. Overrides: SCons.Node.FS.Base.must_be_same

exists(*self*)

Does this node exists? Overrides: SCons.Node.Node.exists extit(inherited documentation)

rel_path(*self*, *other*)

```
new_ninfo(self)
```

Overrides: SCons.Node.Node.new_ninfo

```
get_subst_proxy(self)
```

This method is expected to return an object that will function exactly like this Node, except that it implements any additional special features that we would like to be in effect for Environment variable substitution. The principle use is that some Nodes would like to implement a `__getattr__()` method, but putting that in the Node type itself has a tendency to kill performance. We instead put it in a proxy and return it from this method. It is legal for this method to return self if no new functionality is needed for Environment substitution. Overrides: SCons.Node.Node.get_subst_proxy extit(inherited documentation)

Inherited from SCons.Node.FS.Base(Section 15.6)

RDirs(), Rfindalldirs(), `__getattr__()`, `__lt__()`, `__str__()`, `for_signature()`, `get_abspath()`, `get_dir()`, `get_internal_path()`, `get_labspath()`, `get_path()`, `get_path_elements()`, `get_suffix()`, `get_tpath()`, `getmtime()`, `getsize()`, `is_under()`, `isdir()`, `isfile()`, `islink()`, `reentry()`, `rexists()`, `rstr()`, `set_local()`, `set_src_builder()`, `src_builder()`, `sr_cnode()`, `stat()`, `str_for_display()`, `target_from_source()`

Inherited from SCons.Node.Node(Section 13.6)

Decider(), GetTag(), Tag(), `add_dependency()`, `add_ignore()`, `add_prerequisite()`, `add_source()`, `add_to_implicit()`, `add_to_waiting_parents()`, `add_to_waiting_s_e()`, `add_wkid()`, `all_children()`, `alter_targets()`, `build()`, `builder_set()`, `built()`, `changed()`, `children()`, `children_are_up_to_date()`, `clear()`, `clear_memoized_values()`, `del_binfo()`, `env_set()`, `executor_cleanup()`, `explain()`, `get_binfo()`, `get_build_env()`, `get_build_scanner_path()`, `get_builder()`, `get_cachedir_csig()`, `get_csig()`, `get_env()`, `get_env_scanner()`, `get_executor()`, `get_found_includes()`, `get_implicit_deps()`, `get_ninfo()`, `get_source_scanner()`, `get_state()`, `get_stored_implicit()`, `get_stored_info()`, `get_string()`, `get_target_scanner()`, `has_builder()`, `has_explicit_builder()`, `is_derived()`, `is_literal()`, `is_up_to_date()`, `make_ready()`, `missing()`, `multiple_side_effect_has_builder()`, `new_binfo()`, `post-process()`, `prepare()`, `push_to_cache()`, `release_target_info()`, `remove()`, `render_include_tree()`, `reset_executor()`, `retrieve_from_cache()`, `scan()`, `select_scanner()`, `set_always_build()`, `set_executor()`, `set_explicit()`, `set_nocache()`, `set_noclean()`, `set_precious()`, `set_pseudo()`, `set_specific_source()`, `set_state()`, `visited()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__subclasshook__()`

15.7.2 Properties

Name	Description
cachedir_csig	
cachesig	
contentsig	
dirname	
entries	
on_disk_entries	
released_target_info	
repositories	
root	
scanner_paths	
searched	
srcdir	
variant_dirs	
<i>Inherited from SCons.Node.FS.Base (Section 15.6)</i>	
cwd, dir, duplicate, name, sbuilder	
<i>Inherited from SCons.Node.Node (Section 13.6)</i>	
always_build, attributes, binfo, builder, cached, changed_since_last_build, depends, depends_set, env, executor, ignore, ignore_set, implicit, implicit_set, includes, is_explicit, linked, ninfo, nocache, noclean, precious, prerequisites, pseudo, ref_count, side_effect, side_effects, sources, sources_set, state, store_info, waiting_parents, waiting_s_e, wkids	
<i>Inherited from object</i>	
__class__	

15.7.3 Instance Variables

Name	Description
<i>Inherited from SCons.Node.FS.Base (Section 15.6)</i>	
fs	

15.8 Class LocalFS

```

object └─ SCons.Node.FS.LocalFS

```

Known Subclasses: SCons.Node.FS.FS

15.8.1 Methods

`chmod(self, path, mode)``copy(self, src, dst)``copy2(self, src, dst)``exists(self, path)``getmtime(self, path)``getsize(self, path)``isdir(self, path)``isfile(self, path)``link(self, src, dst)``lstat(self, path)``listdir(self, path)``makedirs(self, path)``mkdir(self, path)``rename(self, old, new)``stat(self, path)``symlink(self, src, dst)``open(self, path)``unlink(self, path)``islink(self, path)`

readlink(*self*, *file*)

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __init__(),
 __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(),
 __sizeof__(), __str__(), __subclasshook__()

15.8.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

15.9 Class FS



15.9.1 Methods

__init__(*self*, *path*=None)

Initialize the Node.FS subsystem.

The supplied path is the top of the source tree, where we expect to find the top-level build file. If no path is supplied, the current directory is the default.

The path argument must be a valid absolute path. Overrides:
object.__init__

set_SConstruct_dir(*self*, *dir*)

get_max_drift(*self*)

set_max_drift(*self*, *max_drift*)

getcwd(*self*)

chdir(*self*, *dir*, *change_os_dir*=0)

Change the current working directory for lookups. If *change_os_dir* is true, we will also change the "real" cwd to match.

get_root(*self*, *drive*)

Returns the root directory for the specified drive, creating it if necessary.

Entry(*self*, *name*, *directory*=None, *create*=1)

Look up or create a generic Entry node with the specified name. If the name is a relative path (begins with ./, ../, or a file name), then it is looked up relative to the supplied directory node, or to the top level directory of the FS (supplied at construction time) if no directory is supplied.

File(*self*, *name*, *directory*=None, *create*=1)

Look up or create a File node with the specified name. If the name is a relative path (begins with ./, ../, or a file name), then it is looked up relative to the supplied directory node, or to the top level directory of the FS (supplied at construction time) if no directory is supplied.

This method will raise TypeError if a directory is found at the specified path.

Dir(*self*, *name*, *directory*=None, *create*=True)

Look up or create a Dir node with the specified name. If the name is a relative path (begins with ./, ../, or a file name), then it is looked up relative to the supplied directory node, or to the top level directory of the FS (supplied at construction time) if no directory is supplied.

This method will raise TypeError if a normal file is found at the specified path.

VariantDir(*self*, *variant_dir*, *src_dir*, *duplicate=1*)

Link the supplied variant directory to the source directory for purposes of building files.

Repository(*self*, **dirs*)

Specify Repository directories to search.

PyPackageDir(*self*, *modulename*)

Locate the directory of a given python module name

For example scon might resolve to Windows:

C:\Python27\Lib\site-packages\scons-2.5.1 Linux: /usr/lib/scons

This can be useful when we want to determine a toolpath based on a python module name

variant_dir_target_climb(*self*, *orig*, *dir*, *tail*)

Create targets in corresponding variant directories

Climb the directory tree, and look up path names relative to any linked variant directories we find.

Even though this loops and walks up the tree, we don't memoize the return value because this is really only used to process the command-line targets.

Glob(*self*, *pathname*, *ondisk=True*, *source=True*, *strings=False*, *exclude=None*, *cwd=None*)

Globs

This is mainly a shim layer

Inherited from SCons.Node.FS.LocalFS(Section 15.8)

chmod(), copy(), copy2(), exists(), getmtime(), getsize(), isdir(), isfile(), islink(),

link(), listdir(), lstat(), makedirs(), mkdir(), open(), readlink(), rename(), stat(),
symlink(), unlink()


Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

15.9.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

15.10 Class DirNodeInfo



The generic base class for signature information for a Node.

Node subclasses should subclass NodeInfoBase to provide their own logic for dealing with their own Node-specific signature information.

15.10.1 Methods

<code>str_to_node(self, s)</code>

Inherited from SCons.Node.NodeInfoBase(Section 13.4)

__getstate__(), __setstate__(), convert(), format(), merge(), update()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __init__(),
__new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(),
__sizeof__(), __str__(), __subclasshook__()


15.10.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

15.10.3 Class Variables

Name	Description
current_version_id	Value: 2
fs	Value: None

15.11 Class *DirBuildInfo*



The generic base class for build information for a Node.

This is what gets stored in a .sconsign file for each target file. It contains a NodeInfo instance for this node (signature information that's specific to the type of Node) and direct attributes for the generic build stuff we have to track: sources, explicit dependencies, implicit dependencies, and action information.

15.11.1 Methods

Inherited from SCons.Node.BuildInfoBase (Section 13.5)

__getstate__(), __init__(), __setstate__(), merge()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

15.11.2 Properties

Name	Description
<i>Inherited from SCons.Node.BuildInfoBase (Section 13.5)</i>	


continued on next page

Name	Description
bact, bactsig, bdepends, bdependsigs, bimplicit, bimplicitsigs, bsources, bsourcesigs	
<i>Inherited from object</i>	
__class__	

15.11.3 Class Variables

Name	Description
current_version_id	Value: 2

15.12 Class Dir



Known Subclasses: SCons.Node.FS.RootDir

A class for directories in a file system.

15.12.1 Methods

__init__ (<i>self</i> , <i>name</i> , <i>directory</i> , <i>fs</i>) Initialize a generic Node.FS.Base object. Call the superclass initialization, take care of setting up our relative and absolute paths, identify our parent directory, and indicate that this node should use signatures. Overrides: object.__init__ extit(inherited documentation)
diskcheck_match (<i>self</i>)

Entry(*self*, *name*)

Looks up or creates an entry node named 'name' relative to this directory.

Dir(*self*, *name*, *create*=True)

Looks up or creates a directory node named 'name' relative to this directory.

File(*self*, *name*)

Looks up or creates a file node named 'name' relative to this directory.

link(*self*, *srcdir*, *duplicate*)

Set this directory as the variant directory for the supplied source directory.

getRepositories(*self*)

Returns a list of repositories for this directory.

get_all_rdirs(*self*)**addRepository**(*self*, *dir*)**up**(*self*)**rel_path**(*self*, *other*)

Return a path to "other" relative to this directory.

get_env_scanner(*self*, *env*, *kw*={})

Overrides: *SCons.Node.Node.get_env_scanner*

get_target_scanner(*self*)

Overrides: SCons.Node.Node.get_target_scanner

get_found_includes(*self, env, scanner, path*)

Return this directory's implicit dependencies.

We don't bother caching the results because the scan typically shouldn't be requested more than once (as opposed to scanning .h file contents, which can be requested as many times as the file is #included by other files).

Overrides: SCons.Node.Node.get_found_includes

prepare(*self*)

Prepare for this Node to be built.

This is called after the Taskmaster has decided that the Node is out-of-date and must be rebuilt, but before actually calling the method to build the Node.

This default implementation checks that explicit or implicit dependencies either exist or are derived, and initializes the BuildInfo structure that will hold the information about how this node is, uh, built.

(The existence of source files is checked separately by the Executor, which aggregates checks for all of the targets built by a specific action.)

Overriding this method allows for for a Node subclass to remove the underlying file from the file system. Note that subclass methods should call this base class method to get the child check and the BuildInfo structure.

Overrides: SCons.Node.Node.prepare extit(inherited documentation)

build(*self, **kw*)

A null "builder" for directories. Overrides: SCons.Node.Node.build

multiple_side_effect_has_builder(*self*)

Return whether this Node has a builder or not.

In Boolean tests, this turns out to be a *lot* more efficient than simply examining the builder attribute directly ("if node.builder: ..."). When the builder attribute is examined directly, it ends up calling `__getattr__` for both the `__len__` and `__nonzero__` attributes on instances of our Builder Proxy class(es), generating a bazillion extra calls and slowing things down immensely. Overrides: `SCons.Node.Node.multiple_side_effect_has_builder` `extit`(inherited documentation)

alter_targets(*self*)

Return any corresponding targets in a variant directory. Overrides: `SCons.Node.Node.alter_targets`

scanner_key(*self*)

A directory does not get scanned. Overrides: `SCons.Node.Node.scanner_key`

get_text_contents(*self*)

We already emit things in text, so just return the binary version.

get_contents(*self*)

Return content signatures and names of all our children separated by new-lines. Ensure that the nodes are sorted. Overrides: `SCons.Node.Node.get_contents`

get_csig(*self*)

Compute the content signature for Directory nodes. In general, this is not needed and the content signature is not stored in the `DirNodeInfo`. However, if `get_contents` on a `Dir` node is called which has a child directory, the child directory should return the hash of its contents. Overrides: `SCons.Node.Node.get_csig`

do_duplicate(*self*, *src*)**is_up_to_date**(*self*)

If any child is not up-to-date, then this directory isn't, either. Overrides: `SCons.Node.Node.is_up_to_date`

rdir(*self*)**sconsign**(*self*)

Return the `.sconsign` file info for this directory.

srcnode(*self*)

`Dir` has a special need for `srcnode()`...if we have a `srcdir` attribute set, then that *is* our `srcnode`. Overrides: `SCons.Node.FS.Base.srcnode`

get_timestamp(*self*)

Return the latest timestamp from among our children

get_abspath(*self*)

Get the absolute path of the file. Overrides: `SCons.Node.Node.get_abspath`

get_labspath(*self*)

Get the absolute path of the file. Overrides:
SCons.Node.FS.Base.get_labspath

get_internal_path(*self*)

Overrides: SCons.Node.FS.Base.get_internal_path

get_tpath(*self*)

Overrides: SCons.Node.FS.Base.get_tpath

get_path_elements(*self*)

Overrides: SCons.Node.FS.Base.get_path_elements

entry_abspath(*self*, *name*)

entry_labspath(*self*, *name*)

entry_path(*self*, *name*)

entry_tpath(*self*, *name*)

entry_exists_on_disk(*self*, *name*)

Searches through the file/dir entries of the current directory, and returns True if a physical entry with the given name could be found.

@see reentry_exists_on_disk

reentry_exists_on_disk(*self*, *name*)

Searches through the file/dir entries of the current *and* all its remote directories (repos), and returns True if a physical entry with the given name could be found. The local directory (*self*) gets searched first, so repositories take a lower precedence regarding the searching order.

@see entry_exists_on_disk

```
srcdir__list(self)
```

```
srcdir__duplicate(self, name)
```

```
srcdir__find__file(self, filename)
```

```
dir__on__disk(self, name)
```

```
file__on__disk(self, name)
```

```
walk(self, func, arg)
```

Walk this directory tree by calling the specified function for each directory in the tree.

This behaves like the `os.path.walk()` function, but for in-memory `Node.FS.Dir` objects. The function takes the same arguments as the functions passed to `os.path.walk()`:

```
func(arg, dirname, fnames)
```

Except that "dirname" will actually be the directory *Node*, not the string. The `'.'` and `'..'` entries are excluded from `fnames`. The `fnames` list may be modified in-place to filter the subdirectories visited or otherwise impose a specific order. The "arg" argument is always passed to `func()` and may be used in any way (or ignored, passing `None` is common).

```
glob(self, pathname, ondisk=True, source=False, strings=False,
      exclude=None)
```

Returns a list of Nodes (or strings) matching a specified pathname pattern.

Pathname patterns follow UNIX shell semantics: * matches any-length strings of any characters, ? matches any character, and [] can enclose lists or ranges of characters. Matches do not span directory separators.

The matches take into account Repositories, returning local Nodes if a corresponding entry exists in a Repository (either an in-memory Node or something on disk).

By default, the glob() function matches entries that exist on-disk, in addition to in-memory Nodes. Setting the "ondisk" argument to False (or some other non-true value) causes the glob() function to only match in-memory Nodes. The default behavior is to return both the on-disk and in-memory Nodes.

The "source" argument, when true, specifies that corresponding source Nodes must be returned if you're globbing in a build directory (initialized with VariantDir()). The default behavior is to return Nodes local to the VariantDir().

The "strings" argument, when true, returns the matches as strings, not Nodes. The strings are path names relative to this directory.

The "exclude" argument, if not None, must be a pattern or a list of patterns following the same UNIX shell semantics. Elements matching a least one pattern of this list will be excluded from the result.

The underlying algorithm is adapted from the glob.glob() function in the Python library (but heavily modified), and uses fnmatch() under the covers.

Inherited from SCons.Node.FS.Base(Section 15.6)

```
RDirs(), Rfindalldirs(), __getattr__(), __lt__(), __str__(), exists(), for_signature(),
get_dir(), get_path(), get_subst_proxy(), get_suffix(), getmtime(), getsize(), is_under(),
isdir(), isfile(), islink(), must_be_same(), reentry(), reexists(), rfile(), rstr(), set_local(),
set_src_builder(), src_builder(), stat(), str_for_display(), target_from_source()
```

Inherited from SCons.Node.Node(Section 13.6)

```
Decider(), GetTag(), Tag(), add_dependency(), add_ignore(), add_prerequisite(),
add_source(), add_to_implicit(), add_to_waiting_parents(), add_to_waiting_s_e(),
add_wkid(), all_children(), builder_set(), built(), changed(), children(), children_are_up_to_date(),
clear(), clear_memoized_values(), del_binfo(), disambiguate(), env_set(), execu-
```

tor_cleanup(), explain(), get_binfo(), get_build_env(), get_build_scanner_path(),
 get_builder(), get_cachedir_csig(), get_env(), get_executor(), get_implicit_deps(),
 get_ninfo(), get_source_scanner(), get_state(), get_stored_implicit(), get_stored_info(),
 get_string(), has_builder(), has_explicit_builder(), is_derived(), is_literal(), make_ready(),
 missing(), new_binfo(), new_ninfo(), postprocess(), push_to_cache(), release_target_info(),
 remove(), render_include_tree(), reset_executor(), retrieve_from_cache(), scan(),
 select_scanner(), set_always_build(), set_executor(), set_explicit(), set_nocache(),
 set_noclean(), set_precious(), set_pseudo(), set_specific_source(), set_state(),
 visited()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __subclasshook__()


15.12.2 Properties

Name	Description
cachedir_csig	
cachesig	
contentsig	
dirname	
entries	
on_disk_entries	
released_target_info	
repositories	
root	
scanner_paths	
searched	
srcdir	
variant_dirs	
<i>Inherited from SCons.Node.FS.Base (Section 15.6)</i>	
cwd, dir, duplicate, name, sbuilder	
<i>Inherited from SCons.Node.Node (Section 13.6)</i>	
always_build, attributes, binfo, builder, cached, changed_since_last_build, depends, depends_set, env, executor, ignore, ignore_set, implicit, implicit_set, includes, is_explicit, linked, ninfo, nocache, noclean, precious, prerequisites, pseudo, ref_count, side_effect, side_effects, sources, sources_set, state, store_info, waiting_parents, waiting_s_e, wkids	
<i>Inherited from object</i>	
__class__	

15.12.3 Instance Variables

Name	Description
<i>Inherited from SCons.Node.FS.Base (Section 15.6)</i> fs	

15.13 Class RootDir



A class for the root directory of a file system.

This is the same as a Dir class, except that the path separator ('/' or '\') is actually part of the name, so we don't need to add a separator when creating the path names of entries within this directory.

15.13.1 Methods

__init__(*self*, *drive*, *fs*)

Initialize a generic Node.FS.Base object.

Call the superclass initialization, take care of setting up our relative and absolute paths, identify our parent directory, and indicate that this node should use signatures. Overrides: object.__init__ extit(inherited documentation)

must_be_same(*self*, *klass*)

This node, which already existed, is being looked up as the specified klass. Raise an exception if it isn't. Overrides: SCons.Node.FS.Base.must_be_same extit(inherited documentation)

__str__(*self*)

A Node.FS.Base object's string representation is its path name. Overrides: object.__str__ exitit(inherited documentation)

entry__abspath(*self*, *name*)

Overrides: SCons.Node.FS.Dir.entry__abspath

entry__labspath(*self*, *name*)

Overrides: SCons.Node.FS.Dir.entry__labspath

entry__path(*self*, *name*)

Overrides: SCons.Node.FS.Dir.entry__path

entry__tpath(*self*, *name*)

Overrides: SCons.Node.FS.Dir.entry__tpath

is_under(*self*, *dir*)

Overrides: SCons.Node.FS.Base.is_under

up(*self*)

Overrides: SCons.Node.FS.Dir.up

get__dir(*self*)

Overrides: SCons.Node.FS.Base.get__dir

src_builder(*self*)

Fetch the source code builder for this node.

If there isn't one, we cache the source code builder specified for the directory (which in turn will cache the value from its parent directory, and so on up to the file system root). Overrides: SCons.Node.FS.Base.src_builder exitit(inherited documentation)

Inherited from SCons.Node.FS.Dir(Section 15.12)

Dir(), Entry(), File(), addRepository(), alter_targets(), build(), dir_on_disk(), diskcheck_match(), do_duplicate(), entry_exists_on_disk(), file_on_disk(), getRepositories(), get_abspath(), get_all_rdirs(), get_contents(), get_csig(), get_env_scanner(), get_found_includes(), get_internal_path(), get_labspath(), get_path_elements(),

get_target_scanner(), get_text_contents(), get_timestamp(), get_tpath(), glob(),
 is_up_to_date(), link(), multiple_side_effect_has_builder(), prepare(), rdir(),
 rel_path(), reentry_exists_on_disk(), scanner_key(), sconsign(), srcdir_duplicate(),
 srcdir_find_file(), srcdir_list(), srcnode(), walk()

Inherited from SCons.Node.FS.Base(Section 15.6)

RDirs(), Rfindalldirs(), __getattr__(), __lt__(), exists(), for_signature(), get_path(),
 get_subst_proxy(), get_suffix(), getmtime(), getsize(), isdir(), isfile(), islink(),
 reentry(), reexists(), rfile(), rstr(), set_local(), set_src_builder(), stat(), str_for_display(),
 target_from_source()

Inherited from SCons.Node.Node(Section 13.6)

Decider(), GetTag(), Tag(), add_dependency(), add_ignore(), add_prerequisite(),
 add_source(), add_to_implicit(), add_to_waiting_parents(), add_to_waiting_s_e(),
 add_wkid(), all_children(), builder_set(), built(), changed(), children(), children_are_up_to_date(),
 clear(), clear_memoized_values(), del_binfo(), disambiguate(), env_set(), execu-
 tor_cleanup(), explain(), get_binfo(), get_build_env(), get_build_scanner_path(),
 get_builder(), get_cachedir_csig(), get_env(), get_executor(), get_implicit_deps(),
 get_ninfo(), get_source_scanner(), get_state(), get_stored_implicit(), get_stored_info(),
 get_string(), has_builder(), has_explicit_builder(), is_derived(), is_literal(), make_ready(),
 missing(), new_binfo(), new_ninfo(), postprocess(), push_to_cache(), release_target_info(),
 remove(), render_include_tree(), reset_executor(), retrieve_from_cache(), scan(),
 select_scanner(), set_always_build(), set_executor(), set_explicit(), set_nocache(),
 set_noclean(), set_precious(), set_pseudo(), set_specific_source(), set_state(),
 visited()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __subclasshook__()

15.13.2 Properties

Name	Description
<i>Inherited from SCons.Node.FS.Dir (Section 15.12)</i>	
cachedir_csig, cachesig, contentsig, dirname, entries, on_disk_entries, released_target_info, repositories, root, scanner_paths, searched, srcdir, variant_dirs	
<i>Inherited from SCons.Node.FS.Base (Section 15.6)</i>	
cwd, dir, duplicate, name, sbuilder	
<i>Inherited from SCons.Node.Node (Section 13.6)</i>	

continued on next page

Name	Description
always_build, attributes, binfo, builder, cached, changed_since_last_build, depends, depends_set, env, executor, ignore, ignore_set, implicit, implicit_set, includes, is_explicit, linked, ninfo, nocache, noclean, precious, prerequisites, pseudo, ref_count, side_effect, side_effects, sources, sources_set, state, store_info, waiting_parents, waiting_s_e, wkids	
<i>Inherited from object</i>	
__class__	

15.13.3 Instance Variables

Name	Description
fs	Reference to parent Node.FS object

15.14 Class FileInfo



The generic base class for signature information for a Node.

Node subclasses should subclass NodeInfoBase to provide their own logic for dealing with their own Node-specific signature information.

15.14.1 Methods

str_to_node (<i>self</i> , <i>s</i>)
__getstate__ (<i>self</i>)
Return all fields that shall be pickled. Walk the slots in the class hierarchy and add those to the state dictionary. If a '___dict___' slot is available, copy all entries to the dictionary. Also include the version id, which is fixed for all instances of a class. Overrides: SCons.Node.NodeInfoBase.__getstate__

<code>__setstate__(self, state)</code>
Restore the attributes from a pickled state. Overrides: SCons.Node.NodeInfoBase.__setstate__

Inherited from SCons.Node.NodeInfoBase(Section 13.4)

convert(), format(), merge(), update()

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__init__()`,
`__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`,
`__sizeof__()`, `__str__()`, `__subclasshook__()`


15.14.2 Properties

Name	Description
csig	
size	
timestamp	
<i>Inherited from object</i>	
<code>__class__</code>	

15.14.3 Class Variables

Name	Description
current_version_id	Value: 2
field_list	Value: ['csig', 'timestamp', 'size']
fs	Value: None

15.15 Class FileBuildInfo



Known Subclasses: SCons.SConf.SConfBuildInfo

The generic base class for build information for a Node.

This is what gets stored in a .sconsign file for each target file. It contains a NodeInfo instance for this node (signature information that's specific to the type of Node) and direct attributes for the generic build stuff we have to track: sources, explicit dependencies, implicit dependencies, and action information.

15.15.1 Methods

convert_from_sconsign(*self*, *dir*, *name*)

Converts a newly-read FileBuildInfo object for in-SCons use

For normal up-to-date checking, we don't have any conversion to perform--but we're leaving this method here to make that clear.

convert_to_sconsign(*self*)

Converts this FileBuildInfo object for writing to a .sconsign file

This replaces each Node in our various dependency lists with its usual string representation: relative to the top-level SConstruct directory, or an absolute path if it's outside.

format(*self*, *names*=0)

prepare_dependencies(*self*)

Prepares a FileBuildInfo object for explaining what changed

The bsources, bdepends and bimplicit lists have all been stored on disk as paths relative to the top-level SConstruct directory. Convert the strings to actual Nodes (for use by the --debug=explain code and --implicit-cache).

Inherited from SCons.Node.BuildInfoBase(Section 13.5)

`__getstate__()`, `__init__()`, `__setstate__()`, `merge()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`


15.15.2 Properties

Name	Description
	<i>Inherited from SCons.Node.BuildInfoBase (Section 13.5)</i> bact, bactsig, bdepends, bdependsigns, bimplicit, bimplicitsigns, bsources, bsourcesigns
	<i>Inherited from object</i> __class__

15.15.3 Class Variables

Name	Description
current_version_id	Value: 2

15.16 Class File



A class for files in a file system.

15.16.1 Methods

diskcheck_match (<i>self</i>)
--

__init__ (<i>self, name, directory, fs</i>)
--

Initialize a generic Node.FS.Base object.

Call the superclass initialization, take care of setting up our relative and absolute paths, identify our parent directory, and indicate that this node should use signatures. Overrides: object.__init__ extit(inherited documentation)

Entry(*self*, *name*)

Create an entry node named 'name' relative to the directory of this file.

Dir(*self*, *name*, *create*=True)

Create a directory node named 'name' relative to the directory of this file.

Dirs(*self*, *pathlist*)

Create a list of directories relative to the SConscript directory of this file.

File(*self*, *name*)

Create a file node named 'name' relative to the directory of this file.

scanner_key(*self*)

Overrides: SCons.Node.Node.scanner_key

get_contents(*self*)

Fetch the contents of the entry. Overrides: SCons.Node.Node.get_contents
extit(inherited documentation)

get_text_contents(*self*)

This attempts to figure out what the encoding of the text is based upon the BOM bytes, and then decodes the contents so that it's a valid python string.

get_content_hash(*self*)

Compute and return the MD5 hash for this file.

get_size(*self*)

get_timestamp(*self*)

convert_old_entry(*self*, *old_entry*)

get_stored_info(*self*)

Overrides: SCons.Node.Node.get_stored_info

get_stored_implicit(*self*)

Fetch the stored implicit dependencies Overrides:
SCons.Node.Node.get_stored_implicit extit(inherited documentation)

rel_path(*self*, *other*)

get_found_includes(*self*, *env*, *scanner*, *path*)

Return the included implicit dependencies in this file. Cache results so we only scan the file once per path regardless of how many times this information is requested. Overrides: SCons.Node.Node.get_found_includes

push_to_cache(*self*)

Try to push the node into a cache Overrides:
SCons.Node.Node.push_to_cache

retrieve_from_cache(*self*)

Try to retrieve the node's content from a cache

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in built().

Returns true if the node was successfully retrieved. Overrides:
SCons.Node.Node.retrieve_from_cache

visited(*self*)

Called just after this node has been visited (with or without a build).
Overrides: SCons.Node.Node.visited extit(inherited documentation)

release_target_info(*self*)

Called just after this node has been marked up-to-date or was built completely.

This is where we try to release as many target node infos as possible for clean builds and update runs, in order to minimize the overall memory consumption.

We'd like to remove a lot more attributes like `self.sources` and `self.sources_set`, but they might get used in a next build step. For example, during configuration the source files for a built `E{*}.o` file are used to figure out which linker to use for the resulting Program (gcc vs. g++)! That's why we check for the 'keep_targetinfo' attribute, config Nodes and the Interactive mode just don't allow an early release of most variables.

In the same manner, we can't simply remove the `self.attributes` here. The smart linking relies on the shared flag, and some parts of the java Tool use it to transport information about nodes...

@see: `built()` and `Node.release_target_info()` Overrides:
`SCons.Node.Node.release_target_info`

find_src_builder(*self*)**has_src_builder(*self*)**

Return whether this Node has a source builder or not.

If this Node doesn't have an explicit source code builder, this is where we figure out, on the fly, if there's a transparent source code builder for it.

Note that if we found a source builder, we also set the `self.builder` attribute, so that all of the methods that actually *build* this file don't have to do anything different.

alter_targets(*self*)

Return any corresponding targets in a variant directory. Overrides:
`SCons.Node.Node.alter_targets`

make_ready(*self*)

Get a Node ready for evaluation.

This is called before the Taskmaster decides if the Node is up-to-date or not. Overriding this method allows for a Node subclass to be disambiguated if necessary, or for an implicit source builder to be attached. Overrides: SCons.Node.Node.make_ready extit(inherited documentation)

prepare(*self*)

Prepare for this file to be created. Overrides: SCons.Node.Node.prepare

remove(*self*)

Remove this file. Overrides: SCons.Node.Node.remove

do_duplicate(*self*, *src*)**exists(*self*)**

Does this node exists? Overrides: SCons.Node.Node.exists extit(inherited documentation)

get_max_drift_csig(*self*)

Returns the content signature currently stored for this node if it's been unmodified longer than the max_drift value, or the max_drift value is 0. Returns None otherwise.

get_csig(*self*)

Generate a node's content signature, the digested signature of its content.

node - the node cache - alternate node to use for the signature cache returns - the content signature Overrides: SCons.Node.Node.get_csig

builder_set(*self*, *builder*)

Overrides: SCons.Node.Node.builder_set

built(*self*)

Called just after this File node is successfully built.

Just like for 'release_target_info' we try to release some more target node attributes in order to minimize the overall memory consumption.

@see: release_target_info Overrides: SCons.Node.Node.built

changed(*self*, *node*=None, *allowcache*=False)

Returns if the node is up-to-date with respect to the BuildInfo stored last time it was built.

For File nodes this is basically a wrapper around Node.changed(), but we allow the return value to get cached after the reference to the Executor got released in release_target_info().

@see: Node.changed() Overrides: SCons.Node.Node.changed

changed_content(*self*, *target*, *prev_ni*)

changed_state(*self*, *target*, *prev_ni*)

changed_timestamp_then_content(*self*, *target*, *prev_ni*)

changed_timestamp_newer(*self*, *target*, *prev_ni*)

changed_timestamp_match(*self*, *target*, *prev_ni*)

is_up_to_date(*self*)

Default check for whether the Node is current: unknown Node subtypes are always out of date, so they will always get built. Overrides: SCons.Node.Node.is_up_to_date extit(inherited documentation)

rfile(*self*)

Overrides: SCons.Node.FS.Base.rfile

rstr(*self*)

A Node.FS.Base object's string representation is its path name. Overrides: SCons.Node.FS.Base.rstr
exitit(inherited documentation)

get__cachedir__csig(*self*)

Fetch a Node's content signature for purposes of computing another Node's cachesig.

This is a wrapper around the normal get_csig() method that handles the somewhat obscure case of using CacheDir with the -n option. Any files that don't exist would normally be "built" by fetching them from the cache, but the normal get_csig() method will try to open up the local file, which doesn't exist because the -n option meant we didn't actually pull the file from cachedir. But since the file *does* actually exist in the cachedir, we can use its contents for the csig. Overrides: SCons.Node.Node.get__cachedir__csig

get__contents__sig(*self*)

A helper method for get__cachedir__bsig.

It computes and returns the signature for this node's contents.

get__cachedir__bsig(*self*)

Return the signature for a cached file, including its children.

It adds the path of the cached file to the cache signature, because multiple targets built by the same action will all have the same build signature, and we have to differentiate them somehow.

Inherited from SCons.Node.FS.Base(Section 15.6)

RDirs(), Rfindalldirs(), __getattr__(), __lt__(), __str__(), for_signature(), get_abspath(), get_dir(), get_internal_path(), get_labspath(), get_path(), get_path_elements(), get_subst_proxy(), get_suffix(), get_tpath(), getmtime(), getsize(), is_under(), isdir(), isfile(), islink(), must_be_same(), reentry(), reexists(), set_local(), set_src_builder(),

src_builder(), srcnode(), stat(), str_for_display(), target_from_source()

Inherited from SCons.Node.Node(Section 13.6)

Decider(), GetTag(), Tag(), add_dependency(), add_ignore(), add_prerequisite(), add_source(), add_to_implicit(), add_to_waiting_parents(), add_to_waiting_s_e(), add_wkid(), all_children(), build(), children(), children_are_up_to_date(), clear(), clear_memoized_values(), del_binfo(), disambiguate(), env_set(), executor_cleanup(), explain(), get_binfo(), get_build_env(), get_build_scanner_path(), get_builder(), get_env(), get_env_scanner(), get_executor(), get_implicit_deps(), get_ninfo(), get_source_scanner(), get_state(), get_string(), get_target_scanner(), has_builder(), has_explicit_builder(), is_derived(), is_literal(), missing(), multiple_side_effect_has_builder(), new_binfo(), new_ninfo(), postprocess(), render_include_tree(), reset_executor(), scan(), select_scanner(), set_always_build(), set_executor(), set_explicit(), set_nocache(), set_noclean(), set_precious(), set_pseudo(), set_specific_source(), set_state()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __subclasshook__()

15.16.2 Properties

Name	Description
cachedir_csig	
cachesig	
contentsig	
dirname	
entries	
on_disk_entries	
released_target_info	
repositories	
root	
scanner_paths	
searched	
srcdir	
variant_dirs	
<i>Inherited from SCons.Node.FS.Base (Section 15.6)</i>	
cwd, dir, duplicate, name, sbuilder	
<i>Inherited from SCons.Node.Node (Section 13.6)</i>	

continued on next page

Name	Description
	always_build, attributes, binfo, builder, cached, changed_since_last_build, depends, depends_set, env, executor, ignore, ignore_set, implicit, implicit_set, includes, is_explicit, linked, ninfo, nocache, noclean, precious, prerequisites, pseudo, ref_count, side_effect, side_effects, sources, sources_set, state, store_info, waiting_parents, waiting_s_e, wkids
<i>Inherited from object</i>	
__class__	

15.16.3 Class Variables

Name	Description
md5_chunksize	Value: 64
convert_copy_attrs	Value: ['bsources', 'bimplicit', 'bdepends', 'bact', 'bactsig', ...]
convert_sig_attrs	Value: ['bsourcesigs', 'bimplicitsigs', 'bdependSIGs']

15.16.4 Instance Variables

Name	Description
<i>Inherited from SCons.Node.FS.Base (Section 15.6)</i>	
fs	

15.17 Class FileFinder

```

object └─ SCons.Node.FS.FileFinder

```

15.17.1 Methods

__init__ (<i>self</i>)
x. __init__ (...) initializes x; see help(type(x)) for signature Overrides: object. __init__ extit(inherited documentation)

filedir_lookup(*self*, *p*, *fd*=None)

A helper method for find_file() that looks up a directory for a file we're trying to find. This only creates the Dir Node if it exists on-disk, since if the directory doesn't exist we know we won't find any files in it... :-)

It would be more compact to just use this as a nested function with a default keyword argument (see the commented-out version below), but that doesn't work unless you have nested scopes, so we define it here just so this work under Python 1.5.2.

find_file(*self*, *filename*, *paths*, *verbose*=None)

Find a node corresponding to either a derived file or a file that exists already.

Only the first file found is returned, and none is returned if no file is found.

filename: A filename to find
paths: A list of directory path *nodes* to search in.
 Can be represented as a list, a tuple, or a callable that is called with no arguments and returns the list or tuple.

returns The node created from the found file.

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

15.17.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

16 Module SCons.Node.Python

scons.Node.Python

Python nodes.

16.1 Variables

Name	Description
<code>__revision__</code>	Value: <code>'src/engine/SCons/Node/Python.py74b2c53bc42290e911b334a6...'</code>
<code>__package__</code>	Value: <code>'SCons.Node'</code>

16.2 Class ValueNodeInfo



The generic base class for signature information for a Node.

Node subclasses should subclass NodeInfoBase to provide their own logic for dealing with their own Node-specific signature information.

16.2.1 Methods

<code>str_to_node(self, s)</code>
--

<code>__getstate__(self)</code>
--

<p>Return all fields that shall be pickled. Walk the slots in the class hierarchy and add those to the state dictionary. If a <code>'__dict__'</code> slot is available, copy all entries to the dictionary. Also include the version id, which is fixed for all instances of a class. Overrides: <code>SCons.Node.NodeInfoBase.__getstate__</code></p>

<code>__setstate__(self, state)</code>
Restore the attributes from a pickled state. Overrides: SCons.Node.NodeInfoBase.__setstate__

Inherited from SCons.Node.NodeInfoBase(Section 13.4)

convert(), format(), merge(), update()

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__init__()`,
`__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`,
`__sizeof__()`, `__str__()`, `__subclasshook__()`

16.2.2 Properties

Name	Description
csig	
<i>Inherited from object</i>	
<code>__class__</code>	

16.2.3 Class Variables

Name	Description
current_version_id	Value: 2
field_list	Value: ['csig']

16.3 Class ValueBuildInfo

object └

SCons.Node.BuildInfoBase └

SCons.Node.Python.ValueBuildInfo

The generic base class for build information for a Node.

This is what gets stored in a .sconsign file for each target file. It contains a NodeInfo instance for this node (signature information that's specific to the type of Node) and direct attributes for the generic build stuff we have to track: sources, explicit dependencies, implicit dependencies, and action information.

16.3.1 Methods

Inherited from SCons.Node.BuildInfoBase(Section 13.5)

`__getstate__()`, `__init__()`, `__setstate__()`, `merge()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

16.3.2 Properties

Name	Description
<i>Inherited from SCons.Node.BuildInfoBase (Section 13.5)</i>	
bact, bactsig, bdepends, bdependsigns, bimplicit, bimplicitsigns, bsources, bsourcesigns	
<i>Inherited from object</i>	
<code>__class__</code>	

16.3.3 Class Variables

Name	Description
<code>current_version_id</code>	Value: 2

16.4 Class Value



A class for Python variables, typically passed on the command line or generated by a script, but not from a file or some other source.

16.4.1 Methods

__init__(*self*, *value*, *built_value*=None)

x.**__init__**(...) initializes *x*; see help(type(*x*)) for signature Overrides: object.**__init__** extit(inherited documentation)

str_for_display(*self*)

__str__(*self*)

str(*x*) Overrides: object.**__str__** extit(inherited documentation)

make_ready(*self*)

Get a Node ready for evaluation.

This is called before the Taskmaster decides if the Node is up-to-date or not. Overriding this method allows for a Node subclass to be disambiguated if necessary, or for an implicit source builder to be attached. Overrides: SCons.Node.Node.make_ready extit(inherited documentation)

build(*self*, ***kw*)

Actually build the node.

This is called by the Taskmaster after it's decided that the Node is out-of-date and must be rebuilt, and after the prepare() method has gotten everything, uh, prepared.

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in built(). Overrides: SCons.Node.Node.build extit(inherited documentation)

is_up_to_date(*self*)

Alternate check for whether the Node is current: If all of our children were up-to-date, then this Node was up-to-date, too.

The SCons.Node.Alias and SCons.Node.Python.Value subclasses rebind their current() method to this method. Overrides: SCons.Node.Node.is_up_to_date

is_under(*self*, *dir*)

write(*self*, *built_value*)

Set the value of the node.

read(*self*)

Return the value. If necessary, the value is built.

get_text_contents(*self*)

By the assumption that the node.built_value is a deterministic product of the sources, the contents of a Value are the concatenation of all the contents of its sources. As the value need not be built when get_contents() is called, we cannot use the actual node.built_value.

get_contents(*self*)

Fetch the contents of the entry. Overrides: SCons.Node.Node.get_contents
exitit(inherited documentation)

changed_since_last_build(*self*, *target*, *prev_ni*)

Overrides: SCons.Node.Node.changed_since_last_build

get_csig(*self*, *calc*=None)

Because we're a Python value node and don't have a real timestamp, we get to ignore the calculator and just use the value contents. Overrides:
SCons.Node.Node.get_csig

Inherited from SCons.Node.Node(Section 13.6)

Decider(), GetTag(), Tag(), add_dependency(), add_ignore(), add_prerequisite(),
add_source(), add_to_implicit(), add_to_waiting_parents(), add_to_waiting_s_e(),
add_wkid(), all_children(), alter_targets(), builder_set(), built(), changed(), chil-
dren(), children_are_up_to_date(), clear(), clear_memoized_values(), del_binfo(),
disambiguate(), env_set(), executor_cleanup(), exists(), explain(), for_signature(),

get_abspath(), get_binfo(), get_build_env(), get_build_scanner_path(), get_builder(),
 get_cachedir_csig(), get_env(), get_env_scanner(), get_executor(), get_found_includes(),
 get_implicit_deps(), get_ninfo(), get_source_scanner(), get_state(), get_stored_implicit(),
 get_stored_info(), get_string(), get_subst_proxy(), get_suffix(), get_target_scanner(),
 has_builder(), has_explicit_builder(), is_derived(), is_literal(), missing(), mul-
 tiple_side_effect_has_builder(), new_binfo(), new_ninfo(), postprocess(), pre-
 pare(), push_to_cache(), release_target_info(), remove(), render_include_tree(),
 reset_executor(), retrieve_from_cache(), reexists(), scan(), scanner_key(), select_scanner(),
 set_always_build(), set_executor(), set_explicit(), set_nocache(), set_noclean(),
 set_precious(), set_pseudo(), set_specific_source(), set_state(), visited()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __subclasshook__()

16.4.2 Properties

Name	Description
<i>Inherited from SCons.Node.Node (Section 13.6)</i>	
always_build, attributes, binfo, builder, cached, depends, depends_set, env, executor, ignore, ignore_set, implicit, implicit_set, includes, is_explicit, linked, ninfo, nocache, noclean, precious, prerequisites, pseudo, ref_count, side_effect, side_effects, sources, sources_set, state, store_info, waiting_parents, waiting_s_e, wkids	
<i>Inherited from object</i>	
__class__	

17 Module *SCons.PathList*

SCons.PathList

A module for handling lists of directory paths (the sort of things that get set as CPPPATH, LIBPATH, etc.) with as much caching of data and efficiency as we can, while still keeping the evaluation delayed so that we Do the Right Thing (almost) regardless of how the variable is specified.

17.1 Functions

node__conv(*obj*)

This is the "string conversion" routine that we have our substitutions use to return Nodes, not strings. This relies on the fact that an EntryProxy object has a get() method that returns the underlying Node that it wraps, which is a bit of architectural dependence that we might need to break or modify in the future in response to additional requirements.

PathList(*pathlist*)

Returns the cached __PathList object for the specified pathlist, creating and caching a new object as necessary.

17.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/PathList.py 74b2c53bc42290e911b334a6b44...
__doc__	Value: ""SCons.PathL...
TYPE_STRING_NO_SUBST	Value: 0
TYPE_STRING_SUBST	Value: 1
TYPE_OBJECT	Value: 2
__package__	Value: 'SCons'

18 Module SCons.SConf

SCons.SConf

Autoconf-like configuration support.

In other words, SConf allows to run tests on the build machine to detect capabilities of system and do some things based on result: generate config files, header files for C/C++, update variables in environment.

Tests on the build system can detect if compiler sees header files, if libraries are installed, if some command line options are supported etc.

18.1 Functions

SetBuildType (<i>type</i>)

SetCacheMode (<i>mode</i>)

Set the Configure cache mode. mode must be one of "auto", "force", or "cache".
--

SetProgressDisplay (<i>display</i>)
--

Set the progress display to use (called from SCons.Script)
--

NeedConfigHBuilder ()

CreateConfigHBuilder (<i>env</i>)
--

Called if necessary just before the building targets phase begins.
--

SConf (* <i>args</i> , ** <i>kw</i>)
--

CheckFunc (<i>context</i> , <i>function_name</i> , <i>header</i> =None, <i>language</i> =None)
--

CheckType (<i>context</i> , <i>type_name</i> , <i>includes</i> ='', <i>language</i> =None)
--

CheckTypeSize(*context*, *type_name*, *includes*='', *language*=None, *expect*=None)

CheckDeclaration(*context*, *declaration*, *includes*='', *language*=None)

createIncludesFromHeaders(*headers*, *leaveLast*, *include_quotes*='\"')

CheckHeader(*context*, *header*, *include_quotes*='<>', *language*=None)

A test for a C or C++ header file.

CheckCC(*context*)

CheckCXX(*context*)

CheckSHCC(*context*)

CheckSHCXX(*context*)

CheckCHheader(*context*, *header*, *include_quotes*='\"')

A test for a C header file.

CheckCXXHeader(*context*, *header*, *include_quotes*='\"')

A test for a C++ header file.

CheckLib(*context*, *library*=None, *symbol*='main', *header*=None, *language*=None, *autoadd*=1)

A test for a library. See also `CheckLibWithHeader`. Note that `library` may also be `None` to test whether the given symbol compiles without flags.

CheckLibWithHeader(*context*, *libs*, *header*, *language*, *call*=None, *autoadd*=1)

Another (more sophisticated) test for a library. Checks, if library and header is available for language (may be 'C' or 'CXX'). Call maybe be a valid expression `__with__` a trailing ';'. As in `CheckLib`, we support `library=None`, to test if the call compiles without extra link flags.


CheckProg(*context*, *prog_name*)

Simple check if a program exists in the path. Returns the path for the application, or None if not found.

18.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/SConf.py 74b2c53bc42290e911b334a6b44f18...
<code>build_type</code>	Value: None
<code>build_types</code>	Value: ['clean', 'help']
<code>dryrun</code>	Value: 0
<code>AUTO</code>	Value: 0
<code>FORCE</code>	Value: 1
<code>CACHE</code>	Value: 2
<code>cache_mode</code>	Value: 0
<code>progress_display</code>	Value: DisplayEngine()
<code>SConfFS</code>	Value: None
<code>sconf_global</code>	Value: None
<code>__package__</code>	Value: 'SCons'

18.3 Class SConfWarning



18.3.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

18.3.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i> <code>args</code> , <code>message</code>	
<i>Inherited from object</i> <code>__class__</code>	

18.4 Class SConfError



Known Subclasses: SCons.SConf.ConfigureCacheError, SCons.SConf.ConfigureDryRunError

18.4.1 Methods

__init__(*self*, *msg*)

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides:
object.**__init__** **exitit**(inherited documentation)

Inherited from exceptions.Exception

__new__()

Inherited from exceptions.BaseException

__delattr__(), **__getattr__**(), **__getitem__**(), **__getslice__**(), **__reduce__**(), **__repr__**(), **__setattr__**(), **__setstate__**(), **__str__**(), **__unicode__**()


Inherited from object

__format__(), **__hash__**(), **__reduce_ex__**(), **__sizeof__**(), **__subclasshook__**()

18.4.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
__class__	

18.5 Class `ConfigureDryRunError`



Raised when a file or directory needs to be updated during a Configure process, but the user requested a dry-run

18.5.1 Methods

`__init__(self, target)`

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` `exitit`(inherited documentation)

Inherited from `exceptions.Exception`

`__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

18.5.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

18.6 Class `ConfigureCacheError`



Raised when a use explicitly requested the cache feature, but the test is run the first time.

18.6.1 Methods

`__init__`(*self*, *target*)

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` extit(inherited documentation)

Inherited from `exceptions.Exception`

`__new__`()

Inherited from `exceptions.BaseException`

`__delattr__`(), `__getattr__`(), `__getitem__`(), `__getslice__`(), `__reduce__`(), `__repr__`(), `__setattr__`(), `__setstate__`(), `__str__`(), `__unicode__`()


Inherited from `object`

`__format__`(), `__hash__`(), `__reduce_ex__`(), `__sizeof__`(), `__subclasshook__`()

18.6.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
args, message	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

18.7 Class SConfBuildInfo



Special build info for targets of configure tests. Additional members are result (did the builder succeed last time?) and string, which contains messages of the original build phase.

18.7.1 Methods

```
__init__(self)
```

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides:
object.**__init__** exitit(inherited documentation)

```
set_build_result(self, result, string)
```

Inherited from SCons.Node.FS.FileBuildInfo(Section 15.15)

convert_from_sconsign(), convert_to_sconsign(), format(), prepare_dependencies()

Inherited from SCons.Node.BuildInfoBase(Section 13.5)

__getstate__(), **__setstate__**(), merge()

Inherited from object

__delattr__(), **__format__**(), **__getattr__**(), **__hash__**(), **__new__**(),
__reduce__(), **__reduce_ex__**(), **__repr__**(), **__setattr__**(), **__sizeof__**(),
__str__(), **__subclasshook__**()

18.7.2 Properties

Name	Description
result	
string	
<i>Inherited from SCons.Node.BuildInfoBase (Section 13.5)</i>	
bact, bactsig, bdepends, bdependSIGs, bimplicit, bimplicitsigs, bsources, bsourcesigs	
<i>Inherited from object</i>	

continued on next page

Name	Description
<code>__class__</code>	

18.7.3 Class Variables

Name	Description
<i>Inherited from SCons.Node.FS.FileBuildInfo (Section 15.15)</i>	
<code>current_version_id</code>	

18.8 Class Streamer

object —
SCons.SConf.Streamer

'Sniffer' for a file-like writable object. Similar to the unix tool tee.

18.8.1 Methods

`__init__(self, orig)`

x.`__init__`(...) initializes x; see help(type(x)) for signature Overrides:
object.`__init__` extit(inherited documentation)

`write(self, str)`

`writelines(self, lines)`

`getvalue(self)`

Return everything written to orig since the Streamer was created.

`flush(self)`


Inherited from object

`__delattr__`(), `__format__`(), `__getattr__`(), `__hash__`(), `__new__`(),
`__reduce__`(), `__reduce_ex__`(), `__repr__`(), `__setattr__`(), `__sizeof__`(),
`__str__`(), `__subclasshook__`()

18.8.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

18.9 Class SCons.SConfBuildTask



This is almost the same as SCons.Script.BuildTask. Handles SConfErrors correctly and knows about the current `cache_mode`.

18.9.1 Methods

display(*self*, *message*)

Hook to allow the calling interface to display a message.

This hook gets called as part of preparing a task for execution (that is, a Node to be built). As part of figuring out what Node should be built next, the actual target list may be altered, along with a message describing the alteration. The calling interface can subclass Task and provide a concrete implementation of this method to see those messages. Overrides: SCons.Taskmaster.Task.display exitit(inherited documentation)

display_cached_string(*self*, *bi*)

Logs the original builder messages, given the SConfBuildInfo instance bi.

failed(*self*)

Default action when a task fails: stop the build.

Note: Although this function is normally invoked on nodes in the executing state, it might also be invoked on up-to-date nodes when using Configure().
 Overrides: SCons.Taskmaster.Task.failed extit(inherited documentation)

collect_node_states(*self*)**execute(*self*)**

Called to execute the task.

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in prepare(), executed() or failed(). Overrides: SCons.Taskmaster.Task.execute extit(inherited documentation)

Inherited from SCons.Taskmaster.AlwaysTask(Section 35.5)

needs_execute()

Inherited from SCons.Taskmaster.Task(Section 35.4)

__init__(), exc_clear(), exc_info(), exception_set(), executed(), executed_with_callbacks(),
 executed_without_callbacks(), fail_continue(), fail_stop(), get_target(), make_ready(),
 make_ready_all(), make_ready_current(), postprocess(), prepare(), trace_message()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

18.9.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

18.10 Class SConfBase



This is simply a class to represent a configure context. After creating a SConf object, you can call any tests. After finished with your tests, be sure to call the `Finish()` method, which returns the modified environment. Some words about caching: In most cases, it is not necessary to cache Test results explicitly. Instead, we use the scons dependency checking mechanism. For example, if one wants to compile a test program (`SConf.TryLink`), the compiler is only called, if the program dependencies have changed. However, if the program could not be compiled in a former SConf run, we need to explicitly cache this error.

18.10.1 Methods

__init__(*self*, *env*, *custom_tests*={}, *conf_dir*='\$CONFIGUREDIR',
log_file='\$CONFIGURELOG', *config_h*=None, *_depth*=0)

Constructor. Pass additional tests in the *custom_tests*-dictionary, e.g. *custom_tests*={'CheckPrivate':MyPrivateTest}, where MyPrivateTest defines a custom test. Note also the *conf_dir* and *log_file* arguments (you may want to build tests in the VariantDir, not in the SourceDir) Overrides: `object.__init__`

Finish(*self*)

Call this method after finished with your tests: `env = sconf.Finish()`

Define(*self*, *name*, *value*=None, *comment*=None)

Define a pre processor symbol name, with the optional given value in the current config header.

If *value* is None (default), then `#define name` is written. If *value* is not none, then `#define name value` is written.

comment is a string which will be put as a C comment in the header, to explain the meaning of the value (appropriate C comments will be added automatically).

BuildNodes(*self*, *nodes*)

Tries to build the given nodes immediately. Returns 1 on success, 0 on error.

pspawn_wrapper(*self*, *sh*, *escape*, *cmd*, *args*, *env*)

Wrapper function for handling piped spawns.

This looks to the calling interface (in Action.py) like a "normal" spawn, but associates the call with the PSPAWN variable from the construction environment and with the streams to which we want the output logged. This gets slid into the construction environment as the SPAWN variable so Action.py doesn't have to know or care whether it's spawning a piped command or not.

TryBuild(*self*, *builder*, *text*=None, *extension*='')

Low level TryBuild implementation. Normally you don't need to call that - you can use TryCompile / TryLink / TryRun instead

TryAction(*self*, *action*, *text*=None, *extension*='')

Tries to execute the given action with optional source file contents <text> and optional source file extension <extension>, Returns the status (0 : failed, 1 : ok) and the contents of the output file.

TryCompile(*self*, *text*, *extension*)

Compiles the program given in text to an env.Object, using extension as file extension (e.g. '.c'). Returns 1, if compilation was successful, 0 otherwise. The target is saved in self.lastTarget (for further processing).

TryLink(*self*, *text*, *extension*)

Compiles the program given in text to an executable env.Program, using extension as file extension (e.g. '.c'). Returns 1, if compilation was successful, 0 otherwise. The target is saved in self.lastTarget (for further processing).

TryRun(*self*, *text*, *extension*)

Compiles and runs the program given in text, using extension as file extension (e.g. '.c'). Returns (1, outputStr) on success, (0, "") otherwise. The target (a file containing the program's stdout) is saved in self.lastTarget (for further processing).

AddTest(*self*, *test_name*, *test_instance*)

Adds test_class to this SConf instance. It can be called with self.test_name(...)

AddTests(*self*, *tests*)

Adds all the tests given in the tests dictionary to this SConf instance

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

18.10.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

18.11 Class *CheckContext*

object —
SCons.SConf.CheckContext

Provides a context for configure tests. Defines how a test writes to the screen and log file.

A typical test is just a callable with an instance of *CheckContext* as first argument:

```
def CheckCustom(context, ...): context.Message('Checking my weird test ...
    ') ret = myWeirdTestFunction(...) context.Result(ret)
```

Often, *myWeirdTestFunction* will be one of *context.TryCompile*/*context.TryLink*/*context.TryRun*. The results of those are cached, for they are only rebuild, if the dependencies have changed.

18.11.1 Methods

__init__(*self*, *sconf*)

Constructor. Pass the corresponding *SConf* instance. Overrides:
 object.__init__

Message(*self*, *text*)

Inform about what we are doing right now, e.g. 'Checking for SOMETHING ...'

Result(*self*, *res*)

Inform about the result of the test. If *res* is not a string, displays 'yes' or 'no' depending on whether *res* is evaluated as true or false. The result is only displayed when *self.did_show_result* is not set.

TryBuild(*self*, **args*, ***kw*)

TryAction(*self*, **args*, ***kw*)

TryCompile(*self*, **args*, ***kw*)

TryLink (<i>self</i> , * <i>args</i> , ** <i>kw</i>)

TryRun (<i>self</i> , * <i>args</i> , ** <i>kw</i>)
--

__getattr__ (<i>self</i> , <i>attr</i>)
--

BuildProg (<i>self</i> , <i>text</i> , <i>ext</i>)

CompileProg (<i>self</i> , <i>text</i> , <i>ext</i>)

CompileSharedObject (<i>self</i> , <i>text</i> , <i>ext</i>)

RunProg (<i>self</i> , <i>text</i> , <i>ext</i>)

AppendLIBS (<i>self</i> , <i>lib_name_list</i>)
--

PrependLIBS (<i>self</i> , <i>lib_name_list</i>)

SetLIBS (<i>self</i> , <i>val</i>)

Display (<i>self</i> , <i>msg</i>)

Log (<i>self</i> , <i>msg</i>)

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

18.11.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

19 Module SCons.SConsign

SCons.SConsign

Writing and reading information to the .sconsign file or files.

19.1 Functions

corrupt_dblite_warning(*filename*)

Get_DataBase(*dir*)

Reset()

Reset global state. Used by unit tests that end up using SConsign multiple times to get a clean slate for each test.

write()

File(*name*, *dbm_module*=None)

Arrange for all signatures to be stored in a global .sconsign.db* file.

19.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/SConsign.py 74b2c53bc42290e911b334a6b44...
sig_files	Value: []
DataBase	Value: {}
DB_Name	Value: '.sconsign'
DB_sync_list	Value: []
__package__	Value: 'SCons'

19.3 Class SConsignEntry



Wrapper class for the generic entry in a .sconsign file. The Node subclass populates it with attributes as it pleases.

XXX As coded below, we do expect a 'binfo' attribute to be added, but we'll probably generalize this in the next refactorings.

19.3.1 Methods

```
__init__(self)
```

x.__init__(...) initializes x; see help(type(x)) for signature Overrides:
object.__init__ extit(inherited documentation)

```
convert_to_sconsign(self)
```

```
convert_from_sconsign(self, dir, name)
```

```
__getstate__(self)
```

```
__setstate__(self, state)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

19.3.2 Properties

Name	Description
binfo	
ninfo	
<i>Inherited from object</i>	
__class__	

19.3.3 Class Variables

Name	Description
current_version_id	Value: 2

19.4 Class Base



Known Subclasses: SCons.SConsign.DB, SCons.SConsign.Dir

This is the controlling class for the signatures for the collection of entries associated with a specific directory. The actual directory association will be maintained by a subclass that is specific to the underlying storage method. This class provides a common set of methods for fetching and storing the individual bits of information that make up signature entry.

19.4.1 Methods

__init__(*self*)

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides:
object.**__init__** extit(inherited documentation)

get_entry(*self*, *filename*)

Fetch the specified entry attribute.

set_entry(*self*, *filename*, *obj*)

Set the entry.

do_not_set_entry(*self*, *filename*, *obj*)

store_info(*self*, *filename*, *node*)

do_not_store_info(*self*, *filename*, *node*)

merge(*self*)

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

19.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

19.5 Class DB

A Base subclass that reads and writes signature information from a global `.sconsign.db*` file--the actual file suffix is determined by the database module.

19.5.1 Methods

<code>__init__(self, dir)</code>
x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature Overrides: object. <code>__init__</code> extit(inherited documentation)
<code>write(self, sync=1)</code>

Inherited from SCons.SConsign.Base(Section 19.4)

```
do_not_set_entry(), do_not_store_info(), get_entry(), merge(), set_entry(), store_info()
```


Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

19.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

19.6 Class Dir



Known Subclasses: SCons.SConsign.DirFile

19.6.1 Methods

__init__ (<i>self</i> , <i>fp</i> =None, <i>dir</i> =None)
fp - file pointer to read entries from Overrides: object.__init__

Inherited from SCons.SConsign.Base(Section 19.4)

do_not_set_entry(), do_not_store_info(), get_entry(), merge(), set_entry(), store_info()


Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

19.6.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

19.7 Class *DirFile*



Encapsulates reading and writing a per-directory `.sconsign` file.

19.7.1 Methods

<code>__init__</code> (<i>self</i> , <i>dir</i>)
<div>dir - the directory for the file Overrides: <code>object.__init__</code></div>

<code>write</code> (<i>self</i> , <i>sync</i> =1)
<div>Write the <code>.sconsign</code> file to disk.</div> <div>Try to write to a temporary file first, and rename it if we succeed. If we can't write to the temporary file, it's probably because the directory isn't writable (and if so, how did we build anything in this directory, anyway?), so try to write directly to the <code>.sconsign</code> file as a backup. If we can't rename, try to copy the temporary contents back to the <code>.sconsign</code> file. Either way, always try to remove the temporary file at the end.</div>

Inherited from `SCons.SConsign.Base`(Section 19.4)

`do_not_set_entry()`, `do_not_store_info()`, `get_entry()`, `merge()`, `set_entry()`, `store_info()`


Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

19.7.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

19.8 Class DB



A Base subclass that reads and writes signature information from a global `.sconsign.db*` file--the actual file suffix is determined by the database module.

19.8.1 Methods

__init__ (<i>self</i> , <i>dir</i>)
x. __init__ (...) initializes x; see help(type(x)) for signature Overrides: object. __init__ extit(inherited documentation)
write (<i>self</i> , <i>sync</i> =1)

Inherited from SCons.SConsign.Base(Section 19.4)

`do_not_set_entry()`, `do_not_store_info()`, `get_entry()`, `merge()`, `set_entry()`, `store_info()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

19.8.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

20 Package SCons.Scanner

SCons.Scanner

The Scanner package for the SCons software construction utility.

20.1 Modules

- **C:** SCons.Scanner.C
(Section 21, p. 232)
- **D:** SCons.Scanner.D
(Section 22, p. 235)
- **Dir** (Section 23, p. 239)
- **Fortran:** SCons.Scanner.Fortran
(Section 24, p. 241)
- **IDL:** SCons.Scanner.IDL
(Section 25, p. 246)
- **LaTeX:** SCons.Scanner.LaTeX
(Section 26, p. 247)
- **Prog** (Section 27, p. 254)
- **RC:** SCons.Scanner.RC
(Section 28, p. 255)
- **SWIG:** SCons.Scanner.SWIG
(Section 29, p. 256)

20.2 Functions

Scanner(*function*, **args*, ***kw*)

Public interface factory function for creating different types of Scanners based on the different types of "functions" that may be supplied.

TODO: Deprecate this some day. We've moved the functionality inside the Base class and really don't need this factory function any more. It was, however, used by some of our Tool modules, so the call probably ended up in various people's custom modules patterned on SCons code.

20.3 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Scanner/__init__.py 74b2c53bc42290e911b...
<code>__package__</code>	Value: 'SCons.Scanner'

20.4 Class FindPathDirs



A class to bind a specific E{*}PATH variable name to a function that will return all of the E{*}path directories.

20.4.1 Methods

`__init__(self, variable)`

x.`__init__`(...) initializes x; see help(type(x)) for signature Overrides:
object.`__init__` extit(inherited documentation)

`__call__(self, env, dir=None, target=None, source=None, argument=None)`

Inherited from object

`__delattr__`(), `__format__`(), `__getattr__`(), `__hash__`(), `__new__`(),
`__reduce__`(), `__reduce_ex__`(), `__repr__`(), `__setattr__`(), `__sizeof__`(),
`__str__`(), `__subclasshook__`()

20.4.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

20.5 Class Base



Known Subclasses: SCons.Scanner.Current, SCons.Scanner.Selector, SCons.Scanner.LaTeX.LaTeX

The base class for dependency scanners. This implements straightforward, single-pass scanning of a single file.

20.5.1 Methods

__call__(*self*, *node*, *env*, *path*=())

This method scans a single object. 'node' is the node that will be passed to the scanner function, and 'env' is the environment that will be passed to the scanner function. A list of direct dependency nodes for the specified node will be returned.

__eq__(*self*, *other*)

__hash__(*self*)

hash(x) Overrides: object.__hash__ extit(inherited documentation)

```
init__(self, function, name='NONE', argument=<class
'SCons.Scanner._Null'>, keys=<class 'SCons.Scanner._Null'>,
path_function=None, node_class=<class 'SCons.Node.FS.Base'>,
node_factory=None, scan_check=None, recursive=None)
```

Construct a new scanner object given a scanner function.

'function' - a scanner function taking two or three arguments and returning a list of strings.

'name' - a name for identifying this scanner object.

'argument' - an optional argument that, if specified, will be passed to both the scanner function and the path_function.

'keys' - an optional list argument that can be used to determine which scanner should be used for a given Node. In the case of File nodes, for example, the 'keys' would be file suffixes.

'path_function' - a function that takes four or five arguments (a construction environment, Node for the directory containing the SConscript file that defined the primary target, list of target nodes, list of source nodes, and optional argument for this instance) and returns a tuple of the directories that can be searched for implicit dependency files. May also return a callable() which is called with no args and returns the tuple (supporting Bindable class).

'node_class' - the class of Nodes which this scan will return. If node_class is None, then this scanner will not enforce any Node conversion and will return the raw results from the underlying scanner function.

'node_factory' - the factory function to be called to translate the raw results returned by the scanner function into the expected node_class objects.

'scan_check' - a function to be called to first check whether this node really needs to be scanned.

'recursive' - specifies that this scanner should be invoked recursively on all of the implicit dependencies it returns (the canonical example being #include lines in C source files). May be a callable, which will be called to filter the list of nodes found to select a subset for recursive scanning (the canonical example being only recursively scanning subdirectories within a directory).

The scanner function's first argument will be a Node that should be scanned for dependencies, the second argument will be an Environment object, the third argument will be the tuple of paths returned by the path_function, and the fourth argument will be the value passed into 'argument', and the returned list should contain the Nodes for all the direct dependencies of the file.

Examples:

```
s = Scanner(my_scanner_function)
```

```
s = Scanner(function = my_scanner_function)
```

```
__str__(self)
```

str(x) Overrides: object.__str__ extit(inherited documentation)

```
add_scanner(self, skey, scanner)
```

```
add_skey(self, skey)
```

Add a key to the list of skeys

```
get_skeys(self, env=None)
```

```
path(self, env, dir=None, target=None, source=None)
```

```
select(self, node)
```


Inherited from object

```
__delattr__(), __format__(), __getattr__(), __new__(), __reduce__(),
__reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __subclasshook__()
```

20.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

20.6 Class Selector



A class for selecting a more specific scanner based on the scanner_key() (suffix) for a specific Node.

TODO: This functionality has been moved into the inner workings of the Base class, and this class will be deprecated at some point. (It was never exposed directly as part of the public interface, although it is used by the Scanner() factory function that was used by various Tool

modules and therefore was likely a template for custom modules that may be out there.)

20.6.1 Methods

`__init__(self, dict, *args, **kw)`

Construct a new scanner object given a scanner function.

'function' - a scanner function taking two or three arguments and returning a list of strings.

'name' - a name for identifying this scanner object.

'argument' - an optional argument that, if specified, will be passed to both the scanner function and the `path_function`.

'skeys' - an optional list argument that can be used to determine which scanner should be used for a given Node. In the case of File nodes, for example, the 'skeys' would be file suffixes.

'path_function' - a function that takes four or five arguments (a construction environment, Node for the directory containing the SConscript file that defined the primary target, list of target nodes, list of source nodes, and optional argument for this instance) and returns a tuple of the directories that can be searched for implicit dependency files. May also return a callable() which is called with no args and returns the tuple (supporting Bindable class).

'node_class' - the class of Nodes which this scan will return. If `node_class` is None, then this scanner will not enforce any Node conversion and will return the raw results from the underlying scanner function.

'node_factory' - the factory function to be called to translate the raw results returned by the scanner function into the expected `node_class` objects.

'scan_check' - a function to be called to first check whether this node really needs to be scanned.

'recursive' - specifies that this scanner should be invoked recursively on all of the implicit dependencies it returns (the canonical example being `#include` lines in C source files). May be a callable, which will be called to filter the list of nodes found to select a subset for recursive scanning (the canonical example being only recursively scanning subdirectories within a directory).

The scanner function's first argument will be a Node that should be scanned for dependencies, the second argument will be an Environment object, the third argument will be the tuple of paths returned by the `path_function`, and the fourth argument will be the value passed into 'argument', and the returned list should contain the Nodes for all the direct dependencies of the file.

Examples:

```
s = Scanner(my_scanner_function)    238
```

```
s = Scanner(function = my_scanner_function)
```

```
s = Scanner(function = my_scanner_function, argument = 'foo') Overrides:
```

```
__call__(self, node, env, path=())
```

This method scans a single object. 'node' is the node that will be passed to the scanner function, and 'env' is the environment that will be passed to the scanner function. A list of direct dependency nodes for the specified node will be returned. Overrides: SCons.Scanner.Base.__call__ extit(inherited documentation)

```
select(self, node)
```

Overrides: SCons.Scanner.Base.select

```
add_scanner(self, skey, scanner)
```

Overrides: SCons.Scanner.Base.add_scanner

Inherited from SCons.Scanner.Base(Section 20.5)

```
__eq__(), __hash__(), __str__(), add_skey(), get_skeys(), path()
```


Inherited from object

```
__delattr__(), __format__(), __getattr__(), __new__(), __reduce__(),
__reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __subclasshook__()
```

20.6.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

20.7 Class Current



Known Subclasses: SCons.Scanner.Classic

A class for scanning files that are source files (have no builder) or are derived files and are current (which implies that they exist, either locally or in a repository).

20.7.1 Methods

`__init__(self, *args, **kw)`

Construct a new scanner object given a scanner function.

'function' - a scanner function taking two or three arguments and returning a list of strings.

'name' - a name for identifying this scanner object.

'argument' - an optional argument that, if specified, will be passed to both the scanner function and the `path_function`.

'skeys' - an optional list argument that can be used to determine which scanner should be used for a given Node. In the case of File nodes, for example, the 'skeys' would be file suffixes.

'path_function' - a function that takes four or five arguments (a construction environment, Node for the directory containing the SConscript file that defined the primary target, list of target nodes, list of source nodes, and optional argument for this instance) and returns a tuple of the directories that can be searched for implicit dependency files. May also return a callable() which is called with no args and returns the tuple (supporting Bindable class).

'node_class' - the class of Nodes which this scan will return. If `node_class` is None, then this scanner will not enforce any Node conversion and will return the raw results from the underlying scanner function.

'node_factory' - the factory function to be called to translate the raw results returned by the scanner function into the expected `node_class` objects.

'scan_check' - a function to be called to first check whether this node really needs to be scanned.

'recursive' - specifies that this scanner should be invoked recursively on all of the implicit dependencies it returns (the canonical example being `#include` lines in C source files). May be a callable, which will be called to filter the list of nodes found to select a subset for recursive scanning (the canonical example being only recursively scanning subdirectories within a directory).

The scanner function's first argument will be a Node that should be scanned for dependencies, the second argument will be an Environment object, the third argument will be the tuple of paths returned by the `path_function`, and the fourth argument will be the value passed into 'argument', and the returned list should contain the Nodes for all the direct dependencies of the file.

Examples:

```
s = Scanner(my_scanner_function) 241
```

```
s = Scanner(function = my_scanner_function)
```

```
s = Scanner(function = my_scanner_function, argument = 'foo') Overrides:
```

Inherited from SCons.Scanner.Base(Section 20.5)


`__call__()`, `__eq__()`, `__hash__()`, `__str__()`, `add_scanner()`, `add_skey()`,
`get_skeys()`, `path()`, `select()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__new__()`, `__reduce__()`,
`__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__subclasshook__()`

20.7.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

20.8 Class Classic

Known Subclasses: `SCons.Scanner.ClassicCPP`, `SCons.Scanner.D.D`, `SCons.Scanner.Fortran.F90Scanner`

A Scanner subclass to contain the common logic for classic CPP-style include scanning, but which can be customized to use different regular expressions to find the includes.

Note that in order for this to work "out of the box" (without overriding the `find_include()` and `sort_key()` methods), the regular expression passed to the constructor must return the name of the include file in group 0.

20.8.1 Methods

__init__(*self, name, suffixes, path_variable, regex, *args, **kw*)

Construct a new scanner object given a scanner function.

'function' - a scanner function taking two or three arguments and returning a list of strings.

'name' - a name for identifying this scanner object.

'argument' - an optional argument that, if specified, will be passed to both the scanner function and the `path_function`.

'skeys' - an optional list argument that can be used to determine which scanner should be used for a given Node. In the case of File nodes, for example, the 'skeys' would be file suffixes.

'path_function' - a function that takes four or five arguments (a construction environment, Node for the directory containing the SConscript file that defined the primary target, list of target nodes, list of source nodes, and optional argument for this instance) and returns a tuple of the directories that can be searched for implicit dependency files. May also return a callable() which is called with no args and returns the tuple (supporting Bindable class).

'node_class' - the class of Nodes which this scan will return. If `node_class` is None, then this scanner will not enforce any Node conversion and will return the raw results from the underlying scanner function.

'node_factory' - the factory function to be called to translate the raw results returned by the scanner function into the expected `node_class` objects.

'scan_check' - a function to be called to first check whether this node really needs to be scanned.

'recursive' - specifies that this scanner should be invoked recursively on all of the implicit dependencies it returns (the canonical example being `#include` lines in C source files). May be a callable, which will be called to filter the list of nodes found to select a subset for recursive scanning (the canonical example being only recursively scanning subdirectories within a directory).

The scanner function's first argument will be a Node that should be scanned for dependencies, the second argument will be an Environment object, the third argument will be the tuple of paths returned by the `path_function`, and the fourth argument will be the value passed into 'argument', and the returned list should contain the Nodes for all the direct dependencies of the file.

Examples:

```
s = Scanner(my_scanner_function)    244
```

```
s = Scanner(function = my_scanner_function)
```

```
s = Scanner(function = my_scanner_function, argument = 'foo') Overrides:
```

```
find_include(self, include, source_dir, path)
```

```
find_include_names(self, node)
```

```
scan(self, node, path=())
```

```
sort_key(self, include)
```

*Inherited from **SCons.Scanner.Base**(Section 20.5)*

```
__call__(), __eq__(), __hash__(), __str__(), add_scanner(), add_skey(),
get_skeys(), path(), select()
```


*Inherited from **object***

```
__delattr__(), __format__(), __getattr__(), __new__(), __reduce__(),
__reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __subclasshook__()
```

20.8.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

20.9 Class **ClassicCPP**



A Classic Scanner subclass which takes into account the type of bracketing used to include the file, and uses classic CPP rules for searching for the files based on the bracketing.

Note that in order for this to work, the regular expression passed to the constructor must return the leading bracket in group 0, and the contained filename in group 1.

20.9.1 Methods

find_include (<i>self</i> , <i>include</i> , <i>source_dir</i> , <i>path</i>)
--

Overrides: <i>SCons.Scanner.Classic.find_include</i>
--

sort_key (<i>self</i> , <i>include</i>)
--

Overrides: <i>SCons.Scanner.Classic.sort_key</i>
--

Inherited from SCons.Scanner.Classic(Section 20.8)

<code>__init__()</code> , <code>find_include_names()</code> , <code>scan()</code>

Inherited from SCons.Scanner.Base(Section 20.5)

<code>__call__()</code> , <code>__eq__()</code> , <code>__hash__()</code> , <code>__str__()</code> , <code>add_scanner()</code> , <code>add_skey()</code> , <code>get_skeys()</code> , <code>path()</code> , <code>select()</code>

Inherited from object

<code>__delattr__()</code> , <code>__format__()</code> , <code>__getattr__()</code> , <code>__new__()</code> , <code>__reduce__()</code> , <code>__reduce_ex__()</code> , <code>__repr__()</code> , <code>__setattr__()</code> , <code>__sizeof__()</code> , <code>__subclasshook__()</code>

20.9.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

21 Module **SCons.Scanner.C**

SCons.Scanner.C

This module implements the dependency scanner for C/C++ code.

21.1 Functions

dictify__CPPDEFINES (<i>env</i>)

CScanner ()

Return a prototype Scanner instance for scanning source files that use the C pre-processor
--

21.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Scanner/C.py 74b2c53bc42290e911b334a6b4...
__package__	Value: 'SCons.Scanner'

21.3 Class **SConsCPPScanner**

object └─

SCons.cpp.PreProcessor └─

SCons.Scanner.C.SConsCPPScanner

SCons-specific subclass of the cpp.py module's processing.

We subclass this so that: 1) we can deal with files represented by Nodes, not strings; 2) we can keep track of the files that are missing.

21.3.1 Methods

__init__(*self*, **args*, ***kw*)

x.__init__(...) initializes x; see help(type(x)) for signature Overrides: object.__init__ exitit(inherited documentation)

initialize_result(*self*, *fname*)

Overrides: SCons.cpp.PreProcessor.initialize_result

finalize_result(*self*, *fname*)

Overrides: SCons.cpp.PreProcessor.finalize_result

find_include_file(*self*, *t*)

Finds the #include file for a given preprocessor tuple. Overrides: SCons.cpp.PreProcessor.find_include_file exitit(inherited documentation)

read_file(*self*, *file*)

Overrides: SCons.cpp.PreProcessor.read_file

Inherited from SCons.cpp.PreProcessor(Section 44.4)

__call__(), all_include(), do_define(), do_elif(), do_else(), do_endif(), do_if(), do_ifdef(), do_ifndef(), do_import(), do_include(), do_include_next(), do_nothing(), do_undef(), eval_expression(), process_contents(), resolve_include(), restore(), save(), scons_current_file(), start_handling_includes(), stop_handling_includes(), tupleize()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

21.3.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

21.4 Class SConsCPPScannerWrapper

object —
SCons.Scanner.C.SConsCPPScannerWrapper

The SCons wrapper around a cpp.py scanner.

This is the actual glue between the calling conventions of generic SCons scanners, and the (subclass of) cpp.py class that knows how to look for #include lines with reasonably real C-preprocessor-like evaluation of #if/#ifdef/#else/#elif lines.

21.4.1 Methods

__init__ (<i>self</i> , <i>name</i> , <i>variable</i>)

x. __init__ (...) initializes x; see help(type(x)) for signature Overrides: object. __init__ extit(inherited documentation)
--

__call__ (<i>self</i> , <i>node</i> , <i>env</i> , <i>path</i> =())

recurse__nodes (<i>self</i> , <i>nodes</i>)
--

select (<i>self</i> , <i>node</i>)

Inherited from object

__delattr__ (), __format__ (), __getattr__ (), __hash__ (), __new__ (), __reduce__ (), __reduce_ex__ (), __repr__ (), __setattr__ (), __sizeof__ (), __str__ (), __subclasshook__ ()
--

21.4.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

22 Module SCons.Scanner.D

SCons.Scanner.D

Scanner for the Digital Mars "D" programming language.

Coded by Andy Friesen 17 Nov 2003

22.1 Functions


DScanner()

Return a prototype Scanner instance for scanning D source files

22.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Scanner/D.py 74b2c53bc42290e911b334a6b4...
__package__	Value: 'SCons.Scanner'

22.3 Class D



22.3.1 Methods

`__init__(self)`

Construct a new scanner object given a scanner function.

'function' - a scanner function taking two or three arguments and returning a list of strings.

'name' - a name for identifying this scanner object.

'argument' - an optional argument that, if specified, will be passed to both the scanner function and the `path_function`.

'skeys' - an optional list argument that can be used to determine which scanner should be used for a given Node. In the case of File nodes, for example, the 'skeys' would be file suffixes.

'path_function' - a function that takes four or five arguments (a construction environment, Node for the directory containing the SConscript file that defined the primary target, list of target nodes, list of source nodes, and optional argument for this instance) and returns a tuple of the directories that can be searched for implicit dependency files. May also return a callable() which is called with no args and returns the tuple (supporting Bindable class).

'node_class' - the class of Nodes which this scan will return. If `node_class` is None, then this scanner will not enforce any Node conversion and will return the raw results from the underlying scanner function.

'node_factory' - the factory function to be called to translate the raw results returned by the scanner function into the expected `node_class` objects.

'scan_check' - a function to be called to first check whether this node really needs to be scanned.

'recursive' - specifies that this scanner should be invoked recursively on all of the implicit dependencies it returns (the canonical example being `#include` lines in C source files). May be a callable, which will be called to filter the list of nodes found to select a subset for recursive scanning (the canonical example being only recursively scanning subdirectories within a directory).

The scanner function's first argument will be a Node that should be scanned for dependencies, the second argument will be an Environment object, the third argument will be the tuple of paths returned by the `path_function`, and the fourth argument will be the value passed into 'argument', and the returned list should contain the Nodes for all the direct dependencies of the file.

Examples:

```
s = Scanner(my_scanner_function)    252
```

```
s = Scanner(function = my_scanner_function)
```

```
s = Scanner(function = my_scanner_function, argument = 'foo') Overrides:
```

find_include (<i>self</i> , <i>include</i> , <i>source_dir</i> , <i>path</i>)
--

Overrides: SCons.Scanner.Classic.find_include

find_include_names (<i>self</i> , <i>node</i>)

Overrides: SCons.Scanner.Classic.find_include_names

Inherited from SCons.Scanner.Classic(Section 20.8)

scan(), sort_key()

Inherited from SCons.Scanner.Base(Section 20.5)

__call__(), __eq__(), __hash__(), __str__(), add_scanner(), add_skey(),
get_skeys(), path(), select()

Inherited from object

__delattr__(), __format__(), __getattr__(), __new__(), __reduce__(),
__reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __subclasshook__()

22.3.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

23 Module *SCons.Scanner.Dir*

23.1 Functions

only_dirs(*nodes*)

DirScanner(***kw*)

Return a prototype Scanner instance for scanning directories for on-disk files

DirEntryScanner(***kw*)

Return a prototype Scanner instance for "scanning" directory Nodes for their in-memory entries

do_not_scan(*k*)

scan_on_disk(*node*, *env*, *path*=())

Scans a directory for on-disk files and directories therein.

Looking up the entries will add these to the in-memory Node tree representation of the file system, so all we have to do is just that and then call the in-memory scanning function.

scan_in_memory(*node*, *env*, *path*=())

"Scans" a Node.FS.Dir for its in-memory entries.

23.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Scanner/Dir.py 74b2c53bc42290e911b334a6...
<code>skip_entry</code>	Value: {'.': 1, '..': 1, '.sconsign': 1, '.sconsign.bak': 1, '.s...

continued on next page

Name	Description
skip_entry_list	Value: ['.', '..', '.sconsign', .sconsign.dblite', '.sconsign.d...
__package__	Value: 'SCons.Scanner'
skip	Value: '.sconsign.db'

24 Module SCons.Scanner.Fortran

SCons.Scanner.Fortran

This module implements the dependency scanner for Fortran code.

24.1 Functions


FortranScan (<i>path_variable</i> ='FORTRANPATH')

Return a prototype Scanner instance for scanning source files for Fortran USE & INCLUDE statements
--

24.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Scanner/Fortran.py 74b2c53bc42290e911b3...'
__package__	Value: 'SCons.Scanner'

24.3 Class F90Scanner



A Classic Scanner subclass for Fortran source files which takes into account both USE and INCLUDE statements. This scanner will work for both F77 and F90 (and beyond) compilers.

Currently, this scanner assumes that the include files do not contain USE statements. To enable the ability to deal with USE statements in include files, add logic right after the module names are found to loop over each include file, search for and locate each USE statement, and append each module name to the list of dependencies. Caching the search

results in a common dictionary somewhere so that the same include file is not searched multiple times would be a smart thing to do.

24.3.1 Methods

__init__(*self, name, suffixes, path_variable, use_regex, incl_regex, def_regex, *args, **kw*)

Construct a new scanner object given a scanner function.

'function' - a scanner function taking two or three arguments and returning a list of strings.

'name' - a name for identifying this scanner object.

'argument' - an optional argument that, if specified, will be passed to both the scanner function and the path_function.

'keys' - an optional list argument that can be used to determine which scanner should be used for a given Node. In the case of File nodes, for example, the 'keys' would be file suffixes.

'path_function' - a function that takes four or five arguments (a construction environment, Node for the directory containing the SConscript file that defined the primary target, list of target nodes, list of source nodes, and optional argument for this instance) and returns a tuple of the directories that can be searched for implicit dependency files. May also return a callable() which is called with no args and returns the tuple (supporting Bindable class).

'node_class' - the class of Nodes which this scan will return. If node_class is None, then this scanner will not enforce any Node conversion and will return the raw results from the underlying scanner function.

'node_factory' - the factory function to be called to translate the raw results returned by the scanner function into the expected node_class objects.

'scan_check' - a function to be called to first check whether this node really needs to be scanned.

'recursive' - specifies that this scanner should be invoked recursively on all of the implicit dependencies it returns (the canonical example being #include lines in C source files). May be a callable, which will be called to filter the list of nodes found to select a subset for recursive scanning (the canonical example being only recursively scanning subdirectories within a directory).

The scanner function's first argument will be a Node that should be scanned for dependencies, the second argument will be an Environment object, the third argument will be the tuple of paths returned by the path_function, and the fourth argument will be the value passed into 'argument', and the returned list should contain the Nodes for all the direct dependencies of the file.

Examples:

259

```
s = Scanner(my_scanner_function)
```

```
s = Scanner(function = my_scanner_function)
```

```
scan(self, node, env, path=())
```

Overrides: SCons.Scanner.Classic.scan

Inherited from SCons.Scanner.Classic(Section 20.8)

find_include(), find_include_names(), sort_key()

Inherited from SCons.Scanner.Base(Section 20.5)

__call__(), __eq__(), __hash__(), __str__(), add_scanner(), add_skey(),
get_skeys(), path(), select()

Inherited from object

__delattr__(), __format__(), __getattr__(), __new__(), __reduce__(),
__reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __subclasshook__()

24.3.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

25 Module SCons.Scanner.IDL

SCons.Scanner.IDL

This module implements the dependency scanner for IDL (Interface Definition Language) files.

25.1 Functions

IDLScan()
Return a prototype Scanner instance for scanning IDL source files

25.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Scanner/IDL.py 74b2c53bc42290e911b334a6...'
__package__	Value: 'SCons.Scanner'

26 Module SCons.Scanner.LaTeX

SCons.Scanner.LaTeX

This module implements the dependency scanner for LaTeX code.

26.1 Functions

modify__env__var (<i>env</i> , <i>var</i> , <i>abspath</i>)
--

LaTeXScanner ()

Return a prototype Scanner instance for scanning LaTeX source files when built with latex.
--

PDFLaTeXScanner ()

Return a prototype Scanner instance for scanning LaTeX source files when built with pdflatex.

26.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Scanner/LaTeX.py 74b2c53bc42290e911b334...'
TexGraphics	Value: ['.eps', '.ps']
LatexGraphics	Value: ['.png', '.jpg', '.gif', '.tif']
__package__	Value: 'SCons.Scanner'

26.3 Class FindENVPathDirs

object — **SCons.Scanner.LaTeX.FindENVPathDirs**

A class to bind a specific E{*}PATH variable name to a function that will return all of the E{*}path directories.

26.3.1 Methods

`__init__(self, variable)`

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` `exitit`(inherited documentation)

`__call__(self, env, dir=None, target=None, source=None, argument=None)`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

26.3.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

26.4 Class LaTeX



Class for scanning LaTeX files for included files.

Unlike most scanners, which use regular expressions that just return the included file name, this returns a tuple consisting of the keyword for the inclusion ("include", "includegraphics", "input", or "bibliography"), and then the file name itself. Based on a quick look at LaTeX documentation, it seems that we should append .tex suffix for the "include" keywords, append .tex if there is no extension for the "input" keyword, and need to add .bib for the "bibliography" keyword that does not accept extensions by itself.

Finally, if there is no extension for an "includegraphics" keyword latex will append .ps or .eps to find the file, while pdftex may use .pdf, .jpg, .tif, .mps, or .png.

The actual subset and search order may be altered by `DeclareGraphicsExtensions` command. This complication is ignored. The default order corresponds to experimentation with `teTeX`:

```
$ latex --version
pdfTeX 3.141592-1.21a-2.2 (Web2C 7.5.4)
kpathsea version 3.5.4
```

The order is: ['.eps', '.ps'] for latex ['.png', '.pdf', '.jpg', '.tif'].

Another difference is that the search path is determined by the type of the file being searched: env['TEXINPUTS'] for "input" and "include" keywords env['TEXINPUTS'] for "include-graphics" keyword env['TEXINPUTS'] for "lstinutlisting" keyword env['BIBINPUTS'] for "bibliography" keyword env['BSTINPUTS'] for "bibliographystyle" keyword env['INDEXSTYLE'] for "makeindex" keyword, no scanning support needed just allows user to set it if needed.

FIXME: also look for the class or style in document[class|style]{ } FIXME: also look for the argument of bibliographystyle{ }

26.4.1 Methods

__init__(*self*, *name*, *suffixes*, *graphics_extensions*, **args*, ***kw*)

Construct a new scanner object given a scanner function.

'function' - a scanner function taking two or three arguments and returning a list of strings.

'name' - a name for identifying this scanner object.

'argument' - an optional argument that, if specified, will be passed to both the scanner function and the `path_function`.

'skeys' - an optional list argument that can be used to determine which scanner should be used for a given Node. In the case of File nodes, for example, the 'skeys' would be file suffixes.

'path_function' - a function that takes four or five arguments (a construction environment, Node for the directory containing the SConscript file that defined the primary target, list of target nodes, list of source nodes, and optional argument for this instance) and returns a tuple of the directories that can be searched for implicit dependency files. May also return a callable() which is called with no args and returns the tuple (supporting Bindable class).

'node_class' - the class of Nodes which this scan will return. If `node_class` is None, then this scanner will not enforce any Node conversion and will return the raw results from the underlying scanner function.

'node_factory' - the factory function to be called to translate the raw results returned by the scanner function into the expected `node_class` objects.

'scan_check' - a function to be called to first check whether this node really needs to be scanned.

'recursive' - specifies that this scanner should be invoked recursively on all of the implicit dependencies it returns (the canonical example being `#include` lines in C source files). May be a callable, which will be called to filter the list of nodes found to select a subset for recursive scanning (the canonical example being only recursively scanning subdirectories within a directory).

The scanner function's first argument will be a Node that should be scanned for dependencies, the second argument will be an Environment object, the third argument will be the tuple of paths returned by the `path_function`, and the fourth argument will be the value passed into 'argument', and the returned list should contain the Nodes for all the direct dependencies of the file.

Examples:

```
s = Scanner(my_scanner_function) 266
```

```
s = Scanner(function = my_scanner_function)
```

```
s = Scanner(function = my_scanner_function, argument = 'foo') Overrides:
```

<code>sort_key(self, include)</code>

<code>find_include(self, include, source_dir, path)</code>
--

<code>canonical_text(self, text)</code>

Standardize an input TeX-file contents.

Currently:

- removes comments, unwrapping comment-wrapped lines.

<code>scan(self, node, subdir='.')</code>

<code>scan_recurse(self, node, path=())</code>
--

do a recursive scan of the top level target file This lets us search for included files based on the directory of the main file just as latex does

Inherited from SCons.Scanner.Base(Section 20.5)

`__call__()`, `__eq__()`, `__hash__()`, `__str__()`, `add_scanner()`, `add_skey()`, `get_skeys()`, `path()`, `select()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__subclasshook__()`

26.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

26.4.3 Class Variables

Name	Description
<code>keyword_paths</code>	Value: {'addbibresource': 'BIBINPUTS', 'addglobalbib': 'BIBINPUT...}

continued on next page

Name	Description
env_variables	Value: ['INDEXSTYLE', 'BIBINPUTS', 'TEXINPUTS', 'BSTINPUTS']
two_arg_commands	Value: ['import', 'subimport', 'includefrom', 'subincludefrom', ...]

27 Module *SCons.Scanner.Prog*

27.1 Functions

ProgramScanner(***kw*)

Return a prototype Scanner instance for scanning executable files for static-lib dependencies

scan(*node*, *env*, *libpath*=())

This scanner scans program files for static-library dependencies. It will search the LIBPATH environment variable for libraries specified in the LIBS variable, returning any files it finds as dependencies.

27.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Scanner/Prog.py 74b2c53bc42290e911b334a...
print_find_libs	Value: None
__package__	Value: 'SCons.Scanner'

28 Module *SCons.Scanner.RC*

SCons.Scanner.RC

This module implements the dependency scanner for RC (Interface Definition Language) files.

28.1 Functions

no_tlb (<i>nodes</i>)
Filter out .tlb files as they are binary and shouldn't be scanned

RCScan ()
Return a prototype Scanner instance for scanning RC source files

28.2 Variables

Name	Description
<code>__revision__</code>	Value: <code>'src/engine/SCons/Scanner/RC.py 74b2c53bc42290e911b334a6b...</code>
<code>__package__</code>	Value: <code>'SCons.Scanner'</code>

29 Module `SCons.Scanner.SWIG`

`SCons.Scanner.SWIG`

This module implements the dependency scanner for SWIG code.

29.1 Functions

SWIGScanner()

29.2 Variables

Name	Description
<code>__revision__</code>	Value: <code>'src/engine/SCons/Scanner/SWIG.py 74b2c53bc42290e911b334a...</code>
<code>SWIGSuffices</code>	Value: <code>['.i']</code>
<code>__package__</code>	Value: <code>'SCons.Scanner'</code>

30 Package SCons.Script

SCons.Script

This file implements the `main()` function used by the `scons` script.

Architecturally, this *is* the `scons` script, and will likely only be called from the external "scons" wrapper. Consequently, anything here should not be, or be considered, part of the build engine. If it's something that we expect other software to want to use, it should go in some other module. If it's specific to the "scons" script invocation, it goes here.

30.1 Modules

- **Interactive:** SCons interactive mode
(Section 31, p. 266)
- **Main:** SCons.Script
(Section 32, p. 269)
- **SConscript':** SCons.Script.SConscript
(Section 33, p. 283)

30.2 Functions

HelpFunction (<i>text</i> , <i>append</i> =False)

Variables (<i>files</i> =[], <i>args</i> ={})

Options (<i>files</i> =[], <i>args</i> ={})

30.3 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Script/__init__.py 74b2c53bc42290e911b3...
<code>start_time</code>	Value: 1510694483.18
<code>call_stack</code>	Value: []
<code>PathVariable</code>	Value: SCons.Variables.PathVariable
<code>PathOption</code>	Value: SCons.Options.PathOption
<code>Chmod</code>	Value: SCons.Defaults.Chmod
<code>Copy</code>	Value: SCons.Defaults.Copy
<code>Delete</code>	Value: SCons.Defaults.Delete

continued on next page

Name	Description
Mkdir	Value: SCons.Defaults.Mkdir
Move	Value: SCons.Defaults.Move
Touch	Value: SCons.Defaults.Touch
CScanner	Value: SCons.Defaults.CScan
DScanner	Value: SCons.Tool.DScanner
DirScanner	Value: SCons.Defaults.DirScanner
ProgramScanner	Value: SCons.Tool.ProgramScanner
SourceFileScanner	Value: SCons.Tool.SourceFileScanner
CScan	Value: SCons.Defaults.CScan
ARGUMENTS	Value: {}
ARGLIST	Value: []
BUILD_TARGETS	Value: []
COMMAND_LINE_TARGETS	Value: []
DEFAULT_TARGETS	Value: []
help_text	Value: None
sconscript_reading	Value: 0
GlobalDefaultEnvironmentFunctions	Value: ['Default', 'EnsurePythonVersion', 'EnsureSConsVersion', ...]
GlobalDefaultBuilders	Value: ['CFile', 'CXXFile', 'DVI', 'Jar', 'Java', 'JavaH', 'Libr...]
SConscript	Value: _SConscript.DefaultEnvironmentCall('SConscript')
Command	Value: _SConscript.DefaultEnvironmentCall('Command', subst= 1)
AddPostAction	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
AddPreAction	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Alias	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
AlwaysBuild	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
BuildDir	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...

continued on next page

Name	Description
CFile	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
CXXFile	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
CacheDir	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Clean	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
DVI	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Decider	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Default	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Depends	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Dir	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
EnsurePythonVersion	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
EnsureSConsVersion	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Entry	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Execute	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Exit	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...

continued on next page

Name	Description
Export	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
File	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
FindFile	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
FindInstalledFiles	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
FindSourceFiles	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Flatten	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
GetBuildPath	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
GetLaunchDir	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Glob	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Help	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Ignore	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Import	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Install	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
InstallAs	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...

continued on next page

Name	Description
InstallVersionedLib	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Jar	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Java	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
JavaH	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Library	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Literal	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
LoadableModule	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Local	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
M4	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
MSVSProject	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
NoCache	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
NoClean	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Object	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
PCH	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...

continued on next page

Name	Description
PDF	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Package	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
ParseDepends	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
PostScript	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Precious	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Program	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
PyPackageDir	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
RES	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
RMIC	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Repository	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Requires	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
SConscriptChdir	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
SConsignFile	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
SharedLibrary	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...


continued on next page

Name	Description
SharedObject	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
SideEffect	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
SourceCode	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
SourceSignatures	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Split	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
StaticLibrary	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
StaticObject	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Tag	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Tar	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
TargetSignatures	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
TypeLibrary	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Value	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
VariantDir	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...
Zip	Value: <SCons.Script.SConscript.DefaultEnvironmentCall object at...

continued on next page

Name	Description
<code>__package__</code>	Value: <code>'SCons.Script'</code>

30.4 Class *TargetList*



30.4.1 Methods

Inherited from UserList.UserList

`__add__()`, `__cmp__()`, `__contains__()`, `__delitem__()`, `__delslice__()`, `__eq__()`, `__ge__()`, `__getitem__()`, `__getslice__()`, `__gt__()`, `__iadd__()`, `__imul__()`, `__init__()`, `__le__()`, `__len__()`, `__lt__()`, `__mul__()`, `__ne__()`, `__radd__()`, `__repr__()`, `__rmul__()`, `__setitem__()`, `__setslice__()`, `append()`, `count()`, `extend()`, `index()`, `insert()`, `pop()`, `remove()`, `reverse()`, `sort()`

Inherited from __abcoll.Sequence

`__iter__()`, `__reversed__()`

Inherited from __abcoll.Sized

`__subclasshook__()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__new__()`, `__reduce__()`,
`__reduce_ex__()`, `__setattr__()`, `__sizeof__()`, `__str__()`

30.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

30.4.3 Class Variables

Name	Description
<i>Inherited from UserList.UserList</i>	
<code>__abstractmethods__</code> , <code>__hash__</code>	

31 Module **SCons.Script.Interactive**

SCons interactive mode

31.1 Functions

interact (<i>fs, parser, options, targets, target_top</i>)

31.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Script/Interactive.py 74b2c53bc42290e91...'
<code>__doc__</code>	Value: ...
<code>__package__</code>	Value: 'SCons.Script'

31.3 Class **SConsInteractiveCmd**

```
cmd.Cmd └─ SCons.Script.Interactive.SConsInteractiveCmd
```

build [TARGETS] Build the specified TARGETS and their dependencies. 'b' is a synonym.
clean [TARGETS] Clean (remove) the specified TARGETS and their dependencies. 'c' is a synonym.
exit Exit SCons interactive mode.
help [COMMAND] Prints help for the specified COMMAND. 'h' and '?' are synonyms.
shell [COMMANDLINE] Execute COMMANDLINE in a subshell. 'sh' and '!' are synonyms.
version Prints SCons version information.

31.3.1 Methods

__init__(*self*, ***kw*)

Instantiate a line-oriented interpreter framework.

The optional argument 'completekey' is the readline name of a completion key; it defaults to the Tab key. If completekey is not None and the readline module is available, command completion is done automatically. The optional arguments stdin and stdout specify alternate input and output file objects; if not specified, sys.stdin and sys.stdout are used. Overrides: cmd.Cmd.__init__ exitit(inherited documentation)

default(*self*, *argv*)

Called on an input line when the command prefix is not recognized.

If this method is not overridden, it prints an error message and returns. Overrides: cmd.Cmd.default exitit(inherited documentation)

onecmd(*self*, *line*)

Interpret the argument as though it had been typed in response to the prompt.

This may be overridden, but should not normally need to be; see the precmd() and postcmd() methods for useful execution hooks. The return value is a flag indicating whether interpretation of commands by the interpreter should stop. Overrides: cmd.Cmd.onecmd exitit(inherited documentation)

do_build(*self*, *argv*)

build [TARGETS] Build the specified TARGETS and their dependencies. 'b' is a synonym.

do_clean(*self*, *argv*)

clean [TARGETS] Clean (remove) the specified TARGETS and their dependencies. 'c' is a synonym.

do_EOF(*self*, *argv*)

do_exit(*self*, *argv*)

exit Exit SCons interactive mode.

do_help(*self*, *argv*)

help [COMMAND] Prints help for the specified COMMAND. 'h' and '?' are synonyms. Overrides: cmd.Cmd.do_help

do_shell(*self*, *argv*)

shell [COMMANDLINE] Execute COMMANDLINE in a subshell. 'sh' and '!' are synonyms.

do_version(*self*, *argv*)

version Prints SCons version information.

Inherited from cmd.Cmd

cmdloop(), columnize(), complete(), complete_help(), completedefault(), complete_names(), emptyline(), get_names(), parseline(), postcmd(), postloop(), precmd(), preloop(), print_topics()

31.3.2 Class Variables

Name	Description
synonyms	Value: {'b': 'build', 'c': 'clean', 'h': 'help', 'scons': 'build...'}
<i>Inherited from cmd.Cmd</i> doc_header, doc_leader, identchars, intro, lastcmd, misc_header, nohelp, prompt, ruler, undoc_header, use_rawinput	

32 Module *SCons.Script.Main*

SCons.Script

This file implements the `main()` function used by the `scons` script.

Architecturally, this *is* the `scons` script, and will likely only be called from the external "scons" wrapper. Consequently, anything here should not be, or be considered, part of the build engine. If it's something that we expect other software to want to use, it should go in some other module. If it's specific to the "scons" script invocation, it goes here.

32.1 Functions

```
fetch_win32_parallel_msg()
```

```
revert_io()
```

```
Progress(*args, **kw)
```

```
GetBuildFailures()
```

```
python_version_string()
```

```
python_version_unsupported(version=sys.version_info(major=2,  
minor=7, micro=6, releaselevel=...)
```

```
python_version_deprecated(version=sys.version_info(major=2,  
minor=7, micro=6, releaselevel=...)
```

```
AddOption(*args, **kw)
```

```
GetOption(name)
```

```
SetOption(name, value)
```

```
PrintHelp(file=None)
```

find_deepest_user_frame(*tb*)

Find the deepest stack frame that is not part of SCons.

Input is a "pre-processed" stack trace in the form returned by `traceback.extract_tb()` or `traceback.extract_stack()`

test_load_all_site_scons_dirs(*d*)

version_string(*label, module*)

path_string(*label, module*)

main()

32.2 Variables

Name	Description
unsupported_python_version	Value: (2, 6, 0)
deprecated_python_version	Value: (2, 7, 0)
__revision__	Value: 'src/engine/SCons/Script/Main.py 74b2c53bc42290e911b334a6...
display	Value: DisplayEngine()
progress_display	Value: SCons.Util.DisplayEngine()
first_command_start	Value: None
last_command_end	Value: None
ProgressObject	Value: Null(0x7F2C42E3A6D0)
print_objects	Value: 0
print_memoizer	Value: 0
print_stacktrace	Value: 0
print_time	Value: 0
sconsript_time	Value: 0
cumulative_command_time	Value: 0
exit_status	Value: 0
this_build_status	Value: 0
num_jobs	Value: None
delayed_warnings	Value: []
OptionsParser	Value: FakeOptionParser()

continued on next page

Name	Description
count_stats	Value: CountStats()
memory_stats	Value: MemStats()
__package__	Value: 'SCons.Script'

32.3 Class *SConsPrintHelpException*



32.3.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

32.3.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
__class__	

32.4 Class Progressor



32.4.1 Methods

```
__init__(self, obj, interval=1, file=None, overwrite=False)
```

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides:
object.**__init__** **exitit**(inherited documentation)

```
write(self, s)
```

```
erase__previous(self)
```

```
spinner(self, node)
```

```
string(self, node)
```

```
replace__string(self, node)
```

```
__call__(self, node)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),  
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),  
__str__(), __subclasshook__()
```

32.4.2 Properties

Name	Description
<i>Inherited from object</i> __class__	


32.4.3 Class Variables

Name	Description
prev	Value: ''

continued on next page

Name	Description
count	Value: 0
target_string	Value: '\$TARGET'

32.5 Class BuildTask



An SCons build task.

32.5.1 Methods

display(*self*, *message*)

Hook to allow the calling interface to display a message.

This hook gets called as part of preparing a task for execution (that is, a Node to be built). As part of figuring out what Node should be built next, the actual target list may be altered, along with a message describing the alteration. The calling interface can subclass Task and provide a concrete implementation of this method to see those messages. Overrides: SCons.Taskmaster.Task.display extit(inherited documentation)

prepare(*self*)

Called just before the task is executed.

This is mainly intended to give the target Nodes a chance to unlink underlying files and make all necessary directories before the Action is actually called to build the targets. Overrides: SCons.Taskmaster.Task.prepare extit(inherited documentation)

needs_execute(*self*)

Returns True (indicating this Task should be executed) if this Task's target state indicates it needs executing, which has already been determined by an earlier up-to-date check. Overrides: SCons.Taskmaster.Task.needs_execute

execute(*self*)

Called to execute the task.

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in `prepare()`, `executed()` or `failed()`. Overrides: `SCons.Taskmaster.Task.execute` extit(inherited documentation)

do_failed(*self*, *status*=2)**executed(*self*)**

Called when the task has been successfully executed and the Taskmaster instance wants to call the Node's callback methods.

This may have been a do-nothing operation (to preserve build order), so we must check the node's state before deciding whether it was "built", in which case we call the appropriate Node method. In any event, we always call "visited()", which will handle any post-visit actions that must take place regardless of whether or not the target was an actual built target or a source Node. Overrides: `SCons.Taskmaster.Task.executed` extit(inherited documentation)

failed(*self*)

Default action when a task fails: stop the build.

Note: Although this function is normally invoked on nodes in the executing state, it might also be invoked on up-to-date nodes when using `Configure()`. Overrides: `SCons.Taskmaster.Task.failed` extit(inherited documentation)

postprocess(*self*)

Post-processes a task after it's been executed.

This examines all the targets just built (or not, we don't care if the build was successful, or even if there was no build because everything was up-to-date) to see if they have any waiting parent Nodes, or Nodes waiting on a common side effect, that can be put back on the candidates list. Overrides: `SCons.Taskmaster.Task.postprocess` extit(inherited documentation)

make_ready(<i>self</i>)
Make a task ready for execution. Overrides: SCons.Taskmaster.Task.make_ready

Inherited from SCons.Taskmaster.Task(Section 35.4)

__init__(), exc_clear(), exc_info(), exception_set(), executed_with_callbacks(),
 executed_without_callbacks(), fail_continue(), fail_stop(), get_target(), make_ready_all(),
 make_ready_current(), trace_message()

Inherited from object


__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

32.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

32.5.3 Class Variables

Name	Description
progress	Value: Null(0x7F2C42E3A6D0)

32.6 Class CleanTask

An SCons clean task.

32.6.1 Methods

fs_delete(*self*, *path*, *pathstr*, *remove=True*)

show(*self*)

remove(*self*)

Called to execute the task.

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in `prepare()`, `executed()` or `failed()`.

execute(*self*)

Called to execute the task.

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in `prepare()`, `executed()` or `failed()`. Overrides: `SCons.Taskmaster.Task.execute` `exitit`(inherited documentation)

executed(*self*)

Called when the task has been successfully executed and the Taskmaster instance doesn't want to call the Node's callback methods. Overrides: `SCons.Taskmaster.Task.executed`

make_ready(*self*)

Marks all targets in a task ready for execution.

This is used when the interface needs every target Node to be visited--the canonical example being the "scons -c" option. Overrides: `SCons.Taskmaster.Task.make_ready`

prepare(*self*)

Called just before the task is executed.

This is mainly intended to give the target Nodes a chance to unlink underlying files and make all necessary directories before the Action is actually called to build the targets. Overrides: SCons.Taskmaster.Task.prepare extit(inherited documentation)

Inherited from SCons.Taskmaster.AlwaysTask(Section 35.5)

needs_execute()

Inherited from SCons.Taskmaster.Task(Section 35.4)

__init__(), display(), exc_clear(), exc_info(), exception_set(), executed_with_callbacks(),
executed_without_callbacks(), fail_continue(), fail_stop(), failed(), get_target(),
make_ready_all(), make_ready_current(), postprocess(), trace_message()


Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

32.6.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

32.7 Class QuestionTask



An SCons task for the -q (question) option.

32.7.1 Methods**prepare(*self*)**

Called just before the task is executed.

This is mainly intended to give the target Nodes a chance to unlink underlying files and make all necessary directories before the Action is actually called to build the targets. Overrides: SCons.Taskmaster.Task.prepare extit(inherited documentation)

execute(*self*)

Called to execute the task.

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in prepare(), executed() or failed(). Overrides: SCons.Taskmaster.Task.execute extit(inherited documentation)

executed(*self*)

Called when the task has been successfully executed and the Taskmaster instance wants to call the Node's callback methods.

This may have been a do-nothing operation (to preserve build order), so we must check the node's state before deciding whether it was "built", in which case we call the appropriate Node method. In any event, we always call "visited()", which will handle any post-visit actions that must take place regardless of whether or not the target was an actual built target or a source Node. Overrides: SCons.Taskmaster.Task.executed extit(inherited documentation)

Inherited from SCons.Taskmaster.AlwaysTask(Section 35.5)

needs_execute()

Inherited from SCons.Taskmaster.Task(Section 35.4)

__init__(), display(), exc_clear(), exc_info(), exception_set(), executed_with_callbacks(), executed_without_callbacks(), fail_continue(), fail_stop(), failed(), get_target(), make_ready(), make_ready_all(), make_ready_current(), postprocess(), trace_message()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),

`__str__()`, `__subclasshook__()`

32.7.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

32.8 Class `TreePrinter`

```

object
 |
 |__SCons.Script.Main.TreePrinter

```

32.8.1 Methods

<code>__init__(self, derived=False, prune=False, status=False)</code>
<code>x.__init__(...)</code> initializes x; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> extit(inherited documentation)
<code>get_all_children(self, node)</code>
<code>get_derived_children(self, node)</code>
<code>display(self, t)</code>

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

32.8.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

32.9 Class FakeOptionParser



A do-nothing option parser, used for the initial OptionsParser variable.

During normal SCons operation, the OptionsParser is created right away by the main() function. Certain tests scripts however, can introspect on different Tool modules, the initialization of which can try to add a new, local option to an otherwise uninitialized OptionsParser object. This allows that introspection to happen without blowing up.

32.9.1 Methods

<code>add_local_option(self, *args, **kw)</code>
--

Inherited from object

```

__delattr__(), __format__(), __getattr__(), __hash__(), __init__(),
__new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(),
__sizeof__(), __str__(), __subclasshook__()

```

32.9.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

32.9.3 Class Variables

Name	Description
values	Value: FakeOptionValues()

32.10 Class Stats



Known Subclasses: SCons.Script.Main.CountStats, SCons.Script.Main.MemStats

32.10.1 Methods

```
__init__(self)
```

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` `exitit`(inherited documentation)

```
enable(self, outfp)
```

```
do_nothing(self, *args, **kw)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

32.10.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

32.11 Class CountStats



32.11.1 Methods

```
do_append(self, label)
```

```
do_print(self)
```

Inherited from SCons.Script.Main.Stats(Section 32.10)

```
__init__(), do_nothing(), enable()
```


Inherited from object


```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

32.11.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

32.12 Class MemStats



32.12.1 Methods

```
do_append(self, label)
```

```
do_print(self)
```

Inherited from SCons.Script.Main.Stats(Section 32.10)

```
__init__(), do_nothing(), enable()
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

32.12.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

33 Module *SCons.Script.SConscript*

SCons.Script.SConscript

This module defines the Python API provided to *SConscript* and *SConstruct* files.

33.1 Functions

get_calling_namespaces()

Return the locals and globals for the function that called into this module in the current call stack.

compute_exports(*exports*)

Compute a dictionary of exports given one of the parameters to the *Export()* function or the *exports* argument to *SConscript()*.

Return(vars*, ***kw*)**

SConscript_exception(*file=sys.stderr*)

Print an exception stack trace just for the *SConscript* file(s). This will show users who have Python errors where the problem is, without cluttering the output with all of the internal calls leading up to where we exec the *SConscript*.

annotate(*node*)

Annotate a node with the stack frame describing the *SConscript* file and line number that created it.

Configure(args*, ***kw*)**

get_DefaultEnvironmentProxy()

BuildDefaultGlobals()

Create a dictionary containing all the default globals for SConstruct and SConscript files.

33.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Script/SConscript.py 74b2c53bc42290e911...'
<code>launch_dir</code>	Value: '/home/bdbaddog/scons/git/as_scons'
<code>GlobalDict</code>	Value: None
<code>global_exports</code>	Value: {}
<code>sconscript_chdir</code>	Value: 1
<code>call_stack</code>	Value: []
<code>stack_bottom</code>	Value: '% Stack bottom %'
<code>__package__</code>	Value: 'SCons.Script'

33.3 Class SConscriptReturn**33.3.1 Methods*****Inherited from exceptions.Exception***

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

33.3.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

33.4 Class Frame

object —
SCons.Script.SConscript'.Frame

A frame on the SConstruct/SConscript call stack

33.4.1 Methods

<code>__init__(self, fs, exports, sconsript)</code>
x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)


Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

33.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

33.5 Class SConsEnvironment



An Environment subclass that contains all of the methods that are particular to the wrapper SCons interface and which aren't (or shouldn't be) part of the build engine itself.

Note that not all of the methods of this class have corresponding global functions, there are some private methods.

33.5.1 Methods

Configure(*self*, *args, **kw)

Overrides: `SCons.Environment.Base.Configure`

Default(*self*, *targets)

EnsureSConsVersion(*self*, major, minor, revision=0)

Exit abnormally if the SCons version is not late enough.

EnsurePythonVersion(*self*, major, minor)

Exit abnormally if the Python version is not late enough.

Exit(*self*, value=0)

Export(*self*, *vars, **kw)

GetLaunchDir(*self*)

GetOption(*self*, name)

Help (<i>self</i> , <i>text</i> , <i>append=False</i>)

Import (<i>self</i> , * <i>vars</i>)

SConscript (<i>self</i> , * <i>ls</i> , ** <i>kw</i>)
--

SConscriptChdir (<i>self</i> , <i>flag</i>)
--

SetOption (<i>self</i> , <i>name</i> , <i>value</i>)

Inherited from SCons.Environment.Base(Section 8.9)

Action(), AddPostAction(), AddPreAction(), Alias(), AlwaysBuild(), Append(), AppendENVPath(), AppendUnique(), BuildDir(), Builder(), CacheDir(), Clean(), Clone(), Command(), Copy(), Decider(), Depends(), Detect(), Dictionary(), Dir(), Dump(), Entry(), Environment(), Execute(), File(), FindFile(), FindInstalledFiles(), FindIxes(), FindSourceFiles(), Flatten(), GetBuildPath(), Glob(), Ignore(), Literal(), Local(), NoCache(), NoClean(), ParseConfig(), ParseDepends(), Platform(), Precious(), Prepend(), PrependENVPath(), PrependUnique(), Pseudo(), PyPackageDir(), Replace(), ReplaceIxes(), Repository(), Requires(), SConsignFile(), Scanner(), SetDefault(), SideEffect(), SourceCode(), SourceSignatures(), Split(), TargetSignatures(), Tool(), Value(), VariantDir(), WhereIs(), __init__(), get_CacheDir(), get_builder(), get_factory(), get_scanner(), get_src_sig_type(), get_tgt_sig_type(), scanner_map_delete()

Inherited from SCons.Environment.SubstitutionEnvironment(Section 8.6)

AddMethod(), MergeFlags(), Override(), ParseFlags(), RemoveMethod(), __contains__(), __delitem__(), __eq__(), __getitem__(), __setitem__(), arg2nodes(), backtick(), get(), gvars(), has_key(), items(), lvars(), subst(), subst_kw(), subst_list(), subst_path(), subst_target_source()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

33.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

33.6 Class `DefaultEnvironmentCall`



A class that implements "global function" calls of Environment methods by fetching the specified method from the DefaultEnvironment's class. Note that this uses an intermediate proxy class instead of calling the DefaultEnvironment method directly so that the proxy can override the `subst()` method and thereby prevent expansion of construction variables (since from the user's point of view this was called as a global function, with no associated construction environment).

33.6.1 Methods

<code>__init__(self, method_name, subst=0)</code>

<code>x.__init__(...)</code> initializes x; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)

<code>__call__(self, *args, **kw)</code>
--

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

33.6.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

34 Module SCons.Subst

SCons.Subst

SCons string substitution.

34.1 Functions

SetAllowableExceptions (* <i>excepts</i>)

raise__exception (<i>exception</i> , <i>target</i> , <i>s</i>)

quote__spaces (<i>arg</i>)

Generic function for putting double quotes around any string that has white space in it.

escape__list (<i>mylist</i> , <i>escape__func</i>)

Escape a list of arguments by running the specified `escape__func` on every object in the list that has an `escape()` method.

subst__dict (<i>target</i> , <i>source</i>)
--

Create a dictionary for substitution of special construction variables.

This translates the following special arguments:

target - the target (object or array of objects), used to generate the TARGET and TARGETS construction variables

source - the source (object or array of objects), used to generate the SOURCES and SOURCE construction variables


```
scons__subst(strSubst, env, mode=1, target=None, source=None, gvars={},  
lvars={}, conv=None)
```

Expand a string or list containing construction variable substitutions.

This is the work-horse function for substitutions in file names and the like. The companion `scons__subst__list()` function (below) handles separating command lines into lists of arguments, so see that function if that's what you're looking for.

```
scons__subst__list(strSubst, env, mode=1, target=None, source=None,  
gvars={}, lvars={}, conv=None)
```

Substitute construction variables in a string (or list or other object) and separate the arguments into a command list.

The companion `scons__subst()` function (above) handles basic substitutions within strings, so see that function instead if that's what you're looking for.

```
scons__subst__once(strSubst, env, key)
```

Perform single (non-recursive) substitution of a single construction variable keyword.

This is used when setting a variable when copying or overriding values in an Environment. We want to capture (expand) the old value before we override it, so people can do things like:

```
env2 = env.Clone(CCFLAGS = '$CCFLAGS -g')
```

We do this with some straightforward, brute-force code here...

34.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/Subst.py 74b2c53bc42290e911b334a6b44f18...
<code>AllowableExceptions</code>	Value: (<type 'exceptions.IndexError'>, <type 'exceptions.NameEr...
<code>NullNodesList</code>	Value: Null(0x7F2C43D93610)

continued on next page

Name	Description
SUBST_CMD	Value: 0
SUBST_RAW	Value: 1
SUBST_SIG	Value: 2
__package__	Value: 'SCons'

34.3 Class Literal

object —
SCons.Subst.Literal

A wrapper for a string. If you use this object wrapped around a string, then it will be interpreted as literal. When passed to the command interpreter, all special characters will be escaped.

34.3.1 Methods

__init__(*self*, *lstr*)

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides:
object.**__init__** **exitit**(inherited documentation)

__str__(*self*)

str(x) Overrides: object.**__str__** **exitit**(inherited documentation)

escape(*self*, *escape_func*)

for_signature(*self*)

is_literal(*self*)

__eq__(*self*, *other*)

__neq__(*self*, *other*)

Inherited from object

__delattr__(), **__format__**(), **__getattr__**(), **__hash__**(), **__new__**(),
__reduce__(), **__reduce_ex__**(), **__repr__**(), **__setattr__**(), **__sizeof__**(),
__subclasshook__()

34.3.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

34.4 Class SpecialAttrWrapper



This is a wrapper for what we call a 'Node special attribute.' This is any of the attributes of a Node that we can reference from Environment variable substitution, such as \$TARGET.abspath or \$SOURCES[1].filebase. We implement the same methods as Literal so we can handle special characters, plus a for_signature method, such that we can return some canonical string during signature calculation to avoid unnecessary rebuilds.

34.4.1 Methods

__init__ (self, lstr, for_signature=None)
The for_signature parameter, if supplied, will be the canonical string we return from for_signature(). Else we will simply return lstr. Overrides: object.__init__
__str__ (self)
str(x) Overrides: object.__str__ exitit(inherited documentation)
escape (self, escape_func)
for_signature (self)
is_literal (self)


Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __subclasshook__()

34.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

34.5 Class CmdStringHolder



This is a special class used to hold strings generated by `scons_subst()` and `scons_subst_list()`. It defines a special method `escape()`. When passed a function with an escape algorithm for a particular platform, it will return the contained string with the proper escape sequences inserted.

34.5.1 Methods

<code>__init__(self, cmd, literal=None)</code>
--

<code>x.__init__(...)</code> initializes x; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)

<code>is_literal(self)</code>

```
escape(self, escape_func, quote_func=<function quote_spaces at
0x7f2c43d875f0>)
```

Escape the string with the supplied function. The function is expected to take an arbitrary string, then return it with all special characters escaped and ready for passing to the command interpreter.

After calling this function, the next call to str() will return the escaped string.

Inherited from UserString.UserString

```
__add__(), __cmp__(), __complex__(), __contains__(), __float__(), __getitem__(),
__getslice__(), __hash__(), __int__(), __len__(), __long__(), __mod__(),
__mul__(), __radd__(), __repr__(), __rmul__(), __str__(), capitalize(),
center(), count(), decode(), encode(), endswith(), expandtabs(), find(), index(),
isalnum(), isalpha(), isdecimal(), isdigit(), islower(), isnumeric(), isspace(),
is-title(), isupper(), join(), ljust(), lower(), lstrip(), partition(), replace(), rfind(),
rindex(), rjust(), rpartition(), rsplit(), rstrip(), split(), splitlines(), startswith(),
strip(), swapcase(), title(), translate(), upper(), zfill()
```

Inherited from __abcoll.Sequence

```
__iter__(), __reversed__()
```

Inherited from __abcoll.Sized

```
__subclasshook__()
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __new__(), __reduce__(),
__reduce_ex__(), __setattr__(), __sizeof__()
```

34.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

34.5.3 Class Variables

Name	Description
<i>Inherited from UserString.UserString</i>	
__abstractmethods__	

34.6 Class NLWrapper



A wrapper class that delays turning a list of sources or targets into a NodeList until it's needed. The specified function supplied when the object is initialized is responsible for turning raw nodes into proxies that implement the special attributes like `.abspath`, `.source`, etc. This way, we avoid creating those proxies just "in case" someone is going to use `$TARGET` or the like, and only go through the trouble if we really have to.

In practice, this might be a wash performance-wise, but it's a little cleaner conceptually...

34.6.1 Methods

```
__init__(self, list, func)
```

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` `exitit`(inherited documentation)


Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

34.6.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

34.7 Class `Targets_or_Sources`



A class that implements `$TARGETS` or `$SOURCES` expansions by in turn wrapping a `NLWrapper`. This class handles the different methods used to access the list, calling the `NLWrapper` to create proxies on demand.

Note that we subclass `collections.UserList` purely so that the `is_Sequence()` function will identify an object of this class as a list during variable expansion. We're not really using any `collections.UserList` methods in practice.

34.7.1 Methods

`__init__`(*self*, *nl*)

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature. Overrides: `object.__init__` extit(inherited documentation)

`__getattr__`(*self*, *attr*)

`__getitem__`(*self*, *i*)

Overrides: `_abcoll.Sequence.__getitem__`

<code>__getslice__(self, i, j)</code>

Overrides: <code>UserList.UserList.__getslice__</code>
--

<code>__str__(self)</code>

<code>str(x)</code> Overrides: <code>object.__str__</code> <code>exitit</code> (inherited documentation)
--

<code>__repr__(self)</code>

<code>repr(x)</code> Overrides: <code>object.__repr__</code> <code>exitit</code> (inherited documentation)
--

Inherited from `UserList.UserList`

`__add__()`, `__cmp__()`, `__contains__()`, `__delitem__()`, `__delslice__()`,
`__eq__()`, `__ge__()`, `__gt__()`, `__iadd__()`, `__imul__()`, `__le__()`, `__len__()`,
`__lt__()`, `__mul__()`, `__ne__()`, `__radd__()`, `__rmul__()`, `__setitem__()`,
`__setslice__()`, `append()`, `count()`, `extend()`, `index()`, `insert()`, `pop()`, `remove()`,
`reverse()`, `sort()`

Inherited from `__abcoll.Sequence`

`__iter__()`, `__reversed__()`

Inherited from `__abcoll.Sized`

`__subclasshook__()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__new__()`, `__reduce__()`,
`__reduce_ex__()`, `__setattr__()`, `__sizeof__()`

34.7.2 Properties

Name	Description
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

34.7.3 Class Variables

Name	Description
<i>Inherited from <code>UserList.UserList</code></i>	
<code>__abstractmethods__</code> , <code>__hash__</code>	

34.8 Class `Target_or_Source`



A class that implements `$TARGET` or `$SOURCE` expansions by in turn wrapping a `NLWrapper`. This class handles the different methods used to access an individual proxy Node, calling the `NLWrapper` to create a proxy on demand.

34.8.1 Methods

<code>__init__(self, nl)</code>

<code>x.__init__(...)</code> initializes <code>x</code> ; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> extit(inherited documentation)

<code>__getattr__(self, attr)</code>

<code>__str__(self)</code>

<code>str(x)</code> Overrides: <code>object.__str__</code> extit(inherited documentation)

<code>__repr__(self)</code>

<code>repr(x)</code> Overrides: <code>object.__repr__</code> extit(inherited documentation)


Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__setattr__()`, `__sizeof__()`, `__subclasshook__()`

34.8.2 Properties

Name	Description
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

34.9 Class *NullNodeList*



34.9.1 Methods

<code>__call__(self, *args, **kwargs)</code>
--

Overrides: <code>SCons.Util.Null.__call__</code>
--

<code>__str__(self)</code>

<code>str(x)</code> Overrides: <code>object.__str__</code> <code>exitit</code> (inherited documentation)
--

Inherited from `SCons.Util.NullSeq`(Section 36.17)

`__delitem__()`, `__getitem__()`, `__iter__()`, `__len__()`, `__setitem__()`

Inherited from `SCons.Util.Null`(Section 36.16)

`__bool__()`, `__delattr__()`, `__getattr__()`, `__init__()`, `__new__()`, `__nonzero__()`,
`__repr__()`, `__setattr__()`

Inherited from `object`

`__format__()`, `__getattribute__()`, `__hash__()`, `__reduce__()`, `__reduce_ex__()`,
`__sizeof__()`, `__subclasshook__()`

34.9.2 Properties

Name	Description
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

35 Module SCons.Taskmaster

This module contains the primary interface(s) between a wrapping user interface and the SCons build engine. There are two key classes here:

Taskmaster

This is the main engine for walking the dependency graph and calling things to decide what does or doesn't need to be built.

Task

This is the base class for allowing a wrapping interface to decide what does or doesn't actually need to be done. The intention is for a wrapping interface to subclass this as appropriate for different types of behavior it may need.

The canonical example is the SCons native Python interface, which has Task subclasses that handle its specific behavior, like printing "'foo' is up to date" when a top-level target doesn't need to be built, and handling the -c option by removing targets as its "build" action. There is also a separate subclass for suppressing this output when the -q option is used.

The Taskmaster instantiates a Task object for each (set of) target(s) that it decides need to be evaluated and/or built.

35.1 Functions

dump_stats()

find_cycle(*stack*, *visited*)

35.2 Variables

Name	Description
__doc__	Value: ...
__revision__	Value: 'src/engine/SCons/Taskmaster.py 74b2c53bc42290e911b334a6b...
StateString	Value: {0: 'no_state', 1: 'pending', 2: 'executing', 3: 'up_to_d...
NODE_NO_STATE	Value: 0
NODE_PENDING	Value: 1

continued on next page

Name	Description
NODE_EXECUTING	Value: 2
NODE_UP_TO_DATE	Value: 3
NODE_EXECUTED	Value: 4
NODE_FAILED	Value: 5
print_prepare	Value: 0
CollectStats	Value: None
StatsNodes	Value: []
fmt	Value: '%(considered)3d %(already_handled)3d %(problem)3d %(chil...
__package__	Value: 'SCons'

35.3 Class Stats

object —
SCons.Taskmaster.Stats

A simple class for holding statistics about the disposition of a Node by the Taskmaster. If we're collecting statistics, each Node processed by the Taskmaster gets one of these attached, in which case the Taskmaster records its decision each time it processes the Node. (Ideally, that's just once per Node.)

35.3.1 Methods

__init__ (<i>self</i>)
Instantiates a Taskmaster.Stats object, initializing all appropriate counters to zero. Overrides: object.__init__

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

35.3.2 Properties

Name	Description
<i>Inherited from object</i>	

continued on next page

Name	Description
<code>__class__</code>	

35.4 Class Task



Known Subclasses: SCons.Taskmaster.AlwaysTask, SCons.Taskmaster.OutOfDateTask

Default SCons build engine task.

This controls the interaction of the actual building of node and the rest of the engine.

This is expected to handle all of the normally-customizable aspects of controlling a build, so any given application *should* be able to do what it wants by sub-classing this class and overriding methods as appropriate. If an application needs to customize something by sub-classing Taskmaster (or some other build engine class), we should first try to migrate that functionality into this class.

Note that it's generally a good idea for sub-classes to call these methods explicitly to update state, etc., rather than roll their own interaction with Taskmaster from scratch.

35.4.1 Methods

```
__init__(self, tm, targets, top, node)
```

x.__init__(...) initializes x; see help(type(x)) for signature Overrides:
object.__init__ extit(inherited documentation)

```
trace_message(self, method, node, description='node')
```

```
display(self, message)
```

Hook to allow the calling interface to display a message.

This hook gets called as part of preparing a task for execution (that is, a Node to be built). As part of figuring out what Node should be built next, the actual target list may be altered, along with a message describing the alteration. The calling interface can subclass Task and provide a concrete implementation of this method to see those messages.

prepare(*self*)

Called just before the task is executed.

This is mainly intended to give the target Nodes a chance to unlink underlying files and make all necessary directories before the Action is actually called to build the targets.

get_target(*self*)

Fetch the target being built or updated by this task.

needs_execute(*self*)**execute(*self*)**

Called to execute the task.

This method is called from multiple threads in a parallel build, so only do thread safe stuff here. Do thread unsafe stuff in prepare(), executed() or failed().

executed_without_callbacks(*self*)

Called when the task has been successfully executed and the Taskmaster instance doesn't want to call the Node's callback methods.

executed_with_callbacks(*self*)

Called when the task has been successfully executed and the Taskmaster instance wants to call the Node's callback methods.

This may have been a do-nothing operation (to preserve build order), so we must check the node's state before deciding whether it was "built", in which case we call the appropriate Node method. In any event, we always call "visited()", which will handle any post-visit actions that must take place regardless of whether or not the target was an actual built target or a source Node.

executed(*self*)

Called when the task has been successfully executed and the Taskmaster instance wants to call the Node's callback methods.

This may have been a do-nothing operation (to preserve build order), so we must check the node's state before deciding whether it was "built", in which case we call the appropriate Node method. In any event, we always call "visited()", which will handle any post-visit actions that must take place regardless of whether or not the target was an actual built target or a source Node.

failed(*self*)

Default action when a task fails: stop the build.

Note: Although this function is normally invoked on nodes in the executing state, it might also be invoked on up-to-date nodes when using Configure().

fail_stop(*self*)

Explicit stop-the-build failure.

This sets failure status on the target nodes and all of their dependent parent nodes.

Note: Although this function is normally invoked on nodes in the executing state, it might also be invoked on up-to-date nodes when using Configure().

fail_continue(*self*)

Explicit continue-the-build failure.

This sets failure status on the target nodes and all of their dependent parent nodes.

Note: Although this function is normally invoked on nodes in the executing state, it might also be invoked on up-to-date nodes when using Configure().

make_ready_all(*self*)

Marks all targets in a task ready for execution.

This is used when the interface needs every target Node to be visited--the canonical example being the "scons -c" option.

make_ready_current(*self*)

Marks all targets in a task ready for execution if any target is not current.

This is the default behavior for building only what's necessary.

make_ready(*self*)

Marks all targets in a task ready for execution if any target is not current.

This is the default behavior for building only what's necessary.

postprocess(*self*)

Post-processes a task after it's been executed.

This examines all the targets just built (or not, we don't care if the build was successful, or even if there was no build because everything was up-to-date) to see if they have any waiting parent Nodes, or Nodes waiting on a common side effect, that can be put back on the candidates list.

exc_info(*self*)

Returns info about a recorded exception.

exc_clear(*self*)

Clears any recorded exception.

This also changes the "exception_raise" attribute to point to the appropriate do-nothing method.

exception_set(*self*, *exception*=None)

Records an exception to be raised at the appropriate time.

This also changes the "exception_raise" attribute to point to the method that will, in fact

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

35.4.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

35.5 Class AlwaysTask

object └─

SCons.Taskmaster.Task └─

SCons.Taskmaster.AlwaysTask

Known Subclasses: SCons.SConf.SConfBuildTask, SCons.Script.Main.CleanTask, SCons.Script.Main.Q

35.5.1 Methods

needs_execute(*self*)

Always returns True (indicating this Task should always be executed).

Subclasses that need this behavior (as opposed to the default of only executing Nodes that are out of date w.r.t. their dependencies) can use this as follows:

```
class MyTaskSubclass(SCons.Taskmaster.Task):
    needs_execute = SCons.Taskmaster.Task.execute_always
```

Overrides: SCons.Taskmaster.Task.needs_execute

Inherited from SCons.Taskmaster.Task(Section 35.4)

`__init__()`, `display()`, `exc_clear()`, `exc_info()`, `exception_set()`, `execute()`, `executed()`, `executed_with_callbacks()`, `executed_without_callbacks()`, `fail_continue()`, `fail_stop()`, `failed()`, `get_target()`, `make_ready()`, `make_ready_all()`, `make_ready_current()`, `postprocess()`, `prepare()`, `trace_message()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

35.5.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

35.6 Class OutOfDateTask



Known Subclasses: SCons.Script.Main.BuildTask

35.6.1 Methods

needs_execute(*self*)

Returns True (indicating this Task should be executed) if this Task's target state indicates it needs executing, which has already been determined by an earlier up-to-date check. Overrides: SCons.Taskmaster.Task.needs_execute

Inherited from SCons.Taskmaster.Task(Section 35.4)

`__init__()`, `display()`, `exc_clear()`, `exc_info()`, `exception_set()`, `execute()`, `executed()`, `executed_with_callbacks()`, `executed_without_callbacks()`, `fail_continue()`, `fail_stop()`, `failed()`, `get_target()`, `make_ready()`, `make_ready_all()`, `make_ready_current()`, `postprocess()`, `prepare()`, `trace_message()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

35.6.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

35.7 Class Taskmaster

object —
SCons.Taskmaster.Taskmaster

The Taskmaster for walking the dependency DAG.

35.7.1 Methods

__init__(*self*, *targets*=[], *tasker*=None, *order*=None, *trace*=None)

x.__init__(...) initializes *x*; see `help(type(x))` for signature Overrides: `object.__init__` `extit`(inherited documentation)

find_next_candidate(*self*)

Returns the next candidate Node for (potential) evaluation.

The candidate list (really a stack) initially consists of all of the top-level (command line) targets provided when the Taskmaster was initialized. While we walk the DAG, visiting Nodes, all the children that haven't finished processing get pushed on to the candidate list. Each child can then be popped and examined in turn for whether *their* children are all up-to-date, in which case a Task will be created for their actual evaluation and potential building.

Here is where we also allow candidate Nodes to alter the list of Nodes that should be examined. This is used, for example, when invoking SCons in a source directory. A source directory Node can return its corresponding build directory Node, essentially saying, "Hey, you really need to build this thing over here instead."

no_next_candidate(*self*)

Stops Taskmaster processing by not returning a next candidate.

Note that we have to clean-up the Taskmaster candidate list because the cycle detection depends on the fact all nodes have been processed somehow.

trace_message(*self*, *message*)**trace_node**(*self*, *node*)**next_task**(*self*)

Returns the next task to be executed.

This simply asks for the next Node to be evaluated, and then wraps it in the specific Task subclass with which we were initialized.

```
will_not_build(self, nodes, node_func=<function <lambda> at
0x7f2c43288de8>)
```

Perform clean-up about nodes that will never be built. Invokes a user defined function on all of these nodes (including all of their parents).

```
stop(self)
```

Stops the current build completely.

```
cleanup(self)
```

Check for dependency cycles.

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

35.7.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

36 Module *SCons.Util*

SCons.Util

Various utility functions go here.

36.1 Functions

dictify(*keys*, *values*, *result*={})

rightmost__separator(*path*, *sep*)

containsAny(*str*, *set*)

Check whether sequence *str* contains ANY of the items in *set*.

containsAll(*str*, *set*)

Check whether sequence *str* contains ALL of the items in *set*.

containsOnly(*str*, *set*)

Check whether sequence *str* contains ONLY items in *set*.

splitext(*path*)

Same as `os.path.splitext()` but faster.

updrive(*path*)

Make the drive letter (if any) upper case. This is useful because Windows is inconsistent on the case of the drive letter, which can cause inconsistencies when calculating command signatures.

get_environment_var(*varstr*)

Given a string, first determine if it looks like a reference to a single environment variable, like "\$FOO" or "\${FOO}". If so, return that variable with no decorations ("FOO"). If not, return None.

render_tree(*root*, *child_func*, *prune*=0, *margin*=[0], *visited*=None)

Render a tree of nodes into an ASCII tree view. **Parameters**

root: : the root node of the tree

child_func: : the function called to get the children of a node

prune: : don't visit the same node twice

margin: : the format of the left margin to use for children of root. 1 results in a pipe, and 0 results in no pipe.

visited: : a dictionary of visited nodes in the current branch if not prune, or in the whole tree if prune.

IDX(*N*)

print_tree(*root*, *child_func*, *prune*=0, *showtags*=0, *margin*=[0], *visited*=None)

Print a tree of nodes. This is like `render_tree`, except it prints lines directly instead of creating a string representation in memory, so that huge trees can be printed. **Parameters**

root: - the root node of the tree

child_func: - the function called to get the children of a node

prune: - don't visit the same node twice

showtags: - print status information to the left of each node line

margin: - the format of the left margin to use for children of root. 1 results in a pipe, and 0 results in no pipe.

visited: - a dictionary of visited nodes in the current branch if not prune, or in the whole tree if prune.

is_Dict(*obj*, *isinstance*=<built-in function isinstance>, *DictTypes*=dict, UserDict)

```
is_List(obj, isinstance=<built-in function isinstance>,
ListTypes=(<type 'list'>, <class 'UserList.UserList'>))
```

```
is_Sequence(obj, isinstance=<built-in function isinstance>,
SequenceTypes=(<type 'list'>, <type 'tuple'>, <class
'UserList.UserList'>))
```

```
is_Tuple(obj, isinstance=<built-in function isinstance>, tuple=<type
'tuple'>)
```

```
is_String(obj, isinstance=<built-in function isinstance>,
StringTypes=(<type 'str'>, <type 'unicode'>, <class
'UserString.UserS...>))
```

```
is_Scalar(obj, isinstance=<built-in function isinstance>,
StringTypes=(<type 'str'>, <type 'unicode'>, <class
'UserString.UserS...>, SequenceTypes=(<type 'list'>, <type
'tuple'>, <class 'UserList.UserList'>))
```

```
do_flatten(sequence, result, isinstance=<built-in function isinstance>,
StringTypes=(<type 'str'>, <type 'unicode'>, <class
'UserString.UserS...>, SequenceTypes=(<type 'list'>, <type
'tuple'>, <class 'UserList.UserList'>))
```

```
flatten(obj, isinstance=<built-in function isinstance>,
StringTypes=(<type 'str'>, <type 'unicode'>, <class
'UserString.UserS...>, SequenceTypes=(<type 'list'>, <type
'tuple'>, <class 'UserList.UserList'>)), do_flatten=<function
do_flatten at 0x7f2c43d7a9b0>)
```

Flatten a sequence to a non-nested list.

Flatten() converts either a single scalar or a nested sequence to a non-nested list. Note that flatten() considers strings to be scalars instead of sequences like Python would.


```
flatten_sequence(sequence, isinstance=<built-in function isinstance>,
StringTypes=(<type 'str'>, <type 'unicode'>, <class
'UserString.UserString'>, SequenceTypes=(<type 'list'>, <type
'tuple'>, <class 'UserList.UserList'>), do_flatten=<function
do_flatten at 0x7f2c43d7a9b0>)
```

Flatten a sequence to a non-nested list.

Same as `flatten()`, but it does not handle the single scalar case. This is slightly more efficient when one knows that the sequence to flatten can not be a scalar.

```
to_String(s, isinstance=<built-in function isinstance>, str=<type
'str'>, UserString=<class 'UserString.UserString'>,
BaseStringTypes=(<type 'str'>, <type 'unicode'>))
```

```
to_String_for_subst(s, isinstance=<built-in function isinstance>,
str=<type 'str'>, to_String=<function to_String at 0x7f2c43d7ab18>,
BaseStringTypes=(<type 'str'>, <type 'unicode'>),
SequenceTypes=(<type 'list'>, <type 'tuple'>, <class
'UserList.UserList'>), UserString=<class 'UserString.UserString'>)
```

```
to_String_for_signature(obj, to_String_for_subst=<function
to_String_for_subst at 0x7f2c43d7ab90>, AttributeError=<type
'exceptions.AttributeError'>)
```

```
semi_deepcopy_dict(x, exclude=[])
```

```
semi_deepcopy(x)
```

```
RegGetValue(root, key)
```

```
RegOpenKeyEx(root, key)
```

```
WhereIs(file, path=None, pathext=None, reject=[])
```

```
PrependPath(oldpath, newpath, sep=':', delete_existing=1,  
canonicalize=None)
```

This prepends newpath elements to the given oldpath. Will only add any particular path once (leaving the first one it encounters and ignoring the rest, to preserve path order), and will os.path.normpath and os.path.normcase all paths to help assure this. This can also handle the case where the given old path variable is a list instead of a string, in which case a list will be returned instead of a string.

Example: Old Path: "/foo/bar:/foo" New Path: "/biz/boom:/foo" Result:
"/biz/boom:/foo:/foo/bar"

If delete_existing is 0, then adding a path that exists will not move it to the beginning; it will stay where it is in the list.

If canonicalize is not None, it is applied to each element of newpath before use.

```
AppendPath(oldpath, newpath, sep=':', delete_existing=1,  
canonicalize=None)
```

This appends new path elements to the given old path. Will only add any particular path once (leaving the last one it encounters and ignoring the rest, to preserve path order), and will os.path.normpath and os.path.normcase all paths to help assure this. This can also handle the case where the given old path variable is a list instead of a string, in which case a list will be returned instead of a string.

Example: Old Path: "/foo/bar:/foo" New Path: "/biz/boom:/foo" Result:
"/foo/bar:/biz/boom:/foo"

If delete_existing is 0, then adding a path that exists will not move it to the end; it will stay where it is in the list.

If canonicalize is not None, it is applied to each element of newpath before use.

AddPathIfNotExists(*env_dict*, *key*, *path*, *sep*=':')

This function will take 'key' out of the dictionary 'env_dict', then add the path 'path' to that key if it is not already there. This treats the value of env_dict[key] as if it has a similar format to the PATH variable...a list of paths separated by tokens. The 'path' will get added to the list if it is not already there.

get_native_path(*path*)

Transforms an absolute path into a native path for the system. Non-Cygwin version, just leave the path alone.

Split(*arg*)**case_sensitive_suffixes**(*s1*, *s2*)**adjustixes**(*fname*, *pre*, *suf*, *ensure_suffix*=False)**unique**(*s*)

Return a list of the elements in s, but without duplicates.

For example, unique([1,2,3,1,2,3]) is some permutation of [1,2,3], unique("abcbac") some permutation of ["a", "b", "c"], and unique(([1, 2], [2, 3], [1, 2])) some permutation of [[2, 3], [1, 2]].

For best speed, all sequence elements should be hashable. Then unique() will usually work in linear time.

If not possible, the sequence elements should enjoy a total ordering, and if list(s).sort() doesn't raise TypeError it's assumed that they do enjoy a total ordering. Then unique() will usually work in O(N*log2(N)) time.

If that's not possible either, the sequence elements must support equality-testing. Then unique() will usually work in quadratic time.

uniquer(*seq*, *idfun*=None)

uniquer__hashables(*seq*)**logical_lines**(*physical_lines*, *joiner*=<built-in method join of str object at 0x7f2c4736d508>)**make_path_relative**(*path*)

makes an absolute path name to a relative pathname.

AddMethod(*obj*, *function*, *name*=None)

Adds either a bound method to an instance or the function itself (or an unbound method in Python 2) to a class. If name is omitted the name of the specified function is used by default.

Example:

```
a = A()
def f(self, x, y):
    self.z = x + y
AddMethod(f, A, "add")
a.add(2, 4)
print(a.z)
AddMethod(lambda self, i: self.l[i], a, "listIndex")
print(a.listIndex(5))
```

RenameFunction(*function*, *name*)

Returns a function identical to the specified function, but with the specified name.

MD5signature(*s*)**MD5filesignature**(*fname*, *chunksize*=65536)

MD5collect(*signatures*)

Collects a list of signatures into an aggregate signature.

signatures - a list of signatures returns - the aggregate signature

silent__intern(*x*)

Perform sys.intern() on the passed argument and return the result. If the input is ineligible (e.g. a unicode string) the original argument is returned and no exception is thrown.

to__bytes(*s*)

to__str(*s*)

cmp(*a*, *b*)

Define cmp because it's no longer available in python3 Works under python 2 as well


36.2 Variables

Name	Description
PY3	Value: False
DictTypes	Value: dict, UserDict
ListTypes	Value: (<type 'list'>, <class 'UserList.UserList'>)
SequenceTypes	Value: (<type 'list'>, <type 'tuple'>, <class 'UserList.UserList'>)
StringTypes	Value: (<type 'str'>, <type 'unicode'>, <class 'UserString.UserS...>)
BaseStringTypes	Value: (<type 'str'>, <type 'unicode'>)
d	Value: {}
can_read_reg	Value: 0
hkey_mod	Value: win32con
RegEnumKey	Value: win32api.RegEnumKey
RegEnumValue	Value: win32api.RegEnumValue
RegQueryValueEx	Value: win32api.RegQueryValueEx

continued on next page

Name	Description
HKEY_CLASSES_ROOT	Value: None
HKEY_LOCAL_MACHINE	Value: None
HKEY_CURRENT_USER	Value: None
HKEY_USERS	Value: None
display	Value: DisplayEngine()
md5	Value: True
__package__	Value: 'SCons'

36.3 Class NodeList



This class is almost exactly like a regular list of Nodes (actually it can hold any object), with one important difference. If you try to get an attribute from this list, it will return that attribute from every item in the list. For example:

```
>>> someList = NodeList([ 'foo', 'bar' ])
>>> someList.strip()
['foo', 'bar']
```

36.3.1 Methods`__nonzero__(self)``__bool__(self)``__str__(self)``str(x)` Overrides: `object.__str__` `exitit`(inherited documentation)`__iter__(self)`Overrides: `_abcoll.Iterable.__iter__``__call__(self, *args, **kwargs)``__getattr__(self, name)``__getitem__(self, index)`

This comes for free on py2, but py3 slices of NodeList are returning a list breaking slicing nodelist and referring to properties and methods on contained object Overrides: `_abcoll.Sequence.__getitem__`

Inherited from UserList.UserList

`__add__()`, `__cmp__()`, `__contains__()`, `__delitem__()`, `__delslice__()`,
`__eq__()`, `__ge__()`, `__getslice__()`, `__gt__()`, `__iadd__()`, `__imul__()`,
`__init__()`, `__le__()`, `__len__()`, `__lt__()`, `__mul__()`, `__ne__()`, `__radd__()`,
`__repr__()`, `__rmul__()`, `__setitem__()`, `__setslice__()`, `append()`, `count()`,
`extend()`, `index()`, `insert()`, `pop()`, `remove()`, `reverse()`, `sort()`

Inherited from _abcoll.Sequence`__reversed__()`***Inherited from _abcoll.Sized***`__subclasshook__()`***Inherited from object***

`__delattr__()`, `__format__()`, `__getattr__()`, `__getattribute__()`, `__new__()`, `__reduce__()`,
`__reduce_ex__()`, `__setattr__()`, `__sizeof__()`

36.3.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

36.3.3 Class Variables

Name	Description
<i>Inherited from UserList.UserList</i>	
__abstractmethods__, __hash__	

36.4 Class DisplayEngine**36.4.1 Methods**

```
__call__(self, text, append_newline=1)
```

```
set_mode(self, mode)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __init__(),
__new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(),
__sizeof__(), __str__(), __subclasshook__()
```

36.4.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

36.4.3 Class Variables*continued on next page*

Name	Description
print_it	Value: True

36.5 Class Proxy

object —
SCons.Util.Proxy

Known Subclasses: SCons.Builder.CompositeBuilder, SCons.Node.FS.EntryProxy

A simple generic Proxy class, forwarding all calls to subject. So, for the benefit of the python newbie, what does this really mean? Well, it means that you can take an object, let's call it 'objA', and wrap it in this Proxy class, with a statement like this

```
proxyObj = Proxy(objA),
```

Then, if in the future, you do something like this

```
x = proxyObj.var1,
```

since Proxy does not have a 'var1' attribute (but presumably objA does), the request actually is equivalent to saying

```
x = objA.var1
```

Inherit from this class to create a Proxy.

Note that, with new-style classes, this does *not* work transparently for Proxy subclasses that use special `.__*__()` method names, because those names are now bound to the class, not the individual instances. You now need to know in advance which `.__*__()` method names you want to pass on to the underlying Proxy object, and specifically delegate their calls like this:

```
class Foo(Proxy): __str__ = Delegate('__str__')
```

36.5.1 Methods

<code>__init__(self, subject)</code>
Wrap an object as a Proxy object Overrides: object.__init__

<code>__getattr__(self, name)</code>
Retrieve an attribute from the wrapped object. If the named attribute doesn't exist, <code>AttributeError</code> is raised

<code>get(self)</code>
Retrieve the entire wrapped object

<code>__eq__(self, other)</code>

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

36.5.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

36.6 Class Delegate

object —
SCons.Util.Delegate

A Python Descriptor class that delegates attribute fetches to an underlying wrapped subject of a Proxy. Typical use:

```
class Foo(Proxy): __str__ = Delegate('__str__')
```

36.6.1 Methods

`__init__(self, attribute)`

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` `exitit`(inherited documentation)

`__get__(self, obj, cls)`


Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

36.6.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

36.7 Class `__NoError`



36.7.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException


`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`,
`__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

36.7.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

36.8 Class PlainWindowsError**36.8.1 Methods*****Inherited from exceptions.OSError***

`__init__()`, `__new__()`

Inherited from exceptions.EnvironmentError

`__reduce__()`, `__str__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__repr__()`,
`__setattr__()`, `__setstate__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

36.8.2 Properties

Name	Description
<i>Inherited from exceptions.EnvironmentError</i>	errno, filename, strerror
<i>Inherited from exceptions.BaseException</i>	args, message
<i>Inherited from object</i>	<code>__class__</code>

36.9 Class PlainWindowsError



36.9.1 Methods

Inherited from exceptions.OSError

`__init__()`, `__new__()`

Inherited from exceptions.EnvironmentError

`__reduce__()`, `__str__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__repr__()`,
`__setattr__()`, `__setstate__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

36.9.2 Properties

Name	Description
<i>Inherited from exceptions.EnvironmentError</i> <code>errno</code> , <code>filename</code> , <code>strerror</code>	
<i>Inherited from exceptions.BaseException</i> <code>args</code> , <code>message</code>	
<i>Inherited from object</i> <code>__class__</code>	

36.10 Class CLVar



A class for command-line construction variables.

This is a list that uses `Split()` to split an initial string along white-space arguments, and similarly to split any strings that get added. This allows us to Do the Right Thing with `Append()` and `Prepend()` (as well as straight Python `foo = env['VAR'] + 'arg1 arg2'`) regardless of whether a user adds a list or a string to a command-line construction variable.

36.10.1 Methods

`__init__(self, seq=[])`

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature Overrides:
`object.__init__` `exitit`(inherited documentation)

`__add__(self, other)`

Overrides: `UserList.UserList.__add__`

`__radd__(self, other)`

Overrides: `UserList.UserList.__radd__`

`__coerce__(self, other)`

`__str__(self)`

`str(x)` Overrides: `object.__str__` `exitit`(inherited documentation)

Inherited from UserList.UserList

`__cmp__()`, `__contains__()`, `__delitem__()`, `__delslice__()`, `__eq__()`, `__ge__()`,
`__getitem__()`, `__getslice__()`, `__gt__()`, `__iadd__()`, `__imul__()`, `__le__()`,
`__len__()`, `__lt__()`, `__mul__()`, `__ne__()`, `__repr__()`, `__rmul__()`, `__setitem__()`,
`__setslice__()`, `append()`, `count()`, `extend()`, `index()`, `insert()`, `pop()`, `remove()`,
`reverse()`, `sort()`

Inherited from __abcoll.Sequence

`__iter__()`, `__reversed__()`

Inherited from __abcoll.Sized

`__subclasshook__()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__new__()`, `__reduce__()`,
`__reduce_ex__()`, `__setattr__()`, `__sizeof__()`

36.10.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

36.10.3 Class Variables

Name	Description
<i>Inherited from UserList.UserList</i>	
__abstractmethods__, __hash__	

36.11 Class OrderedDict



Known Subclasses: SCons.Util.Selector

36.11.1 Methods

__init__ (<i>self</i> , <i>dict</i> =None) Overrides: UserDict.UserDict.__init__
__delitem__ (<i>self</i> , <i>key</i>) Overrides: UserDict.UserDict.__delitem__
__setitem__ (<i>self</i> , <i>key</i> , <i>item</i>) Overrides: UserDict.UserDict.__setitem__
clear (<i>self</i>) Overrides: UserDict.UserDict.clear
copy (<i>self</i>) Overrides: UserDict.UserDict.copy
items (<i>self</i>) Overrides: UserDict.UserDict.items
keys (<i>self</i>) Overrides: UserDict.UserDict.keys

popitem(*self*)

Overrides: UserDict.UserDict.popitem

setdefault(*self, key, failobj=None*)

Overrides: UserDict.UserDict.setdefault

update(*self, dict*)

Overrides: UserDict.UserDict.update

values(*self*)

Overrides: UserDict.UserDict.values

Inherited from UserDict.UserDict

`__cmp__()`, `__contains__()`, `__getitem__()`, `__len__()`, `__repr__()`, `fromkeys()`, `get()`, `has_key()`, `iteritems()`, `iterkeys()`, `itervalues()`, `pop()`

36.11.2 Class Variables

Name	Description
<i>Inherited from UserDict.UserDict</i>	
<code>__hash__</code>	

36.12 Class Selector

UserDict.UserDict

SCons.Util.OrderedDict

SCons.Util.Selector

Known Subclasses: SCons.Builder.CallableSelector, SCons.Builder.DictCmdGenerator, SCons.Builder.DictEmitter

A callable ordered dictionary that maps file suffixes to dictionary values. We preserve the order in which items are added so that `get_suffix()` calls always return the first suffix added.

36.12.1 Methods

__call__(*self, env, source, ext=None*)

Inherited from SCons.Util.OrderedDict(Section 36.11)

`__delitem__()`, `__init__()`, `__setitem__()`, `clear()`, `copy()`, `items()`, `keys()`,
`popitem()`, `setdefault()`, `update()`, `values()`

Inherited from UserDict.UserDict

`__cmp__()`, `__contains__()`, `__getitem__()`, `__len__()`, `__repr__()`, `fromkeys()`,
`get()`, `has_key()`, `iteritems()`, `iterkeys()`, `itervalues()`, `pop()`

36.12.2 Class Variables

Name	Description
<i>Inherited from UserDict.UserDict</i>	
<code>__hash__</code>	

36.13 Class LogicalLines

object —
SCons.Util.LogicalLines

Wrapper class for the `logical_lines` method.

Allows us to read all "logical" lines at once from a given file object.

36.13.1 Methods

<code>__init__(self, fileobj)</code>
x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature Overrides: object. <code>__init__</code> <code>exitit</code> (inherited documentation)
<code>readlines(self)</code>


Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

36.13.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

36.14 Class **UniqueList**



36.14.1 Methods

__init__(*self*, *seq*=[])

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides: object.**__init__** extit(inherited documentation)

__lt__(*self*, *other*)

Overrides: UserList.UserList.**__lt__**

__le__(*self*, *other*)

Overrides: UserList.UserList.**__le__**

__eq__(*self*, *other*)

Overrides: `UserList.UserList.__eq__`

__ne__(*self*, *other*)

Overrides: `UserList.UserList.__ne__`

__gt__(*self*, *other*)

Overrides: `UserList.UserList.__gt__`

__ge__(*self*, *other*)

Overrides: `UserList.UserList.__ge__`

__cmp__(*self*, *other*)

Overrides: `UserList.UserList.__cmp__`

__len__(*self*)

Overrides: `_abcoll.Sized.__len__`

__getitem__(*self*, *i*)

Overrides: `_abcoll.Sequence.__getitem__`

__setitem__(*self*, *i*, *item*)

Overrides: `_abcoll.MutableSequence.__setitem__`

__getslice__(*self*, *i*, *j*)

Overrides: `UserList.UserList.__getslice__`

__setslice__(*self*, *i*, *j*, *other*)

Overrides: `UserList.UserList.__setslice__`

__add__(*self*, *other*)

Overrides: `UserList.UserList.__add__`

__radd__(*self*, *other*)

Overrides: `UserList.UserList.__radd__`

__iadd__(*self*, *other*)

Overrides: `_abcoll.MutableSequence.__iadd__`

__mul__(*self*, *other*)

Overrides: `UserList.UserList.__mul__`

__rmul__(*self*, *other*)

Overrides: `UserList.UserList.__rmul__`

__imul__(*self*, *other*)

Overrides: `UserList.UserList.__imul__`

append(*self*, *item*)

append object to the end of the sequence Overrides:
`_abcoll.MutableSequence.append` `exitit`(inherited documentation)

insert(*self*, *i*)

insert object before index Overrides: `_abcoll.MutableSequence.insert`
`exitit`(inherited documentation)

count(*self*, *item*)

return number of occurrences of value **Return Value**
integer

Overrides: `_abcoll.Sequence.count` `exitit`(inherited documentation)

index(*self*, *item*)

return first index of value. Raises `ValueError` if the value is not present.
Return Value
integer

Overrides: `_abcoll.Sequence.index` `exitit`(inherited documentation)

reverse(*self*)

reverse *IN PLACE* Overrides: `_abcoll.MutableSequence.reverse`
`exitit`(inherited documentation)

```
sort(self, *args, **kws)
```

Overrides: UserList.UserList.sort

```
extend(self, other)
```

extend sequence by appending elements from the iterable Overrides:
__abcoll.MutableSequence.extend extit(inherited documentation)

Inherited from UserList.UserList

__contains__(), __delitem__(), __delslice__(), __repr__(), pop(), remove()

Inherited from __abcoll.Sequence

__iter__(), __reversed__()

Inherited from __abcoll.Sized

__subclasshook__()

Inherited from object

__delattr__(), __format__(), __getattr__(), __new__(), __reduce__(),
__reduce_ex__(), __setattr__(), __sizeof__(), __str__()

36.14.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

36.14.3 Class Variables

Name	Description
<i>Inherited from UserList.UserList</i>	
__abstractmethods__, __hash__	

36.15 Class Unbuffered

```
object └─ SCons.Util.Unbuffered
```

A proxy class that wraps a file object, flushing after every write, and delegating everything

else to the wrapped object.

36.15.1 Methods

```
__init__(self, file)
```

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides:
object.**__init__** exitit(inherited documentation)

```
write(self, arg)
```

```
__getattr__(self, attr)
```

Inherited from object

```
__delattr__(), __format__(), __getattribute__(), __hash__(), __new__(),  
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),  
__str__(), __subclasshook__()
```

36.15.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

36.16 Class Null

```
object └─ SCons.Util.Null
```

Known Subclasses: SCons.Executor.NullEnvironment, SCons.Util.NullSeq

Null objects always and reliably "do nothing."

36.16.1 Methods

__new__(*cls, *args, **kwargs*)

Return Value

a new object with type S, a subtype of T

Overrides: object.__new__ extit(inherited documentation)

__init__(*self, *args, **kwargs*)

x.__init__(...) initializes x; see help(type(x)) for signature Overrides:
object.__init__ extit(inherited documentation)

__call__(*self, *args, **kwargs*)

__repr__(*self*)

repr(x) Overrides: object.__repr__ extit(inherited documentation)

__nonzero__(*self*)

__bool__(*self*)

__getattr__(*self, name*)

__setattr__(*self, name, value*)

x.__setattr__('name', value) <==> x.name = value Overrides:
object.__setattr__ extit(inherited documentation)

__delattr__(*self, name*)

x.__delattr__('name') <==> del x.name Overrides: object.__delattr__
extit(inherited documentation)


Inherited from object

__format__(), **__getattribute__**(), **__hash__**(), **__reduce__**(), **__reduce_ex__**(),
__sizeof__(), **__str__**(), **__subclasshook__**()

36.16.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

36.17 Class *NullSeq*



Known Subclasses: *SCons.Subst.NullNodeList*

36.17.1 Methods

__len__(<i>self</i>)
__iter__(<i>self</i>)
__getitem__(<i>self</i> , <i>i</i>)
__delitem__(<i>self</i> , <i>i</i>)
__setitem__(<i>self</i> , <i>i</i> , <i>v</i>)

Inherited from SCons.Util.Null(Section 36.16)

__bool__(), __call__(), __delattr__(), __getattr__(), __init__(), __new__(),
__nonzero__(), __repr__(), __setattr__()

Inherited from object

__format__(), __getattribute__(), __hash__(), __reduce__(), __reduce_ex__(),
__sizeof__(), __str__(), __subclasshook__()

36.17.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

37 Package SCons.Variables

engine.SCons.Variables

This file defines the Variables class that is used to add user-friendly customizable variables to an SCons build.

37.1 Modules

- **BoolVariable** (*Section ??, p. ??*)
- **BoolVariable'**: engine.SCons.Variables.BoolVariable
(*Section 38, p. 343*)
- **EnumVariable** (*Section ??, p. ??*)
- **EnumVariable'**: engine.SCons.Variables.EnumVariable
(*Section 39, p. 344*)
- **ListVariable** (*Section ??, p. ??*)
- **ListVariable'**: engine.SCons.Variables.ListVariable
(*Section 40, p. 345*)
- **PackageVariable** (*Section ??, p. ??*)
- **PackageVariable'**: engine.SCons.Variables.PackageVariable
(*Section 41, p. 346*)
- **PathVariable** (*Section ??, p. ??*)
- **PathVariable'**: SCons.Variables.PathVariable
(*Section 42, p. 347*)

37.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Variables/__init__.py 74b2c53bc42290e91...
__package__	Value: 'SCons.Variables'

37.3 Class Variables

object └─ SCons.Variables.Variables

37.3.1 Methods

__init__(*self*, *files*=None, *args*=None, *is_global*=1)

files - [optional] List of option configuration files to load

(backward compatibility) If a single string is passed it is automatically placed in a file list

Overrides: object.__init__

keys(*self*)

Returns the keywords for the options

Add(*self*, *key*, *help*='', *default*=None, *validator*=None, *converter*=None, ***kw*)

Add an option.

@param key: the name of the variable, or a list or tuple of arguments @param help: optional help text for the options @param default: optional default value @param validator: optional function that is called to validate the option's value @type validator: Called with (key, value, environment) @param converter: optional function that is called to convert the option's value before putting it in the environment.

AddVariables(*self*, **optlist*)

Add a list of options.

Each list element is a tuple/list of arguments to be passed on to the underlying method for adding options.

Example:

```
opt.AddVariables(  
    ('debug', '', 0),  
    ('CC', 'The C compiler'),  
    ('VALIDATE', 'An option for testing validation', 'notset',  
     validator, None),  
)
```

Update(*self*, *env*, *args*=None)

Update an environment with the option variables.

env - the environment to update.

UnknownVariables(*self*)

Returns any options in the specified arguments lists that were not known, declared options in this object.

Save(*self*, *filename*, *env*)

Saves all the options in the given file. This file can then be used to load the options next run. This can be used to create an option cache file.

filename - Name of the file to save into *env* - the environment get the option values from

GenerateHelpText(*self*, *env*, *sort*=None)

Generate the help text for the options.

env - an environment that is used to get the current values of the options.

cmp - Either a function as follows: The specific sort function should take two arguments or a boolean to indicate if it should be sorted.

FormatVariableHelpText(*self*, *env*, *key*, *help*, *default*, *actual*, *aliases*=[])

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

37.3.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

37.3.3 Class Variables

Name	Description
instance	Holds all the options, updates the environment with the variables, and renders the help text. Value: None
format	Value: '\n%s: %s\n default: %s\n actual: %s\n'
format__	Value: '\n%s: %s\n default: %s\n actual: %s\n aliases: ...'

38 Module *SCons.Variables.BoolVariable*

`engine.SCons.Variables.BoolVariable`

This file defines the option type for SCons implementing true/false values.

Usage example:

```
opts = Variables()
opts.Add(BoolVariable('embedded', 'build for an embedded system', 0))
...
if env['embedded'] == 1:
...
```

38.1 Functions

<code>BoolVariable</code> <i>(key, help, default)</i>
The input parameters describe a boolean option, thus they are returned with the correct converter and validator appended. The 'help' text will be appended by '(yes no)' to show the valid values. The result is usable for input to <code>opts.Add()</code> .

39 Module *SCons.Variables.EnumVariable*

engine.SCons.Variables.EnumVariable

This file defines the option type for SCons allowing only specified input-values.

Usage example:

```
opts = Variables()
opts.Add(EnumVariable('debug', 'debug output and symbols', 'no',
                      allowed_values=('yes', 'no', 'full'),
                      map={}, ignorecase=2))
...
if env['debug'] == 'full':
...
```

39.1 Functions

EnumVariable(*key, help, default, allowed_values, map={}, ignorecase=0*)

The input parameters describe an option with only certain values allowed. They are returned with an appropriate converter and validator appended. The result is usable for input to Variables.Add().

'key' and 'default' are the values to be passed on to Variables.Add().

'help' will be appended by the allowed values automatically

'allowed_values' is a list of strings, which are allowed as values for this option.

The 'map'-dictionary may be used for converting the input value into canonical values (e.g. for aliases).

'ignorecase' defines the behaviour of the validator:

If ignorecase == 0, the validator/converter are case-sensitive. If ignorecase == 1, the validator/converter are case-insensitive. If ignorecase == 2, the validator/converter is case-insensitive and the converted value will always be lower-case.

The 'validator' tests whether the value is in the list of allowed values. The 'converter' converts input values according to the given 'map'-dictionary (unmapped input values are returned unchanged).

40 Module *SCons.Variables.ListVariable*

`engine.SCons.Variables.ListVariable`

This file defines the option type for SCons implementing 'lists'.

A 'list' option may either be 'all', 'none' or a list of names separated by comma. After the option has been processed, the option value holds either the named list elements, all list elements or no list elements at all.

Usage example:

```
list_of_libs = Split('x11 gl qt ical')

opts = Variables()
opts.Add(ListVariable('shared',
                      'libraries to build as shared libraries',
                      'all',
                      elems = list_of_libs))

...
for lib in list_of_libs:
    if lib in env['shared']:
        env.SharedObject(...)
    else:
        env.Object(...)
```

40.1 Functions

ListVariable(*key, help, default, names, map={}*)

The input parameters describe a 'package list' option, thus they are returned with the correct converter and validator appended. The result is usable for input to `opts.Add()` .

A 'package list' option may either be 'all', 'none' or a list of package names (separated by space).

41 Module *SCons.Variables.PackageVariable*

`engine.SCons.Variables.PackageVariable`

This file defines the option type for SCons implementing 'package activation'.

To be used whenever a 'package' may be enabled/disabled and the package path may be specified.

Usage example:

Examples: `x11=no` (disables X11 support) `x11=yes` (will search for the package installation dir) `x11=/usr/local/X11` (will check this path for existence)

To replace `autoconf`'s `--with-xxx=yyy`

```
opts = Variables()
opts.Add(PackageVariable('x11',
                        'use X11 installed here (yes = search some places',
                        'yes'))
...
if env['x11'] == True:
    dir = ... search X11 in some standard places ...
    env['x11'] = dir
if env['x11']:
    ... build with x11 ...
```

41.1 Functions

`PackageVariable(key, help, default, searchfunc=None)`

The input parameters describe a 'package list' option, thus they are returned with the correct converter and validator appended. The result is usable for input to `opts.Add()` .

A 'package list' option may either be 'all', 'none' or a list of package names (separated by space).

42 Module `SCons.Variables.PathVariable`

`SCons.Variables.PathVariable`

This file defines an option type for SCons implementing path settings.

To be used whenever a user-specified path override should be allowed.

Arguments to `PathVariable` are: `option-name` = name of this option on the command line (e.g. "prefix") `option-help` = help string for option `option-dflt` = default value for this option `validator` = [optional] validator for option value. Predefined validators are:

`PathAccept` -- accepts any path setting; no validation `PathIsDir` -- path must be an existing directory `PathIsDirCreate` -- path must be a dir; will create `PathIsFile` -- path must be a file `PathExists` -- path must exist (any type) [default]

The validator is a function that is called and which should return `True` or `False` to indicate if the path is valid. The arguments to the validator function are: (key, val, env). The key is the name of the option, the val is the path specified for the option, and the env is the env to which the Options have been added.

Usage example:

Examples:

```
prefix=/usr/local
```

```
opts = Variables()
```

```
opts = Variables()
opts.Add(PathVariable('qtdir',
                      'where the root of Qt is installed',
                      qtdir, PathIsDir))
opts.Add(PathVariable('qt_includes',
                      'where the Qt includes are installed',
                      '$qtdir/includes', PathIsDirCreate))
opts.Add(PathVariable('qt_libraries',
                      'where the Qt library is installed',
                      '$qtdir/lib'))
```

42.1 Variables

Name	Description
<code>PathVariable</code>	Value: <code>SCons.Variables.PathVariable</code>

43 Module **SCons.Warnings**

SCons.Warnings

This file implements the warnings framework for SCons.

43.1 Functions

suppressWarningClass (<i>clazz</i>)
Suppresses all warnings that are of type <i>clazz</i> or derived from <i>clazz</i> .

enableWarningClass (<i>clazz</i>)
Enables all warnings that are of type <i>clazz</i> or derived from <i>clazz</i> .

warningAsException (<i>flag</i> =1)
Turn warnings into exceptions. Returns the old value of the flag.

warn (<i>clazz</i> , * <i>args</i>)
--

process_warn_strings(*arguments*)

Process string specifications of enabling/disabling warnings, as passed to the --warn option or the SetOption('warn') function.


An argument to this option should be of the form <warning-class> or no-<warning-class>. The warning class is munged in order to get an actual class name from the classes above, which we need to pass to the {enable,disable}WarningClass() functions. The supplied <warning-class> is split on hyphens, each element is capitalized, then smushed back together. Then the string "Warning" is appended to get the class name.

For example, 'deprecated' will enable the DeprecatedWarning class. 'no-dependency' will disable the DependencyWarning class.

As a special case, --warn=all and --warn=no-all will enable or disable (respectively) the base Warning class of all warnings.

43.2 Variables

Name	Description
__revision__	Value: 'src/engine/SCons/Warnings.py 74b2c53bc42290e911b334a6b44...
__package__	Value: 'SCons'

43.3 Class Warning

Known Subclasses: SCons.SConf.SConfWarning, SCons.Warnings.WarningOnByDefault, SCons.Warnings.CacheWriteErrorWarning, SCons.Warnings.DependencyWarning, SCons.Warnings.DeprecatedWarning, SCons.Warnings.FutureDeprecatedWarning, SCons.Warnings.TargetNotBuiltWarning, SCons.Warnings.VI

43.3.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

```
__delattr__(), __getattr__(), __getitem__(), __getslice__(), __reduce__(), __repr__(), __setattr__(), __setstate__(), __str__(), __unicode__()
```


Inherited from object

```
__format__(), __hash__(), __reduce_ex__(), __sizeof__(), __subclasshook__()
```

43.3.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i> args, message	
<i>Inherited from object</i> class	

43.4 Class WarningOnByDefault



Known Subclasses: SCons.Warnings.CacheVersionWarning, SCons.Warnings.CorruptSConsignWarning, SCons.Warnings.DevelopmentVersionWarning, SCons.Warnings.DuplicateEnvironmentWarning, SCons.Warnings.LinkWarning, SCons.Warnings.FutureReservedVariableWarning, SCons.Warnings.Mislead SCons.Warnings.MissingSConscriptWarning, SCons.Warnings.NoMD5ModuleWarning, SCons.Warnings.No SCons.Warnings.NoObjectCountWarning, SCons.Warnings.NoParallelSupportWarning, SCons.Warnings.F SCons.Warnings.StackSizeWarning, SCons.Warnings.VisualCMissingWarning, SCons.Warnings.VisualVers

43.4.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.4.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

43.5 Class `TargetNotBuiltWarning`



43.5.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from exceptions.BaseException


`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.5.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

43.6 Class CacheVersionWarning**43.6.1 Methods*****Inherited from exceptions.Exception***

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__re-`

`duce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.6.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

43.7 Class `CacheWriteErrorWarning`



43.7.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.7.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

43.8 Class `CorruptSConsignWarning`



43.8.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.8.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
__class__	

43.9 Class DependencyWarning



43.9.1 Methods

Inherited from exceptions.Exception

__init__(), __new__()

Inherited from exceptions.BaseException

__delattr__(), __getattr__(), __getitem__(), __getslice__(), __reduce__(), __repr__(), __setattr__(), __setstate__(), __str__(), __unicode__()


Inherited from object

__format__(), __hash__(), __reduce_ex__(), __sizeof__(), __subclasshook__()

43.9.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
__class__	

43.10 Class DevelopmentVersionWarning



43.10.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.10.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.11 Class `DuplicateEnvironmentWarning`



43.11.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.11.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
args, message	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.12 Class `FutureReservedVariableWarning`



43.12.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.12.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
args, message	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.13 Class LinkWarning



Known Subclasses: SCons.Warnings.FortranCxxMixWarning

43.13.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.13.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.14 Class `MisleadingKeywordsWarning`



43.14.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.14.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
args, message	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.15 Class `MissingSConscriptWarning`



43.15.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.15.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
args, message	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.16 Class NoMD5ModuleWarning



43.16.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.16.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.17 Class NoMetaclassSupportWarning



43.17.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.17.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
<code>__class__</code>	

43.18 Class `NoObjectCountWarning`



43.18.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.18.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.19 Class NoParallelSupportWarning



43.19.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.19.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.20 Class ReservedVariableWarning



43.20.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException


`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.20.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
<code>__class__</code>	

43.21 Class StackSizeWarning**43.21.1 Methods*****Inherited from exceptions.Exception***

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.21.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
<code>__class__</code>	

43.22 Class `VisualCMissingWarning`



43.22.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.22.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
	args, message
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.23 Class `VisualVersionMismatch`



43.23.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.23.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.24 Class VisualStudioMissingWarning



43.24.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.24.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

43.25 Class FortranCxxMixWarning



43.25.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.25.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.26 Class FutureDeprecatedWarning



Known Subclasses: SCons.Warnings.DeprecatedSourceCodeWarning

43.26.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException


`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.26.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
	<code>__class__</code>

43.27 Class *DeprecatedWarning*

Known Subclasses: `SCons.Warnings.DeprecatedBuildDirWarning`, `SCons.Warnings.MandatoryDeprecatedWarning`, `SCons.Warnings.PythonVersionWarning`, `SCons.Warnings.TaskmasterNeedsExecuteWarning`

43.27.1 Methods***Inherited from exceptions.Exception***

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.27.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

43.28 Class MandatoryDeprecatedWarning



Known Subclasses: `SCons.Warnings.DeprecatedBuilderKeywordsWarning`, `SCons.Warnings.DeprecatedSCons.Warnings.DeprecatedDebugOptionsWarning`, `SCons.Warnings.DeprecatedOptionsWarning`, `SCons.Warnings.DeprecatedSigModuleWarning`, `SCons.Warnings.DeprecatedSourceSignaturesWarning`, `SCons.Warnings.DeprecatedTargetSignaturesWarning`

43.28.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.28.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.29 Class `PythonVersionWarning`



43.29.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.29.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
	args, message
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.30 Class `DeprecatedSourceCodeWarning`



43.30.1 Methods

Inherited from `exceptions.Exception`

`__init__()`, `__new__()`

Inherited from `exceptions.BaseException`


`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from `object`

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.30.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
	args, message
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.31 Class *DeprecatedBuildDirWarning***43.31.1 Methods*****Inherited from exceptions.Exception***

`__init__()`, `__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`


Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.31.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.32 Class TaskmasterNeedsExecuteWarning



43.32.1 Methods

Inherited from exceptions.Exception

`__init__()`, `__new__()`

Inherited from exceptions.BaseException


`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.32.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
<code>__class__</code>	

43.33 Class *DeprecatedCopyWarning***43.33.1 Methods*****Inherited from exceptions.Exception***

`__init__()`, `__new__()`

Inherited from exceptions.BaseException


`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.33.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.34 Class *DeprecatedOptionsWarning***43.34.1 Methods*****Inherited from exceptions.Exception***

`__init__()`, `__new__()`

Inherited from exceptions.BaseException


`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object


`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.34.2 Properties


Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.35 Class `DeprecatedSourceSignaturesWarning`**43.35.1 Methods*****Inherited from `exceptions.Exception`***`__init__()`, `__new__()`***Inherited from `exceptions.BaseException`***`__delattr__()`, `__getattribute__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`***Inherited from `object`***`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`**43.35.2 Properties**

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.36 Class `DeprecatedTargetSignaturesWarning`**43.36.1 Methods***Inherited from `exceptions.Exception`*`__init__()`, `__new__()`*Inherited from `exceptions.BaseException`*`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`*Inherited from `object`*`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`**43.36.2 Properties**

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

43.37 Class *DeprecatedDebugOptionsWarning***43.37.1 Methods*****Inherited from exceptions.Exception***

`__init__()`, `__new__()`

Inherited from exceptions.BaseException


`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.37.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.38 Class *DeprecatedSigModuleWarning***43.38.1 Methods*****Inherited from exceptions.Exception***

`__init__()`, `__new__()`

Inherited from exceptions.BaseException


`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

43.38.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
	args, message
<i>Inherited from object</i>	
<code>__class__</code>	

43.39 Class `DeprecatedBuilderKeywordsWarning`**43.39.1 Methods*****Inherited from `exceptions.Exception`***`__init__()`, `__new__()`***Inherited from `exceptions.BaseException`***`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__str__()`, `__unicode__()`***Inherited from `object`***`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`**43.39.2 Properties**

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

44 Module SCons.cpp

SCons C Pre-Processor module

44.1 Functions

CPP_to_Python_Ops_Sub (<i>m</i>)

CPP_to_Python (<i>s</i>)

Converts a C pre-processor expression into an equivalent Python expression that can be evaluated.

44.2 Variables

Name	Description
<code>__doc__</code>	Value: ...
<code>cpp_lines_dict</code>	Value: {'define': '\\s+([_A-Za-z][_A-Za-z0-9_]*)\\(([^)]*\\))'?...
<code>Table</code>	Value: {'define': re.compile(r'\\s+([_A-Za-z][_A-Za-z0-9_]*)\\(([^...
<code>e</code>	Value: '^\\s*#\\s*(elif undef include_next endif else include if.
<code>CPP_Expression</code>	Value: re.compile(r'(?m)^\\s*#\\s*(elif undef include_next endif e.
<code>CPP_to_Python_Ops_Dict</code>	Value: {'\\r': ' ', '!': ' not ', '!=': ' != ', '&&': ' and ', ':'...
<code>CPP_to_Python_Ops_Expression</code>	Value: re.compile(r'\\ \\ && != ! \\r :\\ ?')
<code>CPP_to_Python_Eval_List</code>	Value: [[re.compile(r'defined\\s+(\\w+)'), '"\\1" in __dict__'], [...
<code>line_continuations</code>	Value: re.compile(r'\\\\r?\\n')
<code>function_name</code>	Value: re.compile(r'\\S+\\(((\\^\\))*)\\)')
<code>function_arg_separator</code>	Value: re.compile(r',\\s*')
<code>__package__</code>	Value: 'SCons'
<code>x</code>	Value: 'if'

44.3 Class FunctionEvaluator

object —
SCons.cpp.FunctionEvaluator

Handles delayed evaluation of a #define function call.

44.3.1 Methods

__init__ (<i>self, name, args, expansion</i>)
Squirrels away the arguments and expansion value of a #define macro function for later evaluation when we must actually expand a value that uses it. Overrides: object.__init__
__call__ (<i>self, *values</i>)
Evaluates the expansion of a #define macro function called with the specified values.

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

44.3.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

44.4 Class PreProcessor

object —
SCons.cpp.PreProcessor

Known Subclasses: SCons.cpp.DumbPreProcessor, SCons.Scanner.C.SConsCPPScanner

The main workhorse class for handling C pre-processing.

44.4.1 Methods

__call__(*self*, *file*)

Pre-processes a file.

This is the main public entry point.

__init__(*self*, *current*='.', *cpppath*=(), *dict*={}, *all*=0)

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides: object.**__init__** **__exit__**(inherited documentation)

all_include(*self*, *t*)

do_define(*self*, *t*)

Default handling of a `#define` line.

do_elif(*self*, *t*)

Default handling of a `#elif` line.

do_else(*self*, *t*)

Default handling of a `#else` line.

do_endif(*self*, *t*)

Default handling of a `#endif` line.

do_if(*self*, *t*)

Default handling of a `#if` line.

do_ifdef(*self*, *t*)

Default handling of a `#ifdef` line.

do_ifndef(*self*, *t*)

Default handling of a `#ifndef` line.

do_import(*self*, *t*)

Default handling of a `#import` line.

do_include(*self*, *t*)

Default handling of a `#include` line.

do_include_next(*self*, *t*)

Default handling of a `#include` line.

do_nothing(*self*, *t*)

Null method for when we explicitly want the action for a specific preprocessor directive to do nothing.

do_undef(*self*, *t*)

Default handling of a `#undef` line.

eval_expression(*self*, *t*)

Evaluates a C preprocessor expression.

This is done by converting it to a Python equivalent and eval()ing it in the C preprocessor namespace we use to track #define values.

finalize_result(*self*, *fname*)**find_include_file**(*self*, *t*)

Finds the #include file for a given preprocessor tuple.

initialize_result(*self*, *fname*)**process_contents**(*self*, *contents*, *fname*=None)

Pre-processes a file contents.

This is the main internal entry point.

read_file(*self*, *file*)**resolve_include**(*self*, *t*)

Resolve a tuple-ized #include line.

This handles recursive expansion of values without " or <> surrounding the name until an initial " or < is found, to handle

#include FILE

where FILE is a #define somewhere else.

restore(*self*)

Pops the previous dispatch table off the stack and makes it the current one.

save(*self*)

Pushes the current dispatch table on the stack and re-initializes the current dispatch table to the default.

scons_current_file(*self*, *t*)

start_handling_includes(*self*, *t*=None)

Causes the PreProcessor object to start processing `#import`, `#include` and `#include_next` lines.

This method will be called when a `#if`, `#ifdef`, `#ifndef` or `#elif` evaluates True, or when we reach the `#else` in a `#if`, `#ifdef`, `#ifndef` or `#elif` block where a condition already evaluated False.

stop_handling_includes(*self*, *t*=None)

Causes the PreProcessor object to stop processing `#import`, `#include` and `#include_next` lines.

This method will be called when a `#if`, `#ifdef`, `#ifndef` or `#elif` evaluates False, or when we reach the `#else` in a `#if`, `#ifdef`, `#ifndef` or `#elif` block where a condition already evaluated True.

tupleize(*self*, *contents*)

Turns the contents of a file into a list of easily-processed tuples describing the CPP lines in the file.

The first element of each tuple is the line's preprocessor directive (`#if`, `#include`, `#define`, etc., minus the initial `'#'`). The remaining elements are specific to the type of directive, as pulled apart by the regular expression.

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

44.4.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

44.5 Class DumbPreProcessor



A preprocessor that ignores all `#if/#elif/#else/#endif` directives and just reports back *all* of the `#include` files (like the classic SCons scanner did).

This is functionally equivalent to using a regular expression to find all of the `#include` lines, only slower. It exists mainly as an example of how the main PreProcessor class can be sub-classed to tailor its behavior.

44.5.1 Methods

__init__(*self*, **args*, ***kw*)

x.**__init__**(...) initializes x; see help(type(x)) for signature Overrides:
object.**__init__** extit(inherited documentation)

Inherited from SCons.cpp.PreProcessor(Section 44.4)

__call__(), **all_include**(), **do_define**(), **do_elif**(), **do_else**(), **do_endif**(), **do_if**(),
do_ifdef(), **do_ifndef**(), **do_import**(), **do_include**(), **do_include_next**(), **do_nothing**(),
do_undef(), **eval_expression**(), **finalize_result**(), **find_include_file**(), **initialize_result**(),
process_contents(), **read_file**(), **resolve_include**(), **restore**(), **save**(), **scons_current_file**(),
start_handling_includes(), **stop_handling_includes**(), **tupleize**()

Inherited from object

__delattr__(), **__format__**(), **__getattr__**(), **__hash__**(), **__new__**(),
__reduce__(), **__reduce_ex__**(), **__repr__**(), **__setattr__**(), **__sizeof__**(),
__str__(), **__subclasshook__**()

44.5.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

45 Module *SCons.dblite*

45.1 Functions

`corruption_warning(filename)`

`is_string(s)`

`is_bytes(s)`

`unicode(s)`

`open(file, flag=None, mode=438)`

45.2 Variables

Name	Description
<code>keep_all_files</code>	Value: 0
<code>ignore_corrupt_dbfiles</code>	Value: 0
<code>dblite_suffix</code>	Value: <code>' .dblite'</code>
<code>tmp_suffix</code>	Value: <code>' .tmp'</code>
<code>__package__</code>	Value: <code>'SCons'</code>

45.3 Class *dblite*

```

object └─
          SCons.dblite.dblite

```

Squirrel away references to the functions in various modules that we'll use when our `__del__()` method calls our `sync()` method during shutdown. We might get destroyed when Python is in the midst of tearing down the different modules we import in an essentially arbitrary order, and some of the various modules's global attributes may already be wiped out from under us.

See the discussion at: <http://mail.python.org/pipermail/python-bugs-list/2003-March/01687>

45.3.1 Methods

<code>__init__(self, file_base_name, flag, mode)</code>

<code>x.__init__(...)</code> initializes x; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)

<code>close(self)</code>

<code>__del__(self)</code>

<code>sync(self)</code>

<code>__getitem__(self, key)</code>

<code>__setitem__(self, key, value)</code>
--

<code>keys(self)</code>

<code>has_key(self, key)</code>

<code>__contains__(self, key)</code>

<code>iterkeys(self)</code>

<code>__iter__(self)</code>

<code>__len__(self)</code>

Inherited from object

<code>__delattr__()</code> , <code>__format__()</code> , <code>__getattr__()</code> , <code>__hash__()</code> , <code>__new__()</code> , <code>__reduce__()</code> , <code>__reduce_ex__()</code> , <code>__repr__()</code> , <code>__setattr__()</code> , <code>__sizeof__()</code> , <code>__str__()</code> , <code>__subclasshook__()</code>

45.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

46 Module *SCons.exitfuncs*

SCons.exitfuncs

Register functions which are executed when *SCons* exits for any reason.

46.1 Functions

register (<i>func</i> , * <i>targs</i> , ** <i>kargs</i>)
--

register a function to be executed upon normal program termination
--

func - function to be called at exit targs - optional arguments to pass to func

kargs - optional keyword arguments to pass to func
--

46.2 Variables

Name	Description
<code>__revision__</code>	Value: 'src/engine/SCons/exitfuncs.py 74b2c53bc42290e911b334a6b4...
<code>__package__</code>	Value: 'SCons'

Index

- SCons (package), 2–4
 - SCons.Action (module), 5–18
 - SCons.Action.Action (function), 6
 - SCons.Action.ActionBase (class), 6–7
 - SCons.Action.ActionCaller (class), 16–17
 - SCons.Action.ActionFactory (class), 17–18
 - SCons.Action.CommandAction (class), 7–9
 - SCons.Action.CommandGeneratorAction (class), 9–11
 - SCons.Action.default_exitstatfunc (function), 6
 - SCons.Action.FunctionAction (class), 13–14
 - SCons.Action.get_default_ENV (function), 6
 - SCons.Action.LazyAction (class), 11–13
 - SCons.Action.ListAction (class), 14–16
 - SCons.Action.rfile (function), 6
 - SCons.Builder (module), 19–30
 - SCons.Builder.Builder (function), 20
 - SCons.Builder.BuilderBase (class), 26–29
 - SCons.Builder.CallableSelector (class), 22
 - SCons.Builder.CompositeBuilder (class), 29–30
 - SCons.Builder.DictCmdGenerator (class), 20–22
 - SCons.Builder.DictEmitter (class), 22–23
 - SCons.Builder.EmitterProxy (class), 26
 - SCons.Builder.is_a_Builder (function), 20
 - SCons.Builder.ListEmitter (class), 23–25
 - SCons.Builder.match_splitext (function), 20
 - SCons.Builder.OverrideWarner (class), 25–26
 - SCons.CacheDir (module), 31–33
 - SCons.Conftest (module), 34–38
 - SCons.cpp (module), 386–393
 - SCons.dblite (module), 394–395
 - SCons.dblite.corruption_warning (function), 394
 - SCons.dblite.dblite (class), 394–395
 - SCons.dblite.is_bytes (function), 394
 - SCons.dblite.is_string (function), 394
 - SCons.dblite.open (function), 394
 - SCons.dblite.unicode (function), 394
 - SCons.Debug (module), 39–40
 - SCons.Debug.caller_stack (function), 39
 - SCons.Debug.caller_trace (function), 39
 - SCons.Debug.countLoggedInstances (function), 39
 - SCons.Debug.dump_caller_counts (function), 39
 - SCons.Debug.dumpLoggedInstances (function), 39
 - SCons.Debug.fetchLoggedInstances (function), 39
 - SCons.Debug.func_shorten (function), 39
 - SCons.Debug.listLoggedInstances (function), 39
 - SCons.Debug.logInstanceCreation (function), 39
 - SCons.Debug.memory (function), 39
 - SCons.Debug.string_to_classes (function), 39
 - SCons.Debug.Trace (function), 39
 - SCons.Defaults (module), 41–45
 - SCons.Environment (module), 46–75
 - SCons.Environment.alias_builder (function), 46
 - SCons.Environment.apply_tools (function), 46
 - SCons.Environment.Base (class), 54–63, 66–75
 - SCons.Environment.BuilderDict (class), 50–51

- SCons.Environment.BuilderWrapper (*class*), 88
 - 48–50
- SCons.Environment.copy_non_reserved_keywords (*function*), 46
- SCons.Environment.default_copy_from_cache (*function*), 46
- SCons.Environment.default_decide_source (*function*), 46
- SCons.Environment.default_decide_target (*function*), 46
- SCons.Environment.is_valid_construction_value (*function*), 46
- SCons.Environment.MethodWrapper (*class*), 47–48
- SCons.Environment.NoSubstitutionProxy (*function*), 46
- SCons.Environment.OverrideEnvironment (*class*), 63–66
- SCons.Environment.SubstitutionEnvironment (*class*), 51–54
- SCons.Errors (*module*), 76–83
- SCons.Executor (*module*), 84–95
 - SCons.Executor.AddBatchExecutor (*function*), 84
 - SCons.Executor.Batch (*class*), 85
 - SCons.Executor.execute_action_list (*function*), 84
 - SCons.Executor.execute_actions_str (*function*), 84
 - SCons.Executor.execute_nothing (*function*), 84
 - SCons.Executor.execute_null_str (*function*), 84
 - SCons.Executor.Executor (*class*), 88–92
 - SCons.Executor.get_NullEnvironment (*function*), 84
 - SCons.Executor.GetBatchExecutor (*function*), 84
 - SCons.Executor.Null (*class*), 93–95
 - SCons.Executor.NullEnvironment (*class*), 92–93
 - SCons.Executor.rfile (*function*), 84
 - SCons.Executor.TSList (*class*), 85–87
 - SCons.Executor.TSObject (*class*), 87–
- SCons.exitfuncs (*module*), 396
 - SCons.exitfuncs.register (*function*), 396
- SCons.Job (*module*), 96–103
 - SCons.Job.InterruptState (*class*), 96–97
 - SCons.Job.Jobs (*class*), 97–98
 - SCons.Job.Parallel (*class*), 102–103
 - SCons.Job.Serial (*class*), 98–99
 - SCons.Job.ThreadPool (*class*), 101–102
 - SCons.Job.Worker (*class*), 99–101
- SCons.Memoize (*module*), 104–109
 - SCons.Memoize.CountDict (*class*), 108–109
 - SCons.Memoize.CountDictCall (*function*), 105
 - SCons.Memoize.Counter (*class*), 106–107
 - SCons.Memoize.CountMethodCall (*function*), 105
 - SCons.Memoize.CountValue (*class*), 107–108
 - SCons.Memoize.Dump (*function*), 105
 - SCons.Memoize.EnableMemoization (*function*), 105
- SCons.Node (*package*), 110–132
 - SCons.Node.Alias (*module*), 133–138
 - SCons.Node.FS (*module*), 139–185
 - SCons.Node.Python (*module*), 186–191
- SCons.PathList (*module*), 192
 - SCons.PathList.node_conv (*function*), 192
 - SCons.PathList.PathList (*function*), 192
- SCons.Scanner (*module*)
 - SCons.Scanner.Base (*class*), 217–220
 - SCons.Scanner.Classic (*class*), 227–230
 - SCons.Scanner.ClassicCPP (*class*), 230–231
 - SCons.Scanner.Current (*class*), 224–227
 - SCons.Scanner.FindPathDirs (*class*), 217
 - SCons.Scanner.Scanner (*function*), 216
 - SCons.Scanner.Selector (*class*), 220–224
- SCons.Scanner (*package*), 216–231
 - SCons.Scanner.C (*module*), 232–234
 - SCons.Scanner.D (*module*), 235–238
 - SCons.Scanner.Dir (*module*), 239–240

- SCons.Scanner.Fortran (*module*), 241–245
- SCons.Scanner.IDL (*module*), 246
- SCons.Scanner.LaTeX (*module*), 247–253
- SCons.Scanner.Prog (*module*), 254
- SCons.Scanner.RC (*module*), 255
- SCons.Scanner.SWIG (*module*), 256
- SCons.SConf (*module*), 193–208
 - SCons.SConf.CheckCC (*function*), 194
 - SCons.SConf.CheckCHheader (*function*), 194
 - SCons.SConf.CheckContext (*class*), 206–208
 - SCons.SConf.CheckCXX (*function*), 194
 - SCons.SConf.CheckCXXHeader (*function*), 194
 - SCons.SConf.CheckDeclaration (*function*), 194
 - SCons.SConf.CheckFunc (*function*), 193
 - SCons.SConf.CheckHeader (*function*), 194
 - SCons.SConf.CheckLib (*function*), 194
 - SCons.SConf.CheckLibWithHeader (*function*), 194
 - SCons.SConf.CheckProg (*function*), 195
 - SCons.SConf.CheckSHCC (*function*), 194
 - SCons.SConf.CheckSHCXX (*function*), 194
 - SCons.SConf.CheckType (*function*), 193
 - SCons.SConf.CheckTypeSize (*function*), 193
 - SCons.SConf.ConfigureCacheError (*class*), 198–199
 - SCons.SConf.ConfigureDryRunError (*class*), 197–198
 - SCons.SConf.CreateConfigHBuilder (*function*), 193
 - SCons.SConf.createIncludesFromHeaders (*function*), 194
 - SCons.SConf.NeedConfigHBuilder (*function*), 193
 - SCons.SConf.SConf (*function*), 193
 - SCons.SConf.SConfBase (*class*), 203–206
 - SCons.SConf.SConfBuildInfo (*class*), 199–201
 - SCons.SConf.SConfBuildTask (*class*), 202–203
 - SCons.SConf.SConfError (*class*), 196–197
 - SCons.SConf.SConfWarning (*class*), 195–196
 - SCons.SConf.SetBuildType (*function*), 193
 - SCons.SConf.SetCacheMode (*function*), 193
 - SCons.SConf.SetProgressDisplay (*function*), 193
 - SCons.SConf.Streamer (*class*), 201–202
- SCons.SConsign (*module*), 209–215
 - SCons.SConsign.Base (*class*), 211–212
 - SCons.SConsign.corrupt_dblite_warning (*function*), 209
 - SCons.SConsign.DB (*class*), 212–213, 215
 - SCons.SConsign.Dir (*class*), 213
 - SCons.SConsign.DirFile (*class*), 213–215
 - SCons.SConsign.File (*function*), 209
 - SCons.SConsign.Get_DataBase (*function*), 209
 - SCons.SConsign.Reset (*function*), 209
 - SCons.SConsign.SConsignEntry (*class*), 209–211
 - SCons.SConsign.write (*function*), 209
- SCons.Script (*module*)
 - SCons.Script.HelpFunction (*function*), 257
 - SCons.Script.Options (*function*), 257
 - SCons.Script.TargetList (*class*), 264–265
 - SCons.Script.Variables (*function*), 257
- SCons.Script (*package*), 257–265
 - SCons.Script.Interactive (*module*), 266–268
 - SCons.Script.Main (*module*), 269–282
 - SCons.Script.SConscript' (*module*), 283–288
- SCons.Subst (*module*), 289–299
- SCons.Taskmaster (*module*), 300–310
 - SCons.Taskmaster.AlwaysTask (*class*), 306–307
 - SCons.Taskmaster.dump_stats (*function*), 300

- SCons.Taskmaster.find_cycle (*function*), SCons.Conftest.CheckCC (*function*), 34
 300 SCons.Conftest.CheckCXX (*function*), 34
 SCons.Taskmaster.OutOfDateTask (*class*), SCons.Conftest.CheckDeclaration (*function*),
 307–308 36
 SCons.Taskmaster.Stats (*class*), 301–302 SCons.Conftest.CheckFunc (*function*), 35
 SCons.Taskmaster.Task (*class*), 302–306 SCons.Conftest.CheckHeader (*function*), 35
 SCons.Taskmaster.Taskmaster (*class*), 308 SCons.Conftest.CheckLib (*function*), 37
 310 SCons.Conftest.CheckProg (*function*), 37
 SCons.Util (*module*), 311–339 SCons.Conftest.CheckSHCC (*function*), 34
 SCons.Variables (*package*), 339–342 SCons.Conftest.CheckSHCXX (*function*), 35
 SCons.Variables.BoolVariable' (*module*), SCons.Conftest.CheckType (*function*), 35
 343 SCons.Conftest.CheckTypeSize (*function*), 36
 SCons.Variables.EnumVariable' (*module*), SCons.cpp.CPP_to_Python (*function*), 386
 344 SCons.cpp.CPP_to_Python_Ops_Sub (*function*), 386
 SCons.Variables.ListVariable' (*module*),
 345 SCons.cpp.DumbPreProcessor (*class*), 392–393
 SCons.Variables.PackageVariable' (*module*), SCons.cpp.FunctionEvaluator (*class*), 386–387
 346 SCons.cpp.FunctionEvaluator.__call__ (*method*),
 SCons.Variables.PathVariable' (*module*), 387
 347 SCons.cpp.PreProcessor (*class*), 387–392
 SCons.Variables.Variables (*class*), 339– SCons.cpp.PreProcessor.__call__ (*method*),
 342 388
 SCons.Warnings (*module*), 348–385 SCons.cpp.PreProcessor.all_include (*method*),
 SCons.CacheDir.CacheDir (*class*), 31–33 388
 SCons.CacheDir.CacheDir.CacheDebug (*method*), SCons.cpp.PreProcessor.do_define (*method*),
 32 388
 SCons.CacheDir.CacheDir.cachepath (*method*), SCons.cpp.PreProcessor.do_elif (*method*),
 32 388
 SCons.CacheDir.CacheDir.is_enabled (*method*), SCons.cpp.PreProcessor.do_else (*method*),
 32 388
 SCons.CacheDir.CacheDir.is_readonly (*method*), SCons.cpp.PreProcessor.do_endif (*method*),
 32 388
 SCons.CacheDir.CacheDir.push (*method*), SCons.cpp.PreProcessor.do_if (*method*),
 32 388
 SCons.CacheDir.CacheDir.push_if_forced (*method*), SCons.cpp.PreProcessor.do_ifdef (*method*),
 33 389
 SCons.CacheDir.CacheDir.retrieve (*method*), SCons.cpp.PreProcessor.do_ifndef (*method*),
 32 389
 SCons.CacheDir.CachePushFunc (*function*), 31 SCons.cpp.PreProcessor.do_import (*method*),
 SCons.CacheDir.CacheRetrieveFunc (*function*), 389
 31 SCons.cpp.PreProcessor.do_include (*method*),
 SCons.CacheDir.CacheRetrieveString (*function*), 389
 31 SCons.cpp.PreProcessor.do_nothing (*method*),
 SCons.Conftest.CheckBuilder (*function*), 34 389

- SCons.cpp.PreProcessor.do_undef (*method*), 389
 SCons.cpp.PreProcessor.eval_expression (*method*), 389
 SCons.cpp.PreProcessor.finalize_result (*method*), 390
 SCons.cpp.PreProcessor.find_include_file (*method*), 390
 SCons.cpp.PreProcessor.initialize_result (*method*), 390
 SCons.cpp.PreProcessor.process_contents (*method*), 390
 SCons.cpp.PreProcessor.read_file (*method*), 390
 SCons.cpp.PreProcessor.resolve_include (*method*), 390
 SCons.cpp.PreProcessor.restore (*method*), 390
 SCons.cpp.PreProcessor.save (*method*), 390
 SCons.cpp.PreProcessor.scons_current_file (*method*), 391
 SCons.cpp.PreProcessor.start_handling_include (*method*), 391
 SCons.cpp.PreProcessor.stop_handling_include (*method*), 391
 SCons.cpp.PreProcessor.tupleize (*method*), 391
 SCons.Defaults.chmod_func (*function*), 41
 SCons.Defaults.chmod_strfunc (*function*), 41
 SCons.Defaults.copy_func (*function*), 41
 SCons.Defaults.DefaultEnvironment (*function*), 41
 SCons.Defaults.delete_func (*function*), 42
 SCons.Defaults.delete_strfunc (*function*), 42
 SCons.Defaults.get_paths_str (*function*), 41
 SCons.Defaults.mkdir_func (*function*), 42
 SCons.Defaults.move_func (*function*), 42
 SCons.Defaults.NullCmdGenerator (*class*), 43–44
 SCons.Defaults.NullCmdGenerator.__call__ (*method*), 44
 SCons.Defaults.processDefines (*function*), 42
 SCons.Defaults.SharedFlagChecker (*function*), 41
 SCons.Defaults.SharedObjectEmitter (*function*), 41
 SCons.Defaults.StaticObjectEmitter (*function*), 41
 SCons.Defaults.touch_func (*function*), 42
 SCons.Defaults.Variable_Method_Caller (*class*), 44–45
 SCons.Defaults.Variable_Method_Caller.__call__ (*method*), 45
 SCons.Errors.BuildError (*class*), 76–78
 SCons.Errors.convert_to_BuildError (*function*), 76
 SCons.Errors.EnvironmentError (*class*), 80–81
 SCons.Errors.ExplicitExit (*class*), 82–83
 SCons.Errors.InternalError (*class*), 78–79
 SCons.Errors.MSVCErrors (*class*), 81–82
 SCons.Errors.StopError (*class*), 79–80
 SCons.Errors.UserError (*class*), 79
 SCons.Node.Annotate (*function*), 110
 SCons.Node.BuildInfoBase (*class*), 115–116
 SCons.Node.BuildInfoBase.__getstate__ (*method*), 115
 SCons.Node.BuildInfoBase.__setstate__ (*method*), 115
 SCons.Node.BuildInfoBase.merge (*method*), 115
 SCons.Node.changed_since_last_build_alias (*function*), 112
 SCons.Node.changed_since_last_build_entry (*function*), 112
 SCons.Node.changed_since_last_build_node (*function*), 111
 SCons.Node.changed_since_last_build_python (*function*), 112
 SCons.Node.changed_since_last_build_state_changed (*function*), 112
 SCons.Node.classname (*function*), 110
 SCons.Node.decide_source (*function*), 112
 SCons.Node.decide_target (*function*), 112
 SCons.Node.do_nothing (*function*), 112
 SCons.Node.exists_always (*function*), 110
 SCons.Node.exists_base (*function*), 111
 SCons.Node.exists_entry (*function*), 111

- SCons.Node.exists_file (*function*), 111
- SCons.Node.exists_none (*function*), 110
- SCons.Node.get_children (*function*), 112
- SCons.Node.get_contents_dir (*function*), 111
- SCons.Node.get_contents_entry (*function*), 111
- SCons.Node.get_contents_file (*function*), 111
- SCons.Node.get_contents_none (*function*), 111
- SCons.Node.ignore_cycle (*function*), 112
- SCons.Node.is_derived_node (*function*), 110
- SCons.Node.is_derived_none (*function*), 110
- SCons.Node.Node (*class*), 116–130
 - SCons.Node.Node.add_dependency (*method*), 117
 - SCons.Node.Node.add_ignore (*method*), 117
 - SCons.Node.Node.add_prerequisite (*method*), 117
 - SCons.Node.Node.add_source (*method*), 117
 - SCons.Node.Node.add_to_implicit (*method*), 117
 - SCons.Node.Node.add_to_waiting_parents (*method*), 117
 - SCons.Node.Node.add_to_waiting_s_e (*method*), 118
 - SCons.Node.Node.add_wkid (*method*), 118
 - SCons.Node.Node.all_children (*method*), 118
 - SCons.Node.Node.alter_targets (*method*), 118
 - SCons.Node.Node.build (*method*), 118
 - SCons.Node.Node.builder_set (*method*), 118
 - SCons.Node.Node.built (*method*), 118
 - SCons.Node.Node.changed (*method*), 119
 - SCons.Node.Node.children (*method*), 119
 - SCons.Node.Node.children_are_up_to_date (*method*), 119
 - SCons.Node.Node.clear (*method*), 119
 - SCons.Node.Node.clear_memoized_values (*method*), 120
 - SCons.Node.Node.Decider (*method*), 117
 - SCons.Node.Node.del_binfo (*method*), 120
 - SCons.Node.Node.disambiguate (*method*), 120
 - SCons.Node.Node.env_set (*method*), 120
 - SCons.Node.Node.executor_cleanup (*method*), 120
 - SCons.Node.Node.exists (*method*), 120
 - SCons.Node.Node.explain (*method*), 120
 - SCons.Node.Node.for_signature (*method*), 120
 - SCons.Node.Node.get_abspath (*method*), 120
 - SCons.Node.Node.get_binfo (*method*), 121
 - SCons.Node.Node.get_build_env (*method*), 121
 - SCons.Node.Node.get_build_scanner_path (*method*), 121
 - SCons.Node.Node.get_builder (*method*), 121
 - SCons.Node.Node.get_cachedir_csig (*method*), 121
 - SCons.Node.Node.get_contents (*method*), 121
 - SCons.Node.Node.get_csig (*method*), 121
 - SCons.Node.Node.get_env (*method*), 121
 - SCons.Node.Node.get_env_scanner (*method*), 122
 - SCons.Node.Node.get_executor (*method*), 122
 - SCons.Node.Node.get_found_includes (*method*), 122
 - SCons.Node.Node.get_implicit_deps (*method*), 122
 - SCons.Node.Node.get_ninfo (*method*), 122
 - SCons.Node.Node.get_source_scanner (*method*), 122
 - SCons.Node.Node.get_state (*method*), 122
 - SCons.Node.Node.get_stored_implicit (*method*), 123
 - SCons.Node.Node.get_stored_info (*method*), 123
 - SCons.Node.Node.get_string (*method*), 123
 - SCons.Node.Node.get_subst_proxy (*method*), 123
 - SCons.Node.Node.get_suffix (*method*), 123
 - SCons.Node.Node.get_target_scanner (*method*), 123

- 123
- SCons.Node.Node.GetTag (*method*), 117
- SCons.Node.Node.has_builder (*method*), 123, 125
- SCons.Node.Node.has_explicit_builder (*method*), 128
- 124
- SCons.Node.Node.is_derived (*method*), 124
- SCons.Node.Node.is_literal (*method*), 124
- SCons.Node.Node.is_up_to_date (*method*), 124
- SCons.Node.Node.make_ready (*method*), 124
- SCons.Node.Node.missing (*method*), 125
- SCons.Node.Node.new_binfo (*method*), 125
- SCons.Node.Node.new_ninfo (*method*), 125
- SCons.Node.Node.postprocess (*method*), 125
- SCons.Node.Node.prepare (*method*), 125
- SCons.Node.Node.push_to_cache (*method*), 126
- SCons.Node.Node.release_target_info (*method*), 126
- SCons.Node.Node.remove (*method*), 126
- SCons.Node.Node.render_include_tree (*method*), 126
- SCons.Node.Node.reset_executor (*method*), 127
- SCons.Node.Node.retrieve_from_cache (*method*), 127
- SCons.Node.Node.rexists (*method*), 127
- SCons.Node.Node.scan (*method*), 127
- SCons.Node.Node.scanner_key (*method*), 127
- SCons.Node.Node.select_scanner (*method*), 127
- SCons.Node.Node.set_always_build (*method*), 127
- SCons.Node.Node.set_executor (*method*), 128
- SCons.Node.Node.set_explicit (*method*), 128
- SCons.Node.Node.set_nocache (*method*), 128
- SCons.Node.Node.set_noclean (*method*), 128
- SCons.Node.Node.set_precious (*method*), 128
- SCons.Node.Node.set_pseudo (*method*), 128
- SCons.Node.Node.set_specific_source (*method*), 128
- SCons.Node.Node.set_state (*method*), 128
- SCons.Node.Node.Tag (*method*), 117
- SCons.Node.Node.visited (*method*), 128
- SCons.Node.NodeInfoBase (*class*), 113–115
- SCons.Node.NodeInfoBase.__getstate__ (*method*), 114
- SCons.Node.NodeInfoBase.__setstate__ (*method*), 114
- SCons.Node.NodeInfoBase.convert (*method*), 114
- SCons.Node.NodeInfoBase.format (*method*), 114
- SCons.Node.NodeInfoBase.merge (*method*), 114
- SCons.Node.NodeInfoBase.update (*method*), 114
- SCons.Node.NodeList (*class*), 130–131
- SCons.Node.rexists_base (*function*), 111
- SCons.Node.rexists_node (*function*), 111
- SCons.Node.rexists_none (*function*), 111
- SCons.Node.store_info_file (*function*), 112
- SCons.Node.store_info_pass (*function*), 112
- SCons.Node.target_from_source_base (*function*), 111
- SCons.Node.target_from_source_none (*function*), 111
- SCons.Node.Walker (*class*), 131–132
- SCons.Node.Walker.get_next (*method*), 132
- SCons.Node.Walker.is_done (*method*), 132
- SCons.Scanner.Dir.DirEntryScanner (*function*), 239
- SCons.Scanner.Dir.DirScanner (*function*), 239
- SCons.Scanner.Dir.do_not_scan (*function*), 239
- SCons.Scanner.Dir.only_dirs (*function*), 239
- SCons.Scanner.Dir.scan_in_memory (*function*), 239
- SCons.Scanner.Dir.scan_on_disk (*function*), 239
- SCons.Script.Interactive.interact (*function*), 266

- SCons.Script.Interactive.SConsInteractiveCmd (class), 266–268
 SCons.Script.Interactive.SConsInteractiveCmd.do (method), 267
 SCons.Script.Interactive.SConsInteractiveCmd.do_ (method), 267
 SCons.Script.Interactive.SConsInteractiveCmd.do_ (method), 267
 SCons.Script.Interactive.SConsInteractiveCmd.do_ (method), 267
 SCons.Script.Interactive.SConsInteractiveCmd.do_ (method), 267
 SCons.Script.Interactive.SConsInteractiveCmd.do_ (method), 267
 SCons.Script.Interactive.SConsInteractiveCmd.do_ (method), 267
 SCons.Script.Interactive.SConsInteractiveCmd.do_ (method), 267
 SCons.Script.Interactive.SConsInteractiveCmd.do_ (method), 267
 SCons.Subst.CmdStringHolder (class), 293–294
 SCons.Subst.CmdStringHolder.escape (method), 293
 SCons.Subst.CmdStringHolder.is_literal (method), 293
 SCons.Subst.escape_list (function), 289
 SCons.Subst.Literal (class), 291–292
 SCons.Subst.Literal.__eq__ (method), 291
 SCons.Subst.Literal.__neq__ (method), 291
 SCons.Subst.Literal.escape (method), 291
 SCons.Subst.Literal.for_signature (method), 291
 SCons.Subst.Literal.is_literal (method), 291
 SCons.Subst.NLWrapper (class), 294–295
 SCons.Subst.NullNodeList (class), 298–299
 SCons.Subst.quote_spaces (function), 289
 SCons.Subst.raise_exception (function), 289
 SCons.Subst.scons_subst (function), 289
 SCons.Subst.scons_subst_list (function), 290
 SCons.Subst.scons_subst_once (function), 290
 SCons.Subst.SetAllowableExceptions (function), 289
 SCons.Subst.SpecialAttrWrapper (class), 292–293
 SCons.Subst.SpecialAttrWrapper.escape (method), 292
 SCons.Subst.SpecialAttrWrapper.for_signature (method), 292
 SCons.Subst.SpecialAttrWrapper.is_literal (method), 292
 SCons.Subst.subst_dict (function), 289
 SCons.Subst.Target_or_Source (class), 297–298
 SCons.Subst.Target_or_Source.__getattr__ (method), 297
 SCons.Subst.Targets_or_Sources (class), 295–297
 SCons.Subst.Targets_or_Sources.__getattr__ (method), 296
 SCons.Util._NoError (class), 324–325
 SCons.Util.AddMethod (function), 317
 SCons.Util.AddPathIfNotExists (function), 315
 SCons.Util.adjustixes (function), 316
 SCons.Util.AppendPath (function), 315
 SCons.Util.case_sensitive_suffixes (function), 316
 SCons.Util.CLVar (class), 327–329
 SCons.Util.CLVar.__coerce__ (method), 328
 SCons.Util.cmp (function), 318
 SCons.Util.containsAll (function), 311
 SCons.Util.containsAny (function), 311
 SCons.Util.containsOnly (function), 311
 SCons.Util.Delegate (class), 323–324
 SCons.Util.Delegate.__get__ (method), 324
 SCons.Util.dictify (function), 311
 SCons.Util.DisplayEngine (class), 321–322
 SCons.Util.DisplayEngine.__call__ (method), 321
 SCons.Util.DisplayEngine.set_mode (method), 321
 SCons.Util.do_flatten (function), 313
 SCons.Util.flatten (function), 313
 SCons.Util.flatten_sequence (function), 313
 SCons.Util.get_environment_var (function), 311
 SCons.Util.get_native_path (function), 316
 SCons.Util.IDX (function), 312
 SCons.Util.is_Dict (function), 312
 SCons.Util.is_List (function), 312
 SCons.Util.is_Scalar (function), 313

- SCons.Util.is_Sequence (*function*), 313
- SCons.Util.is_String (*function*), 313
- SCons.Util.is_Tuple (*function*), 313
- SCons.Util.logical_lines (*function*), 317
- SCons.Util.LogicalLines (*class*), 331–332
 - SCons.Util.LogicalLines.readlines (*method*), 331
- SCons.Util.make_path_relative (*function*), 317
- SCons.Util.MD5collect (*function*), 317
- SCons.Util.MD5filesignature (*function*), 317
- SCons.Util.MD5signature (*function*), 317
- SCons.Util.NodeList (*class*), 319–321
 - SCons.Util.NodeList.__bool__ (*method*), 320
 - SCons.Util.NodeList.__call__ (*method*), 320
 - SCons.Util.NodeList.__getattr__ (*method*), 320
 - SCons.Util.NodeList.__nonzero__ (*method*), 320
- SCons.Util.Null (*class*), 336–338
 - SCons.Util.Null.__bool__ (*method*), 337
 - SCons.Util.Null.__call__ (*method*), 337
 - SCons.Util.Null.__getattr__ (*method*), 337
 - SCons.Util.Null.__nonzero__ (*method*), 337
- SCons.Util.NullSeq (*class*), 338–339
 - SCons.Util.NullSeq.__delitem__ (*method*), 338
 - SCons.Util.NullSeq.__getitem__ (*method*), 338
 - SCons.Util.NullSeq.__iter__ (*method*), 338
 - SCons.Util.NullSeq.__len__ (*method*), 338
 - SCons.Util.NullSeq.__setitem__ (*method*), 338
- SCons.Util.OrderedDict (*class*), 329–330
- SCons.Util.PlainWindowsError (*class*), 325–327
- SCons.Util.PrependPath (*function*), 314
- SCons.Util.print_tree (*function*), 312
- SCons.Util.Proxy (*class*), 322–323
 - SCons.Util.Proxy.__eq__ (*method*), 323
 - SCons.Util.Proxy.__getattr__ (*method*), 322
- SCons.Util.Proxy.get (*method*), 323
- SCons.Util.RegGetValue (*function*), 314
- SCons.Util.RegOpenKeyEx (*function*), 314
- SCons.Util.RenameFunction (*function*), 317
- SCons.Util.render_tree (*function*), 312
- SCons.Util.rightmost_separator (*function*), 311
- SCons.Util.Selector (*class*), 330–331
 - SCons.Util.Selector.__call__ (*method*), 330
- SCons.Util.semi_deepcopy (*function*), 314
- SCons.Util.semi_deepcopy_dict (*function*), 314
- SCons.Util.silent_intern (*function*), 318
- SCons.Util.Split (*function*), 316
- SCons.Util.splitext (*function*), 311
- SCons.Util.to_bytes (*function*), 318
- SCons.Util.to_str (*function*), 318
- SCons.Util.to_String (*function*), 314
- SCons.Util.to_String_for_signature (*function*), 314
- SCons.Util.to_String_for_subst (*function*), 314
- SCons.Util.Unbuffered (*class*), 335–336
 - SCons.Util.Unbuffered.__getattr__ (*method*), 336
 - SCons.Util.Unbuffered.write (*method*), 336
- SCons.Util.unique (*function*), 316
- SCons.Util.UniqueList (*class*), 332–335
- SCons.Util.uniquer (*function*), 316
- SCons.Util.uniquer_hashables (*function*), 316
- SCons.Util.updrive (*function*), 311
- SCons.Util.WhereIs (*function*), 314
- SCons.Warnings.CacheVersionWarning (*class*), 352–353
- SCons.Warnings.CacheWriteErrorWarning (*class*), 353–354
- SCons.Warnings.CorruptSConsignWarning (*class*), 354–355
- SCons.Warnings.DependencyWarning (*class*), 355–356
- SCons.Warnings.DeprecatedBuildDirWarning (*class*), 376–377
- SCons.Warnings.DeprecatedBuilderKeywordsWarning (*class*), 384–385
- SCons.Warnings.DeprecatedCopyWarning (*class*), 384–385

- 378–379
- SCons.Warnings.DeprecatedDebugOptionsWarning (class), 382–383
- SCons.Warnings.DeprecatedOptionsWarning (class), 379–380
- SCons.Warnings.DeprecatedSigModuleWarning (class), 383–384
- SCons.Warnings.DeprecatedSourceCodeWarning (class), 375–376
- SCons.Warnings.DeprecatedSourceSignaturesWarning (class), 380–381
- SCons.Warnings.DeprecatedTargetSignaturesWarning (class), 381–382
- SCons.Warnings.DeprecatedWarning (class), 372–373
- SCons.Warnings.DevelopmentVersionWarning (class), 356
- SCons.Warnings.DuplicateEnvironmentWarning (class), 356–357
- SCons.Warnings.enableWarningClass (function), 348
- SCons.Warnings.FortranCxxMixWarning (class), 370–371
- SCons.Warnings.FutureDeprecatedWarning (class), 371–372
- SCons.Warnings.FutureReservedVariableWarning (class), 357–358
- SCons.Warnings.LinkWarning (class), 358–359
- SCons.Warnings.MandatoryDeprecatedWarning (class), 373–374
- SCons.Warnings.MisleadingKeywordsWarning (class), 359–360
- SCons.Warnings.MissingSConscriptWarning (class), 360–361
- SCons.Warnings.NoMD5ModuleWarning (class), 361–362
- SCons.Warnings.NoMetaclassSupportWarning (class), 362–363
- SCons.Warnings.NoObjectCountWarning (class), 363–364
- SCons.Warnings.NoParallelSupportWarning (class), 364–365
- SCons.Warnings.process_warn_strings (function), 348
- SCons.Warnings.PythonVersionWarning (class), 374–375
- SCons.Warnings.ReservedVariableWarning (class), 365–366
- SCons.Warnings.StackSizeWarning (class), 366–367
- SCons.Warnings.suppressWarningClass (function), 348
- SCons.Warnings.TargetNotBuiltWarning (class), 351–352
- SCons.Warnings.TaskmasterNeedsExecuteWarning (class), 377–378
- SCons.Warnings.VisualCMissingWarning (class), 367–368
- SCons.Warnings.VisualStudioMissingWarning (class), 369–370
- SCons.Warnings.VisualVersionMismatch (class), 368–369
- SCons.Warnings.warn (function), 348
- SCons.Warnings.Warning (class), 349–350
- SCons.Warnings.warningAsException (function), 348
- SCons.Warnings.WarningOnByDefault (class), 350–351